MELAVANJUR BRANCH & ATM - INTERIOR, FURNISHING, ELECTRICAL, DATA CABLING AND AIR CONDITIONING WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)

Α	MAIN WORKS	Amount(Rs.)				
1	INTERIOR WORK					
2	FIXTURES WORK					
2	BRANCH ELECTRICAL WORK					
3	BRANCH & ATM DATA CABLING WORK					
4	BRANCH A/C WORK					
5	ATM INTERIOR WORK					
5	ATM ELECTRICAL WORK					
6	ATM A/C WORK					
	TOTAL					
(RUPEES ONLY)						
ALL RATES ARE INCLUSIVE OF 18% GST						

MELAVANJUR BRANCH - INTERIOR, FURNISHING WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)

	BILL OF QUA	NTITIES			
S NO	PARTICULARS	QTY	UNIT	RATE(Rs)	AMOUNT (Rs)
1	PARTITIONS				
а	Full & Half Blocked Partition				
	Providing full height double skin fully blocked partitions upto RCC ceiling ht using aluminium plain rectangular sections of 2 1/2"x 1 1/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (Bank approved colors) with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Black) at base and a 100mm wide border (Brown) at the top including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.(Record, dining,strong room,ups room)	142.00	Sft		
b	Partly Glazed Partition Manager & Server Cabin:				
	Providing full height double skin partly glazed partitions using aluminium sections of 2 1/2"x11/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Black) at base and a 100mm wide border (Brown) at the top and shall include the cost of providing 8mm tk. plain float glass with etching Designe to suitable sizes, including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	245.00	Sft		

С	Low Height Partition			
	Providing low height double skin partitions along with Counter Divider partition wicket gate of the same type using aluminium sections of 2 1/2" x 1 1/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (bank approved laminates only) with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Black) at base& including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	45.00	Sft	
d	CASH PARTITIONS (BULK CASH)			
	Providing full height upto 7' 3" from floor level, semi grilled plywood partition for cash cabin, using aluminium sections of 2 1/2" x 1 1/2" size spaced at 2'0" c/c maximum for the frame work , fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (bank approved laminates only) with necessary grooves of 1mm thick, The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Black) at base and a 100mm wide border (Brown) shade at the top and shall include the cost of providing ornamental aluminium grille to suitable sizes, including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	53.00	Sft	
е	CASH CABIN TOP ALUMINIUM GRIL			
	Providing and fixing in position readymade anodized alumium grill of approved design and quality fixed with continuous steam beech / teak wood beads of approved shape (finished 35 x 25 mm) all round polished (in cash cabin)	42.00	Sft	

2	FRONT COUNTER 12MM GLASS			
	Providing front glazing for cash cabin above counter from 3'9" to 7'0" height, and inbetween banking counters using 12mm thick plain glass including edge polishing & etching.	39.00	Sft	
3	DOORS			
a)	ENTRANCE DOOR			
	To be made out of 12mm thk glass with etching as per design. The glass with etching has to be fixed with top & sides rails of $2\frac{1}{2}$ "x4" and bottom rails of size $2\frac{1}{2}$ " x 6". The rails to be made out of beech wood The door shall have 18" long s/s handle (as shown in the drawing) and also double action floor spring of specified make. The door frame to be mde out of 5"x $2\frac{1}{2}$ " best quality beech wood. The etching in glass pattern to be done strictly following instructions of the Architect or following the drawing attached. The exposed wood of frames, rails to be polished as per instructions of the architect. NB: The size of the door may slightly vary as per site conditions for matching the elevation on the fixed glazing. All exposed edges of the glass to be machine polished. The rails are to be made as per the design of the architect. Bank Entrance door (4'0" X 7'0")	42.00	Sft	
b)	FLUSH DOORS			
i)	Door (3'0" x 7'0")	1.00	No	
ii)	ups - (2'6" x 5'0")	1.00	No	
c)	SEMIGLAZED DOORS			
i)	Manager (3'0" x 7'0")	1.00	No	
ii)	Manager & B.cash (2'6"x 7'0")	2.00	No	

d)	WICKET DOOR			
i)	Wicket Door (3'0"x3'0")	1.00	No	
4	SERVER ROOM WORKING COUNTER			
	Working top will be 2' - 6" ht to be provided as per instructions given by the architect. Rest of the working counter as per specifications in fabricated out of 18mm ply for top, sides and 6mm ply for back. The work station will have drawer units, keyboard tray, cpu platforms, leg rest etc., and drawings attached in tender and specifications.All clarificationss to be taken before quoting the prices and no extra cost shall be entertained at the time of execution.The entire work as per the instruction of the Architect at the time of execution.	4.00	Rft	
5	Cheque drop box/ Complaint			
	Providing cheque drop box/ Complaint/Suggestion 1'6" length, 0'9" wide and 1'6" height with 19mm tk. Plywood and lined with 1mm tk. Laminate(Fusion Maple - Wood finish) for top & exposed sides. Exposed edges of plywood shall be fixed with teak wood beading suitably polished and the back side shall be covered with 6mm tk. plywood. The inner sides shall be painted with two coats of enamel paint over acoat of primer & two coats of putty.	1.00	No	
6	Vertical Blinds:		•	
	Providing and fixing 100mm wide Vista Make or equavalent vertical blinds of approved make quality and colour shade and pattern. Rate shall include necessary scotch guard treatment on both side. The overlaps should be uniform and adequate	61.00	Sft	

7	FALSE CEILING (GYPBOARD)				
	Providing & fixing suspended gypboard false	150.00	Sft		
	ceiling, which includes Providing & fixing G.I				
	perimeter channels of size 27mm, 0.5mm thk				
	having one flange of 20mm & another flange				
	of 20mm along with perimeter of the ceiling,				
	screws fixed to brick wall/partitions with the				
	help of rawl plugs & Screws. Then				
	suspending G.I intermediate channels of size				
	45mm, 0.9mm thk with two flanges of 15mm				
	each from the soffit at 1200mm centres with				
	stell G.I hanger of width 25mm,0.5mm thk				
	fixed to soffit with G.I. cleat & steel expansion				
	fasteners. Ceiling section of 0.5mm thickness				
	having knurled wedge of 51.5mm and two				
	flanges of 26mm each with leafs of 10.5mm				
	are then fixed to the intermediate channel with				
	the help of connecting clips and in direction				
	perpendicular to the intermediate channel at				
	450mm centres. 12.5mm tapered edge				
	gypboard is then screwed fixed to ceiling				
	section with 25mm dry wall screws at 230mm				
	with requiste jointing compound, paper tapes,				
	finisher and premier suitable for Gypsum				
	plaster boards. The entire work shall be				
	finished as per instructions of the Architect.				
	And also finished with two or more coats of				
	acrylic emulsion paint of approved shade and				
	make. No extra cost shall be entertained in				
	completing the entire work in all respect.				
	Total Interior Works				
				say	

MELAVANJUR BRANCH - INTERIOR & FIXTURES WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)								
BILL OF QUANTITIES								
S NO	PARTICULARS	QTY	UNIT	RATE(Rs)	AMOUNT (Rs)			
1	TABLE							
	Manager table as per drawing done with structure made of 18mm plywood with drawer unit comprising of 1 drawer, 1 filing shelf fixed with pull out door (box type hinges), locks, D type handles and all accessories to be provided.All drawers, corners, doors to be finished with beach wood lipping/beading, melamine polished., push in type keyboard, all drawers and key board on telescopic channels. All exposed edges Teak/beach wood beadings is finished with melamine polished and inside laminated with 0.8mm laminate. The table to be topped with 12mm float glass with beveling on all four sides. The side unit is provided with two drawers and filing shelf with two pull out doors, finished in same manner.CPU platform with foot rest to be provided. wall to table gap to closed with plywood.							
a) 2	Branch Manager 6'0"x2'6" FRONT COUNTER AND BULK CASH COUNTER	1.00	No					
	Providing and assembling banking counter and Cash, single window counter unit as shown in drawing of size not less than 5'0" x 2'6" x 2'6" or as per site requirements, with regular drawer - 1 No. and shelves on one side, a keyboard drawer at centre and a platform for CPU onto other side for each counter as shown in drawing using 19mm thick commerical plywood lined with 1.0mm thick laminate(Bank approved colors) Cash and single window with 12mm thick glass (to be strictly followed) in front side for all the exposed surfaces, including providing skirting 4" wide with 1.0mm thk laminate (Black) on both sides to match with the adjoining partition and 4" wide border at top with 1.0mm thk laminate (Brown). The customer top at 3'9"ht of 1'3" width & working counter top of 2'6" width to be fixed with 19mm Granite top (Jet Black/approved) with double nosing @ front side as shown in the drawing							
	All the plywood edges shall have teak wood lipping and all inner surfaces shall be painted with two coats of enamel paint over a coat of primer & two coats of putty. The rate shall include providing, fixing & painting a foot rest using first class seasoned country frame of size 3" x 1 1/2".Necessary hardware fittings like draw sliders, hinges, multipurpose locks with set keys, handles shall be provided.							
		5.00	Rft					
i)	Bulk cash	5.00	N 11					

2	STORAGE				
	Providing and fixing filing cabinet in manager cabin for a height of 2'6" & 7' ht. made of 18mm plywood structure comprising of suitable intermediate horizontal racks with open type doors, finished with 1mm laminate and teak wood beadings neatly melamine polished and inside finished with 0.8mm laminate with locks, handles and all accessories				
i)	Manager	7.50	Sft		
ii)	B.Cash	10.00	Sft		
iii)	Hall Sc	107.00	Sft		
3	WRITING LEDGE WITH 12mm GLASS TOP				
	Made out 18 mm ply as per design and exposed external surfaces to be laminated and internal surface to be painted with top provided 12 mm thk etched glass with machine polished edges . The entire work has to be done to the satisfaction of the architect. The design given has to be strictly followed	1.00	No		
4	NOTICE BOARD				
	Providing and fixing of the soft board on the customer lobby made of jolly board with a fabric of B / R @ 200 / - per meter .The design and the entire work has to be done as per the instructions of the architect a the time of execution	12.00	Sft		
5	ROLLING SHUTTER COVER BOX	-			
	Supplying & fixing of rolling shutter box using 19mm thk plywood with adequate support at the ends and finished with lamination of approved make and colour etc., complete	58.00	sft		
	Total Interior Works				
				say	

	MELAVANJUR BRANCH - ELECTRICAL WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)							
	BILL OF QUANTITIES							
SI.No	Description Of Work	Unit	Qty	Rate	Amount			
Α	Supply&Installation&Commisioing of the following							
1	MAIN DB (8WAY VTPN DB)							
	Three Phase, Vertical Distribution board							
	with nuetral bar,earth bar,cables ties,top and							
	bottom removable gland plate and with necessary							
	adopter boxes if any. The DB should be IP 42 metallic							
	double door with provisioin of MCB etc as							
	required including cuting of wall and plastering the							
	same with neat finish.It comprising as flolows:-							
	Incomer :							
	100A TPN MCCB -1Nos							
	Outgoings:							
	63A TP MCB -4Nos							
	32/25/20A SP MCBs- 5Nos	Set	1					
В	Supply&Installation&Commisioing of the following							
1	LIGHTING DB(4WAY TPN DB)							
	Three Phase, Phase Segrigated Distribution board							
	with nuetral bar,earth bar,cables ties,top and							
	bottom removable gland plate and with necessary							
	adopter boxes if any. The DB should be IP 42 metallic							
	double door with provisioin of MCB etc as							
	required including cuting of wall and plastering the							
	same with neat finish.It comprising as flolows:-							
	Incomer : 40A TPN MCB							
	Outgoings:							
	10/6A SP MCBs- 12Nos	Set	1					
2	POWER DB(4WAY TPN DB)							
	Three Phase, Phase Segrigated Distribution board							
	with nuetral bar,earth bar,cables ties,top and							
	bottom removable gland plate and with necessary							
	adopter boxes if any. The DB should be IP 42 metallic							
	double door with provisioin of MCB&ELCB etc as							
	required including cuting of wall and plastering the							
	same with neat finish.It comprising as flolows:-							
	Incomer : 63A TPN MCB							
	Outgoings:				ļ			
	32/25/20A SP MCBs- 12Nos	Set	1					
3	COMPUTER DB(8WAY SPN DB)							
	12 Way SPN Distribution board							
—	with nuetral bar,earth bar,cables ties,top and							
	bottom removable gland plate and with necessary		-	h				
	adopter boxes if any.The DB should be IP 42 metallic							
	double door with provisioin of MCB&ELCB etc as				1			
	required including cuting of wall and plastering the							
	same with neat finish. It comprising as flolows:-							
	Incomer : 40ADP MCB				1			
	Outgoings:				1			
	10A SP MCBs- 6Nos	Set	2		1			

Г

				Ι		1
4	Supply&Installation of the following with the necessary					
	enclosure and adopter boxes if necessary,		-		4	
	a)63A TPN MCB	Set	2			
	b)63A DP MCB	Set	4			
5	Supply&Installation of 32A Metal Clad Socket with					
	top in a specified company manufactured box with					
	suitable rating MCB for AIR CONDITIONS	set	7			
6	Supply&Installation of 63A 4Pole Change over switch	set	1			
7	Supply and Fixing for 63A Phase Selector switch with					
	enclosure and adopter boxes if necessary,	set	2			
				1		
С	LT CABLES			1		
1	Supply&Laying of the following cables in built up					
⊢ <u>∸</u>	trenches,on wall, or in the ground as per the case may be,				1	
	with proper clamping with necessary fixing materials etc.			1		
	Installing testing&commision of 1100V grede UG					
					-	
	cable as per IS 7098/1554 (Finolex/Universal)	N (1+1-	20			
	3.5Corex50Sqmm Aluminium Armored cable Main DB	Mtr	38			
	3.5Corex35Sqmm Aluminium Armored cable power DB	Mtr	20			
	3.5Corex16Sqmm Aluminium Armored cable LDB Main	Mtr	33			
2	End Termination of the above cables with proper Glands				_	
	and Lugs		-		4	
	3.5Corex50Sqmm Aluminium Armored cable Main DB	Set	2			
	3.5Corex35Sqmm Aluminium Armored cable power DB	Set	2			
	3.5Corex16Sqmm Aluminium Armored cable LDB Main	Set	4			
D	WIRING					
1	Light/Fan point wiring with 3 of 1.5 sqmm PVC					
	insulated copper conductor to be laid in 2mm suitable					
	PVC conduit with Bend,Couplings, etc And fixing with					
	clamps screws etc.All conduits to be laid above the					
	false ceiling/partition/concealed in the wall					
	etc. Wiring to be connected with supply&Fixing of					
	6A Modular type switch(MK/ROMA) with suitable					
	Modular plate and metal Box				1	
	a) One light Controlled by One Switch	Pts	22			
	b) Two light Controlled by One Switch	pts	2	1		
	c) 6A Switch box Sockets in the switch board itself	Pts	8			
	d) Ceiling fan with regulator	Pts	10		1	
	e) wall bracket fan point (6A socket with 6A switch)	pts	3	1		
	f) Calling bell point with Calling bell instrument	Pts	1			
	g)Exhaust fan point		3		+	
	BITUI AND	pts	3	ł	+	

2	Supply&Wiring with Flame Retardant				ſ
	insulated PVc wire as per grade IS 994				
	for Circuits,Computer point,Power points within 2mm thk				
	PVc conduits with necessary accessories and with				
	proper clamps and to be concealed below the false				
	ceiling It comprises as follows:-				
	a) 3Runs of 2.5Sgmmcopper wire in PVC conduit for				
	lighting circuit mains	Mtr	230		
	b) 3Runs of 2.5Sqmmcopper wire in PVC conduit for				
	Power points	Mtr	280		
	C) 3Runs of 2.5Sqmm copper wire in PVC conduit for	-			
	computer points	Mtr	300		
	d) 2Runs of 4Sqmm copper wire+1.5Sqmm copper				
	wire in PVC conduit A/C Wiring	Mtr	200		1
	e) 2Runs of 6Sqmm copper wire+2.5Sqmm copper				1
	wire in PVC conduit	Mtr	30		1
	f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper	-			
	wire in PVC conduit	Mtr	23		
		-	_		
E	POWER POINT OUTLETS				
1	Supply&Installation of 3 Nos of 6A Sockets controlled by				
	2of 5A Switches with front plate with enclosure and				
	other accessories etc(MK /ROMA)	Set	12		
2	Supply&Installation of 1Nos of 6A Socket controlled by				
	1No 6A Switch with front plate with enclosure and other				
	accessories etc(MK /ROMA)	Set	10		
3	Supply&Installation of 1Nos of 16A Socket controlled by				
	1No 16A Switch with front plate with enclosure and other				
	accessories etc(MK /ROMA)	set	4		
F	LIGHTING FIXTURES				
1					
	Supply, Fixing & Commisioning of Recess mounting type compact				
	vertical Flat Panel 34W LED fitting in Down Rods with white finish and				
	other fixing accessories. (Crompton, Wipro, Philips)	set	2		
2					
	Supply, Fixing & Commisioning of Recess mounting type compact				
	vertical round shaped 1x15W LED downlighter fitting with white				
	finish and other fixing accessories.,(Crompton, Wipro, Philips)	set	7		
3	Supply&Fixing of Patti Type LED 20Watts Fiitings (Crompton,				
	Wipro,Philips)	Set	18		

4	Supply&Fixing exhaust fan (Crompton, Almonard)	set	3	
5	Supply&Fixing & Commisioning of wall mounting fan			1
	with necessary Down Rods and with all			
	fixing accessories.,(Crompton / Havells)	Set	3	
6	Supply&Fixing & Commisioning of 48" ceiling fan			
	with necessary Down Rods and with all			
	fixing accessories., (Crompton / Havells)	Set	10	
G	EARTHING			
1	Providing dedicated earthing with 600x600x3.15			
	mm copper plate along with 50mm dia.10feet			
	long G.I pipe with other accessories in the earth			
	filled with necessary salt, charcoal, etc. It should			
	be covered with G.I Manhole cover with necessary			
	civil works.etc	Set	1	
2	Supply & Laying of 10 Sqmm PVC Insulated Multi			
	strand copper conductor laid in 25mm dia PVC pipe for			
	Dedicated earth leads from the earth electrodes to			
	the UPSsystem	Mtr	40	
3	Providing general earthing with 50mm dia.10feet			
	long G.I pipe with other accessories in the earth			
	filled with necessary salt, charcoal, etc. It should			
	be covered with G.I Manhole cover with necessary			
	civil works.etc	Set	1	
4	Supply&Laying of 8SWG copper wire	Mtr	60	
F	TELECOMMUNICATION			
1	Supply&Laying of 2 Pair Telephone Cable within PVC			
	Conduit and its necessary accessories etc	Mtr	220	
				ļ
2	Supply&Laying of 20Pair Telephone Cable within PVC			
	Conduit and its necessary accessories etc	Mtr	28	ļ
				ļ
3	Supply&Installation of RJ II Jack with necessary Face			ļ
	plate and Box for connecting telephone points	Set	10	
				ļ
4	Supply & fixing of 10 pair KRONE Box with lock and key	Set	1	ļ
	TOTAL			<u> </u>

	MELAVANJUR BRANCH & ATM - DATA CABLING WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)						
	BILL OF QUANTITIES						
S.No	Description Of Work	Unit	Qty	Rate	Amount		
	DATA CABLING						
1	Supply&Laying of CAT 6 Data Communication cable in 2mm						
	thk heavy duty 20mm dia PVC conduit and makinng holes in						
	the aluminium partitions/wall all accessories as required (DLink)	Mtr	380				
2	Supply&Installation,Testing&Commisioing of Modular type						
	1Nos of RJ45 Female Jack housed in GI anodised metal box						
	with suitable Faceplate fixing the same in the wall/partitions						
	with all accessories etc. as required.	Set	8				
3	Supply and fixing of 1M Mounting Cord	Set	8				
4	Supply and fixing of 2M Mounting Cord	Set	8				
5	Supply&Installation of 24por cat6 SWITCH	Set	1				
6	Supply and installation of 24port cat 6 jack panel	Set	1				
7	Supply and installation of 9u wall mounting rack	Set	1				
	TOTAL						

	MELAVANJUR BRANCH - AIR CONDITIONING WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)							
	BILL OF QUANTITIES							
SI.No	Description Of Work	Unit	Qty	Rate	Amount			
1	Supply, Testing and commissioning of							
	indoor and outdoor split air conditioner with remote							
	control, with 3 star rating units and necessary civil							
	works etc., The rate of units is including the supply							
	and laying of 3 mtr of copper pipes with insulations,							
	rubbers, white cements etc., (Brand: Voltas)							
b	1 .5 TR - Manager & Server	2	No					
2	Supply and laying of copper pipes with rubber							
	insulations, rubbers, white cements etc.,	20	Mtr					
3	Supply and installation of Stabilizer for following							
	units							
а	1.5 TR - 3 KVA	2	No					
b	Installation Charges for 1 Tr Split Air Conditioner	2	No					
4	Supply and Installation of Outdoor Stand with							
	necessary civil works	2	No					
5	Supply and laying of PVC Blue pipes for water							
	drain from the indoor units.	15	Mtr					
6	Civil works like cutting AC hole,packing,drain pipe cutting and							
	packing with mortar etc.	1	Ls					
7	Supply and fixing for Timer for A/C Controlled	1	No					
	Airconditioning works Total:							

BILL OF QUANTITIES							
S.No	ITEMS AND DESCRIPTION	QTY	UNIT	RATE	AMOUNT		
1	FULLY GLAZED ALUMINIUM PARTITION & DOOR						
	FRONT DOTH SIDE FIVED DADTITION . Droviding	0.4	Cth				
а	FRONT BOTH SIDE FIXED PARTITION : Providing and fixing Fully glazed partition in ATM Entrance ,	84	Sft				
	made of aluminium MRF vapocured twin style						
	frame work of size:-58 x38mm, 20 micron of IB -						
	Black colour finished with 10 mm thk float glass						
	with derk silicon (SAINT GOBAIN or MODIGUARD)						
	up to the false ceiling level.Support to be done to the						
	rcc ceiling, but measurements would be taken below						
	the false ceiling level only.						
b	ENTRANCE DOOR (Size : 3'6"x7'0") : Providing and	25	Sft				
	fixing of Fully glazed door for ATM entrance, made of						
	aluminium MRF vapocured twin style frame of size:- 100 x 50 mm, 20 micron of approved colour						
	finished with 10 mm edge polished glass with						
	silicon (SAINT GOBAIN or MODIGUARD) up to the						
	7'0" height, door to be provided with dorma make						
	12" SS handle, lock and door closure(approved						
	make) & stopper						
2	GYPBOARD FALSE CEILING Supply and erection of gypboard false ceiling for	83	sft				
	Manager cabin area at single level with framework of	03	SIL				
	G.I. Section of spacing 4'0" x 2'0" above with 12mm						
	gypboard fixing. Recessed ceiling is to be done as per						
	architects instruction to have provision for indirect						
	lighting rate is included for cutouts for lights, smoke						
	detectors and AC grills. The ceiling is putty finished						
	and sanded to form clean and homogeneous surface.						
	Rate is included for two coats of acrylic emulsion						
	painting.						
3	ATM SOCKETS COVER BOX (1'0"X1'0"x6" - 1no)						
	All ATM Sockets, IO Box to be covered using 12mm	2	nos				
	plywood structure with 1mm thk lamination finish (matching ACP color colour), Shutter type door (up &						
	down) with lock, handle and necessary wire manager						
	groove (at bottom) to be provided.						
4	PIN-UP NOTICE BOARD						
	Providing & fixing Pin-up Board of approx size of	1	no				
	600mm x 800mm made of textile wrapped on 12 mm						
	thick soft board with 6 mm com ply backing and a						
	frame work of 50mm wide with 24 mm thk com ply, finished with 1 mm thk Laminate. The Pin-up Board						
	shall be set into the wall panelling with necessary						
	fittings as directed by the Bank.						

MELAVANJUR - ATM INTERIOR WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)

5	WRITING DESK			
	Writing desk to be done as per plan with 12mm glass topped with pigeon holes made with 18mm plywood structure with additional boxing as per design,	1	no	
6	cheque drop box/ Complaint			
	Providingchequedropbox/Complaint/Suggestion1'6" length,0'9"wideand1'6"heightwith19mmtk.Plywooda ndlinedwith1mmtk.Laminate(FusionMapleWoodfinis h)fortop&exposedsides.Exposededgesofplywoodshall befixedwithteakwoodbeadingsuitablypolishedandthe backsideshallbecoveredwith6mmtk.plywood.Theinn ersidesshallbepaintedwithtwocoatsofenamelpaintov eracoatofprimer&twocoatsof putty.	1	no	
7	ROLLING SHUTTER COVER BOX			
	Supplying & fixing of shutter box using 19 mm plywood, boxing with above entrance partiton and rolling shutter and finished with 1mm lamination.	50	sft	
	TOTAL			

	MELAVANJUR ATM - ELECTRICAL WORKS FOR INDIAN		IDARONA					
	BILL OF QUANTITIES							
SI.	Description	Qty	Unit	Rate	Amount			
А	MAINS & DISTRIBUTION BOARDS							
1	Supply, erection, testing and commissioning of three							
	phase 4 WAY, TPN MCB DB double door vertical type,							
	IP 42 powder coated with							
	40A TPN MCB – 1No as INCOMER							
	32A DP MCB-1No For UPS							
	10/25/32A – 4No.s as OUTGOING							
	Including all interconnections & accessories etc	1	No					
В	POWER CABLES & CONDUIT WIRING							
1	Supplying, laying, testing & commissioning of PVC /							
1	LT insulated 1.1KV grade aluminium armoured							
	conductor cables of the following sizes, laid in trenches							
	below ground level/ clamped on to the walls as per site							
	condition.							
а	3.5C x 25Sqmm aluminium armoured PVC cable	20	mtr					
~								
С	Supplying and terminating the end of cables of the	1						
	following sizes using Siemens type single compression							
	cable glands, crimping type aluminium / copper							
	sockets of required size, gland earthing clips etc.,							
	complete.							
а	3.5C x 25Sqmm aluminium armoured PVC cable	2	Set					
D	AIR CONDITIONING WIRING & ACCESSORIES							
1	Supply&Installation of 32A Metal Clad Socket with							
	top in a specified company manufactured box with							
	suitable rating MCB for AIR CONDITIONS	2	No					
2	Wiring in position 2 runs of 4.0 sq.mm. cable and 1 run							
	of 2.5 sq.mm cable for earth from Main D.B. to 2 Nos							
	split air – conditioners in P.V.C. conduit pipes including							
	chasing in walls / floor wherever necessary.	25	Mtr					
		-						
E	UPS WIRING & ACCESSORIES							
1	Supply, erection, testing and commissioning of single							
	phase 6 WAY, SPN MCBDB double door type, IP 42 powder coated for UPS and Emergency Lighting with							
	40A DP MCB – 1No as INCOMER	+	L					
	10A SP MCB – 1NO as INCOMER 10A SP MCB – 4Nos. as OUTGOING	+		ļ				
	Including all interconnections & accessories etc.,							
	complete.	1	Set					
		±	Jei	ļ	ļ			
2	Wiring in position 2 runs of 6.0 sq.mm. cable and 1 run							
-	of 4.0 sq.mm cable for earth from Main D.B. to UPS and							
	UPS to UPS DB.	12	Mtr					
		1	-					
3	Wiring in position 3 runs of 2.5.sq.mm cable for circuits from							
3								
3	UPS.Lighting, Raw power required places in P.V.C. Conduit pipes							

4	Supply, fixing, testing & commissioning of 2No. 16A			
	multi pin socket outlet in UPS circuit controlled with			
	1No. 16A one way switch in a steel sheet enclosure with			
	8 module top plate including dummies and incidental			
	materials etc.,	2	No	
F	LIGHTING WIRING			
	Supply, fixing, testing & commissioning of the following			
	switch controls in steel sheet enclosure including 3 runs			
	of 1.5sqmm, steel sheet enclosure & modular top plate			
	and all incidental materials etc., complete.			
1	One light Controlled by One Switch	4	No	
2	1 No. 6A socket controlled by single switch	1	No	
G	LIGHTING & FIXTURES			
1	SFTC for the following light fittings with required			
	hardwares such as suspension wires from ceiling, false			
	ceiling, anchor fasteners, chains, bolts, nuts etc.,			
	complete.			
а	36 watts LED light fitting with 2'X2'	1	No	
b	15 watts LED round fitting with LED as	2	No	
С	20watts LED Patty fitting	1	No	
Н	DATA POINT			
1	Supply&Laying of CAT 6 Data Communication cable in 2mm thk			
	heavy duty 20mm dia PVC conduit	60	mtr	
2	Supply&Installation,Testing&Commisioing of Modular type			
	1Nos of RJ45 Female Jack housed in GI anodised metal box			
	with suitable Faceplate fixing the same in the wall/partitions			
	with all accessories etc. as required.	2	No	
I	EARTHING			
1	Providing earthing two numbers , One for ATM and			
	another for AIR-CONDITIONERS including excavating			
	the P.C.C. floor/ earth to 6'0" depth and providing			
	earthing with 50mm dia. G.I. pipe with perforations			
	connected through copper wire including copper flat			
	including copper plate of size 300mm x 300mm, G.I.			
	bolts and filled up with layers of charcoal, salt and			
	earth. (Earth provided for computers shall not be used			
	for any other purpose)	1	No	
2	Supplying and laying of 6 Sqmm multi stranded copper			
	wire for UPS earth in suitable PVC conduit with all			
	incidental materials etc., complete.	25	Mtr	
	Total			

MELAVANJUR ATM - AIR CONDITIONING WORKS FOR INDIAN BANK (KUMBAKONAM ZONE)							
BILL OF QUANTITIES							
SI.No	Description Of Work	Unit	Qty	Rate	Amount		
1	Supply, Testing and commissioning of						
	indoor and outdoor split air conditioner with remote						
	control, with 3 star rating units and necessary civil						
	works etc., The rate of units is including the supply						
	and laying of 3 mtr of copper pipes with insulations,						
	rubbers, white cements etc., (Brand: Voltas)						
b	1 TR - Manager & Server	2	No				
2	Supply and laying of copper pipes with rubber						
	insulations, rubbers, white cements etc.,	20	Mtr				
3	Supply and installation of Stabilizer for following						
	units						
а	1.5 TR - 3 KVA	2	No				
b	Installation Charges for 1 Tr Split Air Conditioner	2	No				
4	Supply and Installation of Outdoor Stand with						
	necessary civil works	2	No				
5	Supply and laying of PVC Blue pipes for water						
	drain from the indoor units.	15	Mtr				
6	Civil works like cutting AC hole,packing,drain pipe cutting						
-	and packing with mortar etc.	1	Ls				
7	Supply and fixing for Timer for A/C Controlled	1	No				
	Airconditioning works Total	:					