

| PROJECT NAME - BOQ FOR CARPENTRY WORKS OF CHCCHANI BRANCH OF INDIAN BANK | | | | | |
|--|---|------|--------|------|--------|
| ADDRESS - AT CHACHANI, ASSAM | | | | | |
| WORK TYPE- CARPENTRY WORKS | | | | | |
| SR.NO. | DESCRIPTION | UNIT | QNTY | RATE | AMOUNT |
| A. | CARPENTRY WORKS | | | | |
| 1 | PARTITION WORKS | | | | |
| | Note :- The rate shall be include of frame work above false ceiling level. Measurement should be taken up to false ceiling level and visible portion only. | | | | |
| a | FULL HT SOLID PARTITION | SFT | 0.00 | | |
| (i) | BOTH SIDE LAMINATE | | | | |
| | Providing & fixing in position solid Full Height Partition in frame work in 2'x 2' grid (horizontally and vertically) comprising of 2"x 2" T.W. Section with 9 mm thick plywood and finished with 1 mm thick laminates of approved make and colour as shown in drawing, on both sides. All exposed T.W. surfaces to be finished in melamine polish of matching laminate colour as directed including all necessary wood preservative paint etc. as per list of approved material and as approved by the Project Consultant/ Bank complete in all respects | | | | |
| (ii) | Full Ht Ht Solid Partition in Aesbestos Sheet with Door (Having Fire Rating of 3Hours for UPS Room) Finished with POP and approved shade of Acrylic Emulsion Paint | SFT | 0.00 | | |
| | Providing & fixing in position Semi-Height Solid Partition in Aluminium frame work in 2'x 2' grid (horizontally and vertically) comprising of 50mm x 50mm x 3mm thk Aluminium Section covered with 8 mm thick Aesbestos Sheet on both sides and finished with paint of approved make and colour as shown in drawing, on both sides. It shall also consist of a Flush door of required size and fixed with aesbestos Sheet in Aluminium sections on both sides and finished with paint of approved shade | | | | |
| b. | Semi ht Solid / Glazed Partition | SFT | 40.00 | | |
| | Specification same as 4 above but of low ht as per the drawing. All external surface and edges to be finish with 1mm thk laminate of approved shade & make. Providing and Fixing inserted Soft board / White boards / Glass maintaining the vertical surface lines and no extra measurements would be taken for the soft boards / white boards / Glass. | | | | |
| c | FULLY GLAZED PARTITION WITH FLOAT GLASS (Till 8' High) | SFT | 210.00 | | |
| | Providing and fixing partition framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm @ 600mm c/c Horizontally and Vertically . The vertical alternate frames to be fixed to the ceiling with necessary fixtures. The framing shall be finished with 8/9 mm thk. Commercial ply on both side and finished with 1.00 mm thk. Laminate finished with melamine polish. The shade of laminate should be as approved by the Architect. Approved make 10mm thick Clear Float glass with frosted film of approved shade and pattern to be fixed from skirting level to 2100mm level (in the top line of Door) or as directed by the architect. The skirting should be as per approved laminate as per drawing and direction. Rate shall be inclusive of necessary hardware items, etc. Complete. The edge beadings with steam beach wood and vineer should be finished with melamine. | | | | |
| | ALUMINIUM HEAVY DUTY FRONT GLAZING | SFT | 24.00 | | |
| | Providing and fixing fully glazed heavy duty alluminium sections (14 Guage) at the main entrance as shown in the drwng with anodised section(as per the colour as approved by the architect). Glazing shall consist of approved make heavy duty 6" x 2" sections for the top & bottom rails and 2" x 2" sections for the vertical styles. 10mm thk. approved make clear float glass shall be provided and fixed in the framing. Rate shall include necessary etching film / LOGO, and any necessary hardware items. (Heavy Duty 6" & 2" thick frames(14 Guage) - approved make) | | | | |
| 2 | DOORS | | | | |
| i | ENTRANCE DOORS- WITH COLOURED ANNODISED ALLUMINIUM SECTIONS (HEAVY DUTY-14 GAUGE) | SFT | 24.00 | | |
| | Providing and fixing fully glazed alluminium (heavy duty 14 gauge) pivoted doors at the main entrances as shown in the drawing. Door shall consist of "Indal/Jindal" make heavy duty 14 gauge sections 6"x2" for top and bottom rails, 2" x 2" for vertical styles. 10mm thk Modi Guard make clear float glass shall be provided and fixed in the framing with necessary packing materials. All the edges of the glass shall be machine polished. Rates shall include necessary itching / frosted filmsas directed by the architect, approved locking system, 1 pair of 18" lonf S.S handle of approved make, floor spring, door stopper, gaskets and misc hardware items | | | | |
| ii | SOLID DOORS- IN LAMINATE FINISH (with hardware fittings MAKE EVERITE / GOLDEN /HARDWIN /EVEREST) (WITH OR WITH OUT VISION PANEL AS PER DIRECTION OF the ARCHITECT | | | | |

| | | | | | |
|---|---|-----|-------|--|--|
| | Providing and fixing solid doors of sizes as shown in the drawing. The door shutter shall of 35 mm thick flush shutter of approved make and finished with 1mm thick approved laminate on both sides. The edges finished with steam beach lipping. A door frame of 3.5" x 2" steam beach section shall be provided finished in mellamine. Rate shall include Dead lock (Godrej Make), floor springs / door closure (as the case may be), door stopper, a pair of handles 12" SS Brushed finished, 5" hinges 4 Nos., buffers, tower bolts, etc with necessary hardware items and with or with out door frames as mentioned above | | | | |
| a | With Door Closure | SFT | 78.00 | | |
| 3 | PANELLING ON COLUMNS/WALLS/DOORS WITH/ WITHOUT FRAMING | | | | |
| i | IN PLYWOOD FINISHED WITH LAMINATE FINISH TILL 4'-0" HEIGHT UNLESS SPECIFIED | SFT | 112 | | |
| | Providing and fixing panelling on walls/ columns with or without framing as per the directions of the architect. Framing if required and provided, shall consists of aluminium sections 50mm x 40mm(wall thickness 2mm) @ 2'-0" c/c both ways horizontally and vertically on the wall. The framing would be covered with 1/4" thk plywood finished in approved shade of laminate of thickness 1.0mm. Wooden moulding, lipping etc as directed by the architect shall be provided wherever required. The panelling should be done in such a way that it can house the sliding folding partition when fully opened and remain in flush with the panelling | | | | |
| 4 | LOW HT RUNNING STORAGE(1'-6"DX2'-6"HT) (BACK CADENZA) | SFT | 66 | | |
| | Providing and laying low ht Storage unit of sizes as mentioned above. They shall consist of 3/4" thk plywood for top, base and sides and base 1/4" thk marine plywood, 3/4" thk plywood shutter with self closing hinges of haffle make(full ovel open) & PVC lipping matching with the approved shade of laminate on all the edges. All external surfaces shall be finished with 1.0mm thk laminate of approved shade and make. Divisions of the shutter shall be make equally according to the length of the storage. A 3/4" thk fixed ply wood shelf on battens shall be provided @16" intervals from the base. Suitable wooden moulding (as per Architects design) with mellamine polish shall be provided to the edges of the storage top. All inner surfaces including shutters shall be finished with natural french polish. Rates shall be inclusive of all necessary approved fittings like hinges(haffle make), locks, 3" long brushed finish handle, tower bolts and any other misc hardware items of approved make | | | | |
| 5 | SHUTTER BOXING | SFT | 28 | | |
| | Providing and Fixing Shutter Boxing with 19mm thk Marine Ply and Finished with Aluminium Composite Panel. The boxing of shutter should be made opennable type for periodic maintainance. Note the mode of measurement would be the multiplication of the length and the height of the boxing | | | | |
| 6 | GYPSUM BOARD CEILING WITH POP PUNNING | SFT | 0 | | |
| | Providing and fixing 1/2" thk Gypsum India Board false ceiling at levels as shown in the drg. From the FFL. Rate shall be inclusive of all Gypsum India Components contained G.I perimeter channels of size 0.55 thk having one flange of 20mm and another flange of 30mm and a web of 27mm along the perimeter of the ceiling, screw fixed to brick wall/partition with the help of nylon sleeves and screws at 610mm centres. The suspending G.I intermediate channels of size 45mm, 0.9mm thk with two flanges of 15mm each from the soffit at 1220mm centres with ceiling angles of width 25mm x 10mm x 0.55mm thk fixed to soffit with G.I cleat and steel expansion fastner at every 610mm c/c. Ceiling sections of 0.55mm thk having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the intermediate channel with the help of connecting clip and in directions perpendicular to the intermediate channel at 457mm centres. 12.5mm tapered edge Gypboard is then screw fixed to ceiling section with 25mm drywall screws driver or drilling machine with suitable attachment. The board are to be jointed and finished so as to have a flush look which includes filling and finishing the tapered and square edge of the boards with jointing compound & jointing paper tape. Rate shall be inclusive of any vertical ceiling part, cutouts for spot and tube lights, a.c grills, fire and security system cutouts. All Sections should adhere to the manufacturer's guidelines . | | | | |
| | Note- Rates shall be inclusive of The drop/band of 6"-12" between the gypsum(at lower level) and Armstrong(at heigher level). No extra can be claimed for the same. Amount will be paid as per the measurement of the horizontal surfaces of Gypsum and Armstrong and nothing will be paid for vertical surface / band/ drop as it is all inclusive | | | | |
| 7 | MODULAR FALSE CEILING- ARMSTRONG make | SFT | 0 | | |
| | Providing and fixing Armstrong (Fine Fissured Micro Look with Tagular Edge using 15mm grid sections) false ceiling of size 24" X24" AT LEVELS AS SHOWN IN THE DRG. FROM THE FFL. Rates shall be inclusive of providing the total system with installation etc. The contractor has to maintain all ceiling tiles in good order and replace the defective tiles (at his own cost) before the handing over of the site. | | | | |
| 8 | COLOURED ACRYLIC SHEET LOGO FOR THE BANK, (BACK LIT) OVERALL SIZE 450MM X 450 MM- | NOS | 0.00 | | |
| | Supplying , fabricating and installation ofINDIAN BANK's Logo made of coloured acrylic sheet 5-6mm thk in box section, and as per the sizes as mentioned in the detailed drawings . This Coloured Acrylic sheet box logo should be fixed with light from inside so as to have a back lit , as per the direction of the architect. | | | | |
| 9 | PAINTING & POP/ WALL PUTTY WORKS | | | | |

Archiventions- Architects Engineers

| | | | | | |
|-----|--|-------|------|--|--|
| i | PLASTIC EMULSION (ONLY IN BANKING HALL) | S.FT. | 0.00 | | |
| | Providing & applying plastic emulsion paint on walls, columns & ceilings. The rate shall include scrapping, levelling & preparing the surface. Primer coat + (minimum) 3 coats to get evenly spread quality finish (roller finish) of approved make, quality & finish shall be provided. | | | | |
| ii | DISTEMPER PAINT AT STORE, UPS, PANTRY, TOILETS & OTHER NON-CUSTOMER AREAS | S.FT. | 0.00 | | |
| | Providing & applying distemper paint on walls, columns & ceilings at places as mentioned above and as directed by the architect. The rate shall include scrapping, levelling & preparing the surface. Primer coat + (minimum) 3 coats to get evenly spread quality finish (roller finish) of approved make, quality & finish shall be provided. | | | | |
| iii | LUSTRE PAINT IN GYPSUM FALSE CEILING | S.FT. | 0.00 | | |
| | Providing & applying Luster Paint on walls, columns & ceilings. The rate shall include scrapping, levelling & preparing the surface. Primer coat + (minimum) 3 coats to get evenly spread quality finish (roller finish) of approved make, quality & shade shall be provided. | | | | |
| iv | ENAMEL PAINT IN ROLLING SHUTTER, COLLAPSABLE GATE, WINDOW GRILLS AND OTHER METAL WORKS | S.FT. | 0.00 | | |
| | Providing & applying 1 st quality oil paint of approved make, quality & shade. The rate shall include scrapping, levelling & preparing the surface with primer quote. | | | | |
| v | POP/ WALL PUTTY ON EXISTING WALLS (ONLY IN BANKING HALL) | S.FT. | 0.00 | | |
| | Providing and applying POP Punning/ Birla Wall Putty on walls and columns (average 6mm thk). The rate shall include scrapping, levelling and preparing the surface. The rate shall include scrapping, levelling and preparing the surface. The rate shall be inclusive of all types of grooves above the skirting, around the windows and door frames. If the average thickness is found to be 4mm or less than POP/ Wall putty will be considered as a putty finish and the rate shall be 50% of the quoted rate | | | | |
| B. | LOOSE FURNITURE WORKS | | | | |
| 1 | DESK & DRAWERS | | | | |
| i | OFFICER'S TABLE (2'3" x 4'-6" x 2'-6" ht) | NOS | 1 | | |
| | Providing and fixing a desk of overall size of top as mentioned. It shall consist of 3/4" thk plywood top as per design(double edge on the front and the back with 1 1/2" thk half round moulding on the edges) supported on 3/4" thk plywood verticals. Suitable (as per architect's design) wooden moulding with mellamine polish shall be provided to the edges of the top. A 3/4" thk plywood apron shall be provided as per architect's design with necessary pattern. The table top shall be finished with 1.0 mm thk laminate of approved shade and all external surfaces to be finished with 1.0mm thk laminate of approved shade. Each top shall be provided with a pedestal (set of three drawers with central locking system either movable or fixed to the table), 1.no metal computer key board tray as per architect's design fixed with telescopic /double (haffle/albihari/solo make) sliders, a 3" dia PVC wire manager of approved quality near the CPU/Monitor position as shown in the drg. 1 no Metal CPU Trolley to be provided below the desk as shown in the drg and a foot rest made out of 19mm thk plywood as per the design or as directed by the architect shall also be provide below the counter. All the inner surfaces shall be finished with Laminate finish of approved shade. Rates shall be inclusive of all necessary approved fittings like locks(godrej/vijayan make) for drawers and any misc. hardware items | | | | |
| ii | CLERICAL TABLE (2'0" x 4'-0" x 2'-6" ht) | NOS | | | |
| | Specifications same as above but of overall size as mentioned here | | | | |
| iii | MANAGER'S TABLE (2'-6" X 6'-0" X 2'-6") WITH 6MM THK CLEAR GLASS WITH POLISHED EDGES ON TABLETOP | NOS | 1 | | |
| | Providing and fixing a desk of overall size of top as mentioned. It shall consist of 3/4" thk plywood top as per design(double edge on the front and the back with 1 1/2" thk half round moulding on the edges) supported on 3/4" thk plywood verticals. Suitable (as per architect's design) wooden moulding with mellamine polish shall be provided to the edges of the top. A 3/4" thk plywood apron shall be provided as per architect's design with necessary pattern. The table top shall be finished with 1.0 mm thk laminate of approved shade and all external surfaces to be finished with 1.0mm thk laminate of approved shade. Each top shall be provided with a pedestal (set of three drawers with central locking system either movable or fixed to the table), 1.no metal computer key board tray as per architect's design fixed with telescopic /double (haffle/albihari/solo make) sliders, a 3" dia PVC wire manager of approved quality near the CPU/Monitor position as shown in the drg. 1 no Metal CPU Trolley to be provided below the desk as shown in the drg and a foot rest made out of 19mm thk plywood as per the design or as directed by the architect shall also be provide below the counter. All the inner surfaces shall be finished with Laminate finish of approved shade. Rates shall be inclusive of all necessary approved fittings like locks(godrej/vijayan make) for drawers and any misc. hardware items | | | | |
| iv | LINEAR WORK STATIONS (RUNNING COUNTER)-1050 MM WIDTH (WITH CUSTOMER LEDGE) | RFT | 11.5 | | |

| | | | | | |
|---|--|-----|---|--|--|
| | Providing and fixing a <u>Clerical Desk / Linear Work Station</u> as per the width as mentioned above. Each top shall be provided with a pedestal (set of three drawers with central locking system either movable or fixed to the table), 1.no metal computer key board tray as per architect's design fixed with telescopic /double (haffle/albihari/solo make) sliders ,a 3" dia PVC wire manager of approved quality near the CPU/Monitor position as shown in the drg. 1 no Metal CPU Trolley to be provided below the desk as shown in the drg and a foot rest under the table as per design. All the inner surfaces shall be finished with Laminate finish of approved shade. Rates shall be inclusive of all necessary approved fittings like locks(godrej/vijayan make) for drawers and any misc. hardware items It shall consist of 3/4" thk. Comm. Ply top as per design (double edge on the front and back with 1 1/2" thk half round moulding on the edges) supported on 1/2" thk. Comm. Ply verticals at every 4'-6" length. Suitable (as per Architects design) wooden moulding with melamine shall be provided to the edge of the top. The top of the counter should be finished with 1.0mm Laminate and all other external surfaces to be finished in 1.0 mm. Thk. Laminate (suede finish)of approved make. Afoot rest made out of 19mm thk plywood as per the design or as directed by the architect shall also be provide below the counter.Rates shall be inclusive of all necessary approved fittings like locks(godrej/vijayan make) for drawers and any misc. hardware items | | | | |
| v | CASH COUNTER 1650 mm x 1950 mm . with partitions ,Rear Door etc. all complete | NOS | 2 | | |
| | Providing and fixing Cash Counter in Laminate finish of clear internal dimension 5'-6" X 6'-6" all complete with glazed partition in 12 mm thk itched glass as per design in front including rear doors fixed with Godrej Make Night Latch, The counter shall be provided with a table top of 2'-6" deep of 1 1/2" thk and finished with laminate of approved shade. The counter shall comprises of a Metal key board Tray, Metal Cpu Trolley, Wire Manager etc.A drawer unit comprising of three drawer set shall be fixed with the counter or as directed by the architect. The drawer unit shall have a central locking arrangement and the lock should be of godrej make. Rates shall be inclusive of all hardware fittings like locks, handles, hinges, telescopic channel etc as required. A foot rest made out of 19mm thk plywood as per the design or as directed by the architect shall also be provide below the counter. provision should be made on side by providing a niche of size 6" x 6" on sides of counter for boucher passing. <u>NOTE- Rates shall be inclusive of all full ht semi glazed partition of maximum height 8'-0" from FFL on sides and back, including covering the top of the cash counter with aluminium laali as per design and no claim of partition in cash cabin will be entertained extra.</u> i)Working top made with 25mm thick plywood finished with 1mm thick laminate. Outside edge of the working top shall be provided with 1 1/2"x1" Teak Wood moulding finished with melamine polish. Inside edge will be provided with 1/2"x1" T.W. beading patti with melamine polish.ii)Vertical facia (Apron) made with 18mm thick plywood finished with 1mm thick laminate with 1mm thick groove at the joint of laminates of two different shades. | | | | |
| | iv)1'-0" height solid partition over working top and fixed with a ledge(transaction top) made in 19mm thk plywood of approved shade and make @3'-6" from finished floor lvl (Mirror Polished) rounded and taken below as apron with necessary grooving for strip light as per design.The ledge should be such that it is projecting 4" inside the counte and 8" outside the counter and rounded and taken down to 2'-6" above Finished floor level on customer side v) A gap of 4"should be left above the transaction top (all along the width of the teller counter) vi)Glazed partition having height 1'-0" above the transaction top (in facia) and also above 4" clear gap shall be provided with 12 mm thick glass (itched) as per drawing. The edges of cut out and the top edge of glass are to be mirror polished and to be fixed to partition as per fixing details and to boxing with concealed S. S. finished 'D' brackets as shown in the drawing. vii)FULL Glazed (IN FRONT, SIDES AND BACK till 6'-0" lvl from ground level) partition provided with 12mm thick glass (itched) above the slit to be fixed to partition as per fixing details and to boxing with concealed S. S. finished 'D' brackets as shown in the drawing. . The exposed edges shall be finished in mirror polish.ix)Telescopic CPU Stand/ ready made Keyboard tray shall be provided of approved model and make.x) Footrest made with T.W. member of size 4"x1 1/2" " finished with french polish. | | | | |
| | xi) Drawer units as per drawing shall be provided and each drawer should have vertical partitions for keeping the currency notes and multipurpose Godrej locks. Facia of drawer unit shall be finished with 1mm thick laminate and all other sides shall be finished with white enamel paint. The drawers will be provided with handles (Stainless Steel finish) and channels as per approval of the Project Consultant / Bank.xii) Boxing as per drawing made with 12mm thick plywood finished with Synthetic enamel paint shall be provided below the table top for electrical conduiting and at the bottom for the LAN cabling/Telephone wire conduiting. <u>The item to include all necessary hardware and fittings in Stainless Steel finish.. Necessary beadings with matching melamine polish for fixing the glass are to be provided as per drawing/ as directed.Rates shall also be inclusive of Doors with Godrej Night Latch for Cash counters</u> | | | | |
| v | SIDE CADENZA - 1050MM X 450MM X 700MM | | | | |

| | | | | | |
|------|--|-----|------|--|--|
| | Providing and laying side cadenza of above sizes and as mentioned in the drawing. It shall consist of 3/4" thk plywood top, side and bases and 1/4" thk back. The edges on th top shall be provided with suitable (as per architect's design) wooden moulding with melamine finish. A pair of 3/4" wood shutters will be provided which will slide on 1" x 1" wooden battens above skirting. 1" a3/8" deep vertical depression shall be made on each shutters to act as handle as shown in the drawing. All external surfaces should be finished in 1.0mm laminate of approved shade and make. A 3/4" thk fixed ply wood shelf on battens shall be provided at 16" intervals from the base. Rates shall be inclusive of necessary approved fittings like sliding rollers, locks, tower bolts and any other misc. hardware items | | | | |
| (a) | SIZE - 1050MM X 400MM X 750MM (For BM only) | NOS | 1 | | |
| (b) | SIZE - 975MM X 400MM X 750MM | NOS | 1 | | |
| vi | SUB-STAFF TABLE - 900-1000 MM X 600 MM X 750MM | NOS | 0 | | |
| | Providing and laying a Plain Table for Security Gurd with a Pencil Drawers for over all size of top as mentioned above. It shall consist of 3/4" thk. Comm. Ply top as per design (double edge on the front and back with 1 1/2" thk half round moulding on the edges) supported on 3/4" thk. Comm. Ply verticals at every 3' length. Suitable (as per Architects design) wooden moulding with mellamine shall be provided to the edge of the top. The top of the counter should be finished with 1.0mm Laminate and all other external surfaces to be finished in 1.0 mm. Thk. Laminate (suede finish) of approved make. | | | | |
| vii | WALL MOUNTED WRITING TABLE 0'-10" TO 1'-0" WIDE | RFT | 4 | | |
| | Providing and Fixing wall mounted writing ledge as per design. The top shall be made of 19 mm thk plywood fixed with flexi ply to achieve curved surfaces on either sides as per design and fixed with 6mm thk corian, mirror polished, of approved shade and make. The ledge shall be provided with 10" high plywood selves with necessary partitions in between made out of 19mm thk plywood and finished with laminate of approved shade. ledge should be supported on 19mm thick comm. ply on rear side for fixing to the wall. The bottom ply piece to be supported additionally with 2 Nos. of SS Brackets. | | | | |
| | | | | | |
| viii | NOTICE BOARD | SFT | 12 | | |
| | Providing and fixing notice board size as required/ directed (matching with the panel of the cabin) with openable shutter on the front. Made out of 19mm thick Steam beech veneered block board frame and outer frame in 2 1/2" x 1 1/2" Steam beech wood section, concealed hinges, locking arrangement, and glass of (5.5mm thick) with rear panel of SITATEX board, covered with fabric of approved shade. (Basic rate Rs.100/-per mtr, 48" width), fixed to back ply 6mm thick. All complete including melamine polish in stain of required shade. All complete as per approval of the Architect / employer | | | | |
| | | | | | |
| ix | COMPLAIN BOX & SUGGESTION BOX | NOS | 1 | | |
| | Supplying and erecting free-standing complain box of overall size 300 mm long x 200 mm deep x 450 mm high made of 19 mm thick phenol formaldehyde block board, all as in drawing, complete with hardware fittings and fixtures of approved make and quality. Top and all exposed surfaces of block board are to be finished with 1.00 mm thick laminate sheet of approved shade and quality. Inner faces of block board surfaces are to be finished with minimum two coats of synthetic enamel paint of approved shade and quality over a coat of approved primer. | | | | |
| | | | | | |
| x | CHEQUE DROP BOX | NOS | 1 | | |
| | Supplying and erecting cheque drop box (overall size 450 mm x 300 mm x 750 mm) made of 19mm thick phenol formaldehyde bonded plyboard and the curved portion at top made out of 90 mm x 90 mm C.P teak wood section. A slit opening of 10 mm x 150 mm is to be provided at the top of the box. An openable shutter of 259 mm x 262 mm size made of 19 mm thick phenol formaldehyde bonded block board is to be provided at 1.50 mm above finished floor level. All the exposed timber surfaces including all free edges are to be finished with 1 mm thick laminate sheet of combination shade. Inner faces of block board surfaces are to be finished with minimum two coats of synthetic enamel paint of approved shade and quality over a coat of approved primer. Rate to include cost of necessary hardware fittings e.g. brass hinges, lock, knob etc. of approved design and quality. | | | | |
| | | | | | |
| xi | VERTICAL BLINDS | SFT | | | |
| | Supplying and Fixing VERTICAL BLINDS Vista/Mac/Parytex make. Blinds made using 100% polyester with acrylic polymer coating, of the shade and colour as approved by the Arcitect/ Bank ffficial (only for external windows. In case of front facia necessary approval need to be obtained) | | | | |
| xii | Sealing of existing window 19mm thk marine plywood and then finishing the inside surface with 1.0mm thk laminate of approved shade and make as directed by the architect | SFT | 0.00 | | |
| | | | | | |
| | GRAND TOTAL | | | | |