EDAIYUR BRANCH & ATM - INTERIOR, FURNISHING, ELECTRICAL, DATA CABLING AND AIR CONDITIONING WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

A	MAIN WORKS	Amount(Rs.)
1	INTERIOR WORK	
2	FIXTURES WORK	
3	BRANCH ELECTRICAL WORK	
4	BRANCH & ATM DATA CABLING WORK	
5	BRANCH AIR CONDITIONING	
6	ATM INTERIOR WORK	
7	ATM ELECTRICAL WORK	
8	ATM AIR CONDITIONING	
	TOTAL	
(RUPE	EES	ONLY

EDAIYUR BRANCH - INTERIOR, FURNISHING WORKS FOR INDIAN BANK ZONE)

(NAGAPATTINAM

	DILL OF QUANTITIES						
S NO	PARTICULARS	QTY	UNIT	RATE(Rs)	AMOUNT (Rs)		
1	<u>PARTITIONS</u>						
а	Full & Half Blocked Partition						
	Providing full height double skin fully blocked partitions upto RCC ceiling ht using aluminium plain rectangular sections of 2 1/2"x 1 1/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (Bank approved colors) with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Indian Bank Blue) at base and a 100mm wide border (Indian Bank Blue) at the top including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.(Record, dining,strong room,ups room)	115.00	Sft				
b	Partly Glazed Partition Manager & Server Cabin:						
	Providing full height double skin partly glazed partitions using aluminium sections of 2 1/2"x11/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Indian Bank Blue) at base and a 100mm wide border (Indian Bank Blue) at the top and shall include the cost of providing 8mm tk. plain float glass with etching Designe to suitable sizes, including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	184.00	Sft				

С	Low Height Partition			
	Providing low height double skin partitions along with Counter Divider partition wicket gate of the same type using aluminium sections of 2 1/2" x 1 1/2" size spaced at 2'0" c/c maximum for the frame work, fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (bank approved laminates only) with necessary grooves of 1mm thick. The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Indian Bank Blue) at base& including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	79.00	Sft	
d	CASH PARTITIONS (BULK CASH)			
	Providing full height upto 7' 3" from floor level, semi grilled plywood partition for cash cabin, using aluminium sections of 2 1/2" x 1 1/2" size spaced at 2'0" c/c maximum for the frame work , fixed with 6mm plywood on both sides and lined with 1mm tk. laminate (bank approved laminates only) with necessary grooves of 1mm thick, The rate shall include the cost of providing 100mm wide skirting with 1mm tk. laminate (Indian Bank Blue) at base and a 100mm wide border (Indian Bank Blue) shade at the top and shall include the cost of providing ornamental aluminium grille to suitable sizes, including making necessary slots for cable conduits to pass through and all incidental materials etc., complete.	63.00	Sft	
е	CASH CABIN TOP ALUMINIUM GRIL			
	Providing and fixing in position readymade anodized alumium grill of approved design and quality fixed with continuous steam beech / teak wood beads of approved shape (finished 35 x 25 mm) all round polished (in cash cabin)	50.00	Sft	

2	FRONT COUNTER 12MM GLASS			
	Providing front glazing for cash cabin above counter from 3'9" to 7'0" height, and inbetween banking counters using 12mm thick plain glass including edge polishing & etching.	72.00	Sft	
3	DOORS			
a)	ENTRANCE DOOR			
	To be made out of 12mm thk glass with etching as per design. The glass with etching has to be fixed with top & sides rails of 2½"x4" and bottom rails of size 2½" x 6". The rails to be made out of beech wood The door shall have 18" long s/s handle (as shown in the drawing) and also double action floor spring of specified make. The door frame to be mde out of 5"x 2½" best quality beech wood. The etching in glass pattern to be done strictly following instructions of the Architect or following the drawing attached. The exposed wood of frames, rails to be polished as per instructions of the architect. NB: The size of the door may slightly vary as per site conditions for matching the elevation on the fixed glazing. All exposed edges of the glass to be machine polished. The rails are to be made as per the design of the architect. Bank Entrance door (4'0" X 7'0")	42.00	Sft	
b)	FLUSH DOORS			
i)	Door (3'0" x 7'0")	3.00	No	
ii)	ups - (2'6" x 5'0")	1.00	No	
c)	SEMIGLAZED DOORS			
i)	Manager (3'0" x 7'0")	1.00	No	
ii)	Manager & B.cash (2'6"x 7'0")	2.00	No	
d)	WICKET DOOR			
i)	Wicket Door (3'0"x3'0")	1.00	No	
5	Cheque drop box/ Complaint	4.00	.	
	Providing cheque drop box/ Complaint/Suggestion 1'6" length, 0'9" wide and 1'6" height with 19mm tk. Plywood and lined with 1mm tk. Laminate(Fusion Maple - Wood finish) for top & exposed sides. Exposed edges of plywood shall be fixed with teak wood beading suitably polished and the back side shall be covered with 6mm tk. plywood. The inner sides shall be painted with two coats of enamel paint over acoat of primer & two coats of putty.	1.00	No	

6	Vertical Blinds:			
	Providing and fixing 100mm wide Vista Make or equavalent vertical blinds of approved make quality and colour shade and pattern. Rate shall include necessary scotch guard treatment on both side. The overlaps should be uniform and adequate	140.00	Sft	
7	FALSE CEILING (GYPBOARD)			
	Providing & fixing suspended gypboard false ceiling, which includes Providing & fixing G.I perimeter channels of size 27mm, 0.5mm thk having one flange of 20mm & another flange of 20mm along with perimeter of the ceiling, screws fixed to brick wall/partitions with the help of rawl plugs & Screws. Then suspending G.I intermediate channels of size 45mm, 0.9mm thk with two flanges of 15mm each from the soffit at 1200mm centres with stell G.I hanger of width 25mm,0.5mm thk fixed to soffit with G.I. cleat & steel expansion fasteners. Ceiling section of 0.5mm thickness having knurled wedge of 51.5mm and two flanges of 26mm each with leafs of 10.5mm are then fixed to the intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 450mm centres. 12.5mm tapered edge gypboard is then screwed fixed to ceiling section with 25mm dry wall screws at 230mm centres Screw fixing will be done	1000.00	Sft	
	with requiste jointing compound, paper tapes, finisher and premier suitable for Gypsum plaster boards. The entire work shall be finished as per instructions of the Architect. And also finished with two or more coats of acrylic emulsion paint of approved shade and make. No extra cost shall be entertained in completing the entire work in all respect.			
	Total Interior Works	_	_	

EDAIYUR BRANCH - INTERIOR & FIXTURES WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

1	PARTICULARS	QTY	UNIT	RATE(Rs)	AMOUNT (Rs)
	TABLE				
	Manager table as per drawing done with structure made of 18mm plywood with drawer unit comprising of 1 drawer, 1 filing shelf fixed with pull out door (box type hinges), locks, D type handles and all accessories to be provided. All drawers, corners, doors to be finished with beach wood lipping/beading, melamine polished., push in type keyboard, all drawers and key board on telescopic channels. All exposed edges Teak/beach wood beadings is finished with melamine polished and inside laminated with 0.8mm laminate. The table to be topped with 12mm float glass with beveling on all four sides. The side unit is provided with two drawers and filing shelf with two pull out doors, finished in same manner.CPU platform with foot rest to be provided. wall to table gap to closed with plywood.				
a)	Branch Manager 6'0"x2'6"	1.00	No		
2	FRONT COUNTER AND BULK CASH COUNTER				
	drawing of size not less than 5'0" x 2'6" x 2'6" or as per site requirements, with regular drawer - 1 No. and shelves on one side, a keyboard drawer at centre and a platform for CPU onto other side for each counter as shown in drawing using 19mm thick commerical plywood lined with 1.0mm thick laminate(Bank approved colors) Cash and single window with 12mm thick glass (to be strictly followed) in front side for all the exposed surfaces, including providing skirting 4" wide with 1.0mm thk laminate (Indian Bank Blue) on both sides to match with the adjoining partition and 4" wide border at top with 1.0mm thk laminate (Indian Bank Blue). The customer top at 3'9"ht of 1'3" width & working counter top of 2'6" width to be fixed with 19mm Granite top (approved) with double nosing @ front side as shown in the drawing				
	All the plywood edges shall have teak wood lipping and all inner surfaces shall be painted with two coats of enamel paint over a coat of primer & two coats of putty. The rate shall include providing, fixing & painting a foot rest using first class seasoned country frame of size 3" x 1 1/2".Necessary hardware fittings like draw sliders, hinges, multipurpose locks with set keys, handles shall be provided.				
i)	Bulk cash	5.00	Rft		

2	STORAGE				
	Providing and fixing filing cabinet in manager cabin for a height of 2'6" & 7' ht. made of 18mm plywood structure comprising of suitable intermediate horizontal racks with open type doors, finished with 1mm laminate and teak wood beadings neatly melamine polished and inside finished with 0.8mm laminate with locks, handles and all accessories				
i)	Manager Sc	7.50	Sft		
ii)	Cash Sc	10.00	Sft		
iii)	Hall Sc	72.00	Sft		
iv)	Hall Sc	28.00	Sft		
3	WRITING LEDGE WITH 12mm GLASS TOP				
	Made out 18 mm ply as per design and exposed external surfaces to be laminated and internal surface to be painted with top provided 12 mm thk etched glass with machine polished edges. The entire work has to be done to the satisfaction of the architect. The design given has to be strictly followed	1.00	No		
4	NOTICE BOARD				
	Providing and fixing of the soft board on the customer lobby made of jolly board with a fabric of B / R @ 200 / - per meter .The design and the entire work has to be done as per the instructions of the architect a the time of execution	12.00	Sft		
5	ROLLING SHUTTER COVER BOX				
	Supplying & fixing of rolling shutter box using	45.00	sft		
	19mm thk plywood with adequate support at				
	the ends and finished with lamination of				
	approved make and colour etc., complete				
	Total Interior Works			1	

EDAIYUR BRANCH - ELECTRICAL WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

Sl.No	Description Of Work	Unit	Qty	Rate	Amount
Α	Supply&Installation&Commissioing of the following				
1	MAIN DB (8WAY VTPN DB)				
	Three Phase, Vertical Distribution board				
	with nuetral bar,earth bar,cables ties,top and				
	bottom removable gland plate and with necessary				
	adopter boxes if any.The DB should be IP 42 metallic				
	double door with provisioin of MCB etc as				
	required including cuting of wall and plastering the				
	same with neat finish.It comprising as flolows:-				
	Incomer :				
	100A TPN MCCB -1Nos				
	Outgoings:				
	63A TP MCB -4Nos				
	32/25/20A SP MCBs- 5Nos	Set	1		
В	Supply&Installation&Commisioing of the following				
1	LIGHTING DB(4WAY TPN DB)				
	Three Phase, Phase Segrigated Distribution board				
	with nuetral bar,earth bar,cables ties,top and				
	bottom removable gland plate and with necessary				
	adopter boxes if any. The DB should be IP 42 metallic				
	double door with provisioin of MCB etc as				
	required including cuting of wall and plastering the				
	same with neat finish.It comprising as flolows:-				
	Incomer : 40A TPN MCB				
	Outgoings:				
	10/6A SP MCBs- 12Nos	Set	1		
2	POWER DB(4WAY TPN DB)				
	Three Phase, Phase Segrigated Distribution board				
	with nuetral bar,earth bar,cables ties,top and				
	bottom removable gland plate and with necessary				
	adopter boxes if any. The DB should be IP 42 metallic				

	double door with provisioin of MCB&ELCB etc as			
	required including cuting of wall and plastering the			
	same with neat finish.It comprising as flolows:-			
	Incomer : 63A TPN MCB			
	Outgoings:			
	32/25/20A SP MCBs- 12Nos	Set	1	
3	COMPUTER DB(8WAY SPN DB)			
	12 Way SPN Distribution board			
	with nuetral bar,earth bar,cables ties,top and			
	bottom removable gland plate and with necessary			
	adopter boxes if any.The DB should be IP 42 metallic			
	double door with provisioin of MCB&ELCB etc as			
	required including cuting of wall and plastering the			
	same with neat finish.It comprising as flolows:-			
	Incomer : 40ADP MCB			
	Outgoings:			
	10A SP MCBs- 6Nos	Set	2	
4	Supply&Installation of the following with the necessary			
	enclosure and adopter boxes if necessary,			
	a)63A TPN MCB	Set	2	
	b)63A DP MCB	Set	4	
5	Supply&Installation of 32A Metal Clad Socket with			
Ť	top in a specified company manufactured box with			
	suitable rating MCB for AIR CONDITIONS	set	7	
6	Supply&Installation of 63A 4Pole Change over switch	set	1	
7	Supply and Fixing for 63A Phase Selector switch with			
	enclosure and adopter boxes if necessary,	set	2	
_				
С	LT CABLES			

1	Complete the state of the state					
1	Supply&Laying of the following cables in built up					
	trenches,on wall, or in the ground as per the case may be,					
	with proper clamping with necessary fixing materials etc.					
	Installing testing&commisiong of 1100V grede UG					
	cable as per IS 7098/1554 (Finolex/ Universal)	2.4	22			
	3.5Corex50Sqmm Aluminium Armored cable Main DB	Mtr	33		_	
	3.5Corex35Sqmm Aluminium Armored cable power DB	Mtr	18			
	3.5Corex16Sqmm Aluminium Armored cable LDB Main	Mtr	28		_	
2	End Termination of the above cables with proper Glands				_	
	and Lugs	6 .			_	
	3.5Corex50Sqmm Aluminium Armored cable Main DB	Set	2		_	
	3.5Corex35Sqmm Aluminium Armored cable power DB	Set	2		_	
	3.5Corex16Sqmm Aluminium Armored cable LDB Main	Set	4		-	
					-	
D	WIRING				-	
1	Light/Fan point wiring with 3 of 1.5 sqmm PVC					
	insulated copper conductor to be laid in 2mm suitable				1	
	PVC conduit with Bend, Couplings, etc And fixing with			1		
	clamps screws etc.All conduits to be laid above the				_	
	false ceiling/partition/concealed in the wall					
	etc. Wiring to be connected with supply&Fixing of				1	
	6A Modular type switch(MK/ROMA) with suitable					
	Modular plate and metal Box					
	a) One light Controlled by One Switch	Pts	15			
	b) Two light Controlled by One Switch	pts	15			
	c) 6A Switch box Sockets in the switch board itself	Pts	9			
	d) Ceiling fan with regulator	Pts	4			
	e) wall bracket fan point (6A socket with 6A switch)	pts	9			
	f) Calling bell point with Calling bell instrument	Pts	1			
	g)Exhaust fan point	pts	3			
					_	
2	Supply&Wiring with Flame Retardant				-	
	insulated PVc wire as per grade IS 994				-	
	for Circuits,Computer point,Power points within 2mm thk				-	
	PVc conduits with necessary accessories and with					
	proper clamps and to be concealed below the false					
	ceiling It comprises as follows:-					
	a) 3Runs of 2.5Sqmmcopper wire in PVC conduit for				1	
<u> </u>	lighting circuit mains	Mtr	175			
	b) 3Runs of 2.5Sqmmcopper wire in PVC conduit for		. — ·		_	
	Power points	Mtr	170		1	
	C) 3Runs of 2.5Sqmm copper wire in PVC conduit for					
	computer points	Mtr	180		_	
	d) 2Runs of 4Sqmm copper wire+1.5Sqmm copper				1	
	wire in PVC conduit A/C Wiring	Mtr	180			
		1		1		
	e) 2Runs of 6Samm copper wire+2.5Samm copper					
	e) 2Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit	Mtr	35			
	wire in PVC conduit	Mtr	35			
	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper					
	wire in PVC conduit	Mtr	35 25			
F	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit					
E 1	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit POWER POINT OUTLETS					
E 1	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit POWER POINT OUTLETS Supply&Installation of 3 Nos of 6A Sockets controlled by					
_	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit POWER POINT OUTLETS Supply&Installation of 3 Nos of 6A Sockets controlled by 2of 5A Switches with front plate with enclosure and	Mtr	25			
1	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit POWER POINT OUTLETS Supply&Installation of 3 Nos of 6A Sockets controlled by 2of 5A Switches with front plate with enclosure and other accessories etc(MK /ROMA)					
	wire in PVC conduit f) 4Runs of 6Sqmm copper wire+2.5Sqmm copper wire in PVC conduit POWER POINT OUTLETS Supply&Installation of 3 Nos of 6A Sockets controlled by 2of 5A Switches with front plate with enclosure and	Mtr	25			

			_	1	
	accessories etc(MK /ROMA)	Set	10		
3	Supply&Installation of 1Nos of 16A Socket controlled by				
	1No 16A Switch with front plate with enclosure and other				
	accessories etc(MK /ROMA)	set	4		
F	LIGHTING FIXTURES				
1					
	Supply, Fixing & Commisioning of Recess mounting type compact				
	vertical Flat Panel 34W LED fitting in Down Rods with white finish and				
	other fixing accessories.(Crompton, Wipro, Philips)	set	15		
2					
	Supply, Fixing & Commisioning of Recess mounting type compact				
	vertical round shaped 1x15W LED downlighter fitting with white finish				
	and other fixing accessories.,(Crompton, Wipro,Philips)	set	4		
3	Supply&Fixing of Patti Type LED 20Watts Fiitings (Crompton,				
	Wipro,Philips)	Set	8		
4	Supply&Fixing exhaust fan(Crompton, Almonard)	set	3		
5	Supply&Fixing & Commisioning of wall mounting Mettal fan				
	with necessary Down Rods and with all				
	fixing accessories.,(Crompton / Havells)	Set	9		
6	Supply&Fixing & Commisioning of 48" ceiling fan				
	with necessary Down Rods and with all				
	fixing accessories.,(Crompton / Havells)	Set	4		
G	EARTHING				
1	Providing dedicated earthing with 600x600x3.15				
	mm copper plate along with 50mm dia.10feet				
	long G.I pipe with other accessories in the earth				
	filled with necessary salt, charcoal, etc. It should				
	be covered with G.I Manhole cover with necessary				
	civil works.etc	Set	1		
2	Supply & Laying of 10 Sqmm PVC Insulated Multi				
	strand copper conductor laid in 25mm dia PVC pipe for				
	Dedicated earth leads from the earth electrodes to				
	the UPSsystem	Mtr	30		
3	Providing general earthing with 50mm dia.10feet				
	long G.I pipe with other accessories in the earth				1
	filled with necessary salt, charcoal, etc. It should				
	be covered with G.I Manhole cover with necessary				1
	civil works.etc	Set	1		
<u> </u>	la Lau : fogue				1
4	Supply&Laying of 8SWG copper wire	Mtr	52		1
<u> </u>	TELECOMMUNICATION				
-	TELECOMMUNICATION			ļ	1
1	Supply&Laying of 2 Pair Telephone Cable within PVC		400		
	Conduit and its necessary accessories etc	Mtr	130		
	Complete Lordon of 200ps in Tolombons Coldensisting DVC				
2	Supply&Laying of 20Pair Telephone Cable within PVC	P.44	20		
	Conduit and its necessary accessories etc	Mtr	30		1
_	Comple Clastellation of DIV to device the control of				
3	Supply&Installation of RJ II Jack with necessary Face	Cat	10		
	plate and Box for connecting telephone points	Set	10		
	Cumply 9 fiving of 10 pain KDONE Downsith to the addition	Cat	4		
4	Supply & fixing of 10 pair KRONE Box with lock and key	Set	1		-
	TOTAL				

EDAIYUR BRANCH & ATM - DATA CABLING WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

	(NAGAPATTINAM ZONE)								
	BILL OF QUANTITIES								
S.No	Description Of Work	Unit	Qty	Rate	Amount				
	DATA CABLING								
1	Supply&Laying of CAT 6 Data Communication cable in 2mm								
	thk heavy duty 20mm dia PVC conduit and makinng holes in								
	the aluminium partitions/wall all accessories as required (DLink)	Mtr	180						
2	Supply&Installation,Testing&Commisioing of Modular type								
	1Nos of RJ45 Female Jack housed in GI anodised metal box								
	with suitable Faceplate fixing the same in the wall/partitions								
	with all accessories etc. as required.	Set	9						
3	Supply and fixing of 1M Mounting Cord	Set	9						
4	Supply and fixing of 2M Mounting Cord	Set	9						
5	Supply&Installation of 24por cat6 SWITCH	Set	1						
6	Supply and installation of 24port cat 6 jack panel	Set	1						
7	Supply and installation of 9u wall mounting rack	Set	1						
	TOTAL								

EDAIYUR BRANCH - AIR CONDITIONING WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

Sl.No	Description Of Work	Unit	Qty	Rate	Amount
1	Supply, Testing and commissioning of	Oint	Qιγ	Nate	Amount
	indoor and outdoor split air conditioner with remote				
	control, with 3 star rating units and necessary civil				
	works etc., The rate of units is including the supply				
	and laying of 3 mtr of copper pipes with insulations,				
	rubbers, white cements etc., (Brand: Voltas)	2	N		
a	1.5 TR - Manager & Server&Hall	2	No		
b	2 TR - Banking hall and manager	4	No		
2	Supply and laying of copper pipes with rubber				
	insulations, rubbers, white cements etc.,	35	Mtr		
3	Supply and installation of Stabilizer for following				
	units				
а	1.5 TR - 4 KVA	2	No		
b	2 TR - 5 KVA	4	No		
b	Installation Charges for 1 Tr,2 Tr Split Air Conditioner	6	No		
4	Supply and Installation of Outdoor Stand with				
	necessary civil works	6	No		
5	Supply and laying of PVC Blue pipes for water				
	drain from the indoor units.	55	Mtr		
	Civil works like cutting AC hole, packing, drain pipe cutting and				
6	packing with mortar etc.	1	Ls		
7	Supply and fixing Timer controlled for server Unit	1	No		
	Airconditioning works Total:				

EDAIYUR - ATM INTERIOR WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

	BILL OF QUANTITIES								
S.No	ITEMS AND DESCRIPTION	QTY	UNIT	RATE	AMOUNT				
1	FULLY GLAZED ALUMINIUM PARTITION & DOOR								
	EDONE DOWN CADE ENVED DADERSON D 1	70	O.C.						
a	FRONT BOTH SIDE FIXED PARTITION: Providing	70	Sft						
	and fixing Fully glazed partition in ATM Entrance , made of aluminium MRF vapocured twin style								
	frame work of size:-58 x38mm, 20 micron of IB-								
	Black colour finished with 10 mm thk float glass								
	with derk silicon (SAINT GOBAIN or MODIGUARD) up								
	to the false ceiling level. Support to be done to the rcc								
	ceiling, but measurements would be taken below the								
	false ceiling level only.								
b	ENTRANCE DOOR (Size : 3'6"x7'0") : Providing and	25	Sft						
	fixing of Fully glazed door for ATM entrance, made of								
	aluminium MRF vapocured twin style frame of size:- 100 x 50 mm, 20 micron of approved colour								
	finished with 10 mm edge polished glass with								
	silicon (SAINT GOBAIN or MODIGUARD) up to the								
	7'0" height, door to be provided with dorma make 12 "								
	SS handle, lock and door closure(approved make) &								
	stopper								
2	ACP WALL PANELLING								
	Providing and fixing Wall Panelling using 3mm thk	288	Sft						
	Aluminium Composite Panels of Alstrong or equivalant make over necessary frame work. The								
	joints formed by the junction of two panels shall be								
	filled with silicon sealent. The Wall Panelling / Boxing								
	shall be erected 75 mm above the Highest False								
	Ceiling Level. However, only exposed portions below								
	the Highest False Ceiling Level shall be considered for								
	payment. Pattern of wall panelling to be got colour								
	approved from the Bank.								

4	GYPBOARD FALSE CEILING			
	Supply and erection of gypboard false ceiling for Manager cabin area at single level with framework of G.I. Section of spacing 4'0" x 2'0" above with 12mm gypboard fixing. Recessed ceiling is to be done as per architects instruction to have provision for indirect lighting rate is included for cutouts for lights, smoke detectors and AC grills. The ceiling is putty finished and sanded to form clean and homogeneous surface. Rate is included for two coats of acrylic emulsion painting.	100	sft	
5	ATM SOCKETS COVER BOX (1'0"X1'0"x6" - 1no)			
	All ATM Sockets, IO Box to be covered using 12mm plywood structure with 1mm thk lamination finish (matching ACP color colour), Shutter type door (up & down) with lock, handle and necessary wire manager groove (at bottom) to be provided.	2	nos	
6	PIN-UP NOTICE BOARD			
7	Providing & fixing Pin-up Board of approx size of 600mm x 800mm made of textile wrapped on 12 mm thick soft board with 6 mm com ply backing and a frame work of 50mm wide with 24 mm thk com ply, finished with 1 mm thk Laminate. The Pin-up Board shall be set into the wall panelling with necessary fittings as directed by the Bank. WRITING DESK	1	no	
	Writing desk to be done as per plan with 12mm glass topped with pigeon holes made with 18mm plywood structure with additional boxing as per design,	1	no	
8	CHEQUE DROP BOX/ COMPLAINT			
	Providing cheque drop box/Complaint/Suggestion 1'6" length, 0'9" wideand 1'6" height with 19mmtk. Plywood and lined with 1mmtk. Laminate (Fusion Maple Wood finish) for top & exposed sides. Exposed edges of plywood shall be fixed with teak wood be ading suitably polished and the back sides hall be covered with 6mmtk. plywood. The innersides shall be painted with two coats of enamel paint over a coat of primer & two coats of putty.	1	no	
9	ROLLING SHUTTER COVER BOX			
	Supplying & fixing of shutter box using 19 mm plywood, boxing with above entrance partiton and rolling shutter and finished with 1mm lamination.	40	sft	
	TOTAL			

EDAIYUR ATM - ELECTRICAL WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

SI.	Description	Qty	Unit	Rate	Amoun
Α	MAINS & DISTRIBUTION BOARDS				
1	Supply, erection, testing and commissioning of three				
	phase 4 WAY, TPN MCB DB double door vertical type,				
	IP 42 powder coated with				
	40A TPN MCB – 1No as INCOMER				
	32A DP MCB-1No For UPS				
	10/25/32A – 4No.s as OUTGOING				
	Including all interconnections & accessories etc	1	No		
В	POWER CABLES & CONDUIT WIRING				
1	Supplying, laying, testing & commissioning of PVC /				
	LT insulated 1.1KV grade aluminium armoured				
	conductor cables of the following sizes, laid in trenches				
	below ground level/ clamped on to the walls as per site				
	condition.				
а	3.5C x 25Sqmm aluminium armoured PVC cable	18	mtr		
С	Supplying and terminating the end of cables of the				
	following sizes using Siemens type single compression				
	cable glands, crimping type aluminium / copper				
	sockets of required size, gland earthing clips etc.,				
	complete.				
а	3.5C x 25Sqmm aluminium armoured PVC cable	2	Set		
	·				
D	AIR CONDITIONING WIRING & ACCESSORIES				
1	Supply&Installation of 32A Metal Clad Socket with				
	top in a specified company manufactured box with				
	suitable rating MCB for AIR CONDITIONS	2	No		
2	Wiring in position 2 runs of 4.0 sq.mm. cable and 1 run				
	of 2.5 sq.mm cable for earth from Main D.B. to 2 Nos				
	split air – conditioners in P.V.C. conduit pipes including				
	chasing in walls / floor wherever necessary.	20	Mtr		
E	UPS WIRING & ACCESSORIES				
1	Supply, erection, testing and commissioning of single				
	phase 6 WAY, SPN MCBDB double door type, IP 42				
	powder coated for UPS and Emergency Lighting with				
	40A DP MCB – 1No as INCOMER				
	10A SP MCB – 4Nos. as OUTGOING				
	Including all interconnections & accessories etc.,				
	complete.	1	Set		
2	Wiring in position 2 runs of 6.0 sq.mm. cable and 1 run				
	of 4.0 sq.mm cable for earth from Main D.B. to UPS and				
	UPS to UPS DB.	10	Mtr		
		-			
3	Wiring in position 3 runs of 2.5.sq.mm cable for circuits from				
-	UPS.Lighting,Raw power required places in P.V.C. Conduit pipes				
	including chasing in walls / floor wherever necessary	35	Mtr		
		- 55		}	

4	Supply, fixing, testing & commissioning of 2No. 16A			
	multi pin socket outlet in UPS circuit controlled with			
	1No. 16A one way switch in a steel sheet enclosure with			
	8 module top plate including dummies and incidental			
	materials etc.,	2	No	
	·			
F	LIGHTING WIRING			
	Supply, fixing, testing & commissioning of the following			
	switch controls in steel sheet enclosure including 3 runs			
	of 1.5sqmm, steel sheet enclosure & modular top plate			
	and all incidental materials etc., complete.			
1	One light Controlled by One Switch	3	No	
2	1 No. 6A socket controlled by single switch	2	No	
G	LIGHTING & FIXTURES			
1	SFTC for the following light fittings with required			
	hardwares such as suspension wires from ceiling, false			
	ceiling, anchor fasteners, chains, bolts, nuts etc.,			
	complete.			
a	36 watts LED light fitting with 2'X2'	1	No	
b	15 watts LED round fitting with LED as2	4	No	
С	20watts LED Patty fitting	1	No	
Н	DATA POINT			
1	Supply&Laying of CAT 6 Data Communication cable in 2mm thk heavy			
	duty 20mm dia PVC conduit	38	mtr	
2	Supply&Installation,Testing&Commisioing of Modular type			
	1Nos of RJ45 Female Jack housed in GI anodised metal box			
	with suitable Faceplate fixing the same in the wall/partitions			
	with all accessories etc. as required.	2	No	
	With an accessories etc. as required.		110	
I	EARTHING			
1	Providing earthing two numbers , One for ATM and			
	another for AIR-CONDITIONERS including excavating			
	the P.C.C. floor/ earth to 6'0" depth and providing			
	earthing with 50mm dia. G.I. pipe with perforations			
	connected through copper wire including copper flat			
	including copper plate of size 300mm x 300mm, G.I.			
	bolts and filled up with layers of charcoal, salt and			
	earth. (Earth provided for computers shall not be used			
	for any other purpose)	1	No	
	Complaine and legine of C Company and this translation and			
2	Supplying and laying of 6 Sqmm multi stranded copper		+ +	
	wire for UPS earth in suitable PVC conduit with all	10	N.4+::	
	incidental materials etc., complete. Total	18	Mtr	

NAGAPATTINAM ATM - AIR CONDITIONING WORKS FOR INDIAN BANK (NAGAPATTINAM ZONE)

Sl.No	Description Of Work	Unit	Qty	Rate	Amount
1	Supply, Testing and commissioning of				
	indoor and outdoor split air conditioner with remote				
	control, with 3 star rating units and necessary civil				
	works etc., The rate of units is including the supply				
	and laying of 3 mtr of copper pipes with insulations,				
	rubbers, white cements etc., (Brand: Voltas)				
b	1 TR - Manager & Server	2	No		
2	Supply and laying of copper pipes with rubber				
	insulations, rubbers, white cements etc.,	20	Mtr		
3	Supply and installation of Stabilizer for following				
	units				
а	1.5 TR - 3 KVA	2	No		
b	Installation Charges for 1 Tr Split Air Conditioner	2	No		
4	Supply and Installation of Outdoor Stand with				
	necessary civil works	2	No		
5	Supply and laying of PVC Blue pipes for water				
	drain from the indoor units.	18	Mtr		
6	Civil works like cutting AC hole,packing,drain pipe cutting				
	and packing with mortar etc.	1	Ls		
7	Supply and fixing for Timer for A/C Controlled	1	No		
	Airconditioning works Total:				