BILL OF QUANTITY FOR FURNISHING WORKS FOR ATM OF INDIAN BANK AT S.P MARG BRANCH, CIVIL LINES ,PRAYAGRAJ

S.NO.	PARTICULAR OF ITEM	Quantity	UNIT	RATE RS. P.	PER	Amount RS.P
1	Shutter Boxing & ATM Paneling			1		
	Providing & Fixing in position partition made of ACP(Aluminium Composite Panel) with framing of Aluminium Tube section of min 1.5"X1" and 18 gauge 2'-0" C/C both ways ACP to be in 2' wide panels or distributed equally. The panels to be fixed to the frame with 3M or equivalent adhesive . Joints to be finished with Silicon based sealant . ACP thickness of 3mm minimum.Aluminum foil thichkness to be .15mm. ACP only on the ATM side with thickness of 3mm minimum . The back side of the partition to be finished with painted 6mm ply. Alubond, Eurobond , Fujibond, Alcobond or equivalent brands to be used. ACP Door 3'X7' made of Aluminum frame.	45	SQM		SQM	
			2014		2014	
2	Flase ceiling (Armstrong)	4.5	SQM		SQM	
	Providing and fixing 12 mm th 600 mm x 600 mm mineral fiber tiles false ceiling of Armstrongapproved of micro look system including suspension system as per manufacturer's specifications and instructions of Architect/ Engineer complete in all respects including making cutouts where necessary for electrical lighting fittings etc. complete all as directed by the Bank.					
				1		
3	Entrance Door /Fixed glazing	4	SQM	0	SQM	0

Providing fabricating & fixing in	
position single leaf at Main Entrance	
made of frameless or toughened	
12mm thick glass(Modi/ Saint Gobain	
make) including fixing the frame to	
brick wall/RCC/wooden surfaces with	
necessary fasteners to have proper	
fixity including all incidentals etc	
complete. Glass to be fixed in the	
grooves of the teak wood/al. sections	
with necessary materials/beading etc.	
The job also includes cost of providing	
& fixing heavy duty double action	
hydraulic floor spring (ISI mark) in	
the floor, fixing the door on it,	
including necessary fixing materials	
on the lintel/bottom, bolts, locks &	
satin finish stainless steel decorative	
tubular handles(approx.300mm long)	
on both faces complete as per	
drawing and instructions. The	
exposed teak wood surfaces to be	
polished in approved shade N.C	
lacquer in mat satin finish. The rate	
should also include cost for	
decorative etching on the glass.	

RS.

I

SPECIFICATIONS OF MATERIAL

S.No.	Item	Make/Specifications
1	BLOCK BOARD	Century /Kitply/ Green (BWP Grade)
2	PLY BOARD	Century /Kitply/ Green (BWP Grade)
3	LAMINATES	
	A)FOR	Century Ply :303- Bodensee Beech,
	PARTITIONS/TABLES/COUNTER	Sunmica : E-224/1224-Steam Beech,
	SURFACES	Formica-FI-1224(SF)-Steam Beech-I,
		Greenlam : 685-Swiss Pear
	A)FOR BOARDER AND	Century :191-RADIENT RED,
	SKIRTING	Sunmica : G-448/1448-TERACOTTA,
	_	Formica-FI-1517(SF)-SIENNA,
		Greenlam : 165-LIGHT RED
4	GLASS	Modi/Saint Gobin/ Indo Asahi/Triveni
5	GYP BOARD	India Gypsum or equivalent approved.
6	LOCKS/HANDLES	Godrej/Harrison/Vijayan
7	DRAWER SLIDING FITTING	Earl Bihari (EBCO)/Godrej/Blum or equivalent
		approved.
8	FLOOR SPRING/DOOR CLOSER	Sandhu / Hemco / Hardwin or equivalent approved.
9	ACP	ALSTRONG, ALUTUFF
10	White Cement	J.K., Birla, Nitco
11	Aluminium Section	Jindal, Hindalco
12	O.B.D./Emulsion/Enamel	Nerolac Asian, Berger,
13	OTHER MATERIALS	ISI MARK & APPROVED BY THE BANK