



FGM Office, Lucknow,
1st Floor, New Building,
Hazaratganj,
Lucknow-226001

**BID DOCUMENT - PROVIDING & FIXING OF
MODULARWORK STATION FOR SETTING OF FGM
Office, Lucknow, 1st Floor, New Building, Hazaratganj,
Lucknow-226001**

PART-II FINANCIAL BID

Ref.No: CO:EST:FGMO -02

Date : 20.03.2025

Name of the contractor:

.....
.....
.....

Last date of submission of tenders	02.04.2025 upto 15.00Hrs. at Indian Bank, FGM Office, Lucknow, 1st Floor, New Building, Hazaratganj, Lucknow-226001
Date of opening Tender	02.04.2025 upto 15.30Hrs . at Indian Bank, FGM Office, Lucknow, 1st Floor, New Building, Hazaratganj, Lucknow-226001
Cost Of Tender	Free Of Cost.

This part of the tender should be submitted in a separate envelope and financial bid shall be quoted only in this form and no other form will be accepted.

This Tender document contains 04 pages

Schedule of Quantities

**Quote for Providing Modular Works Station for Setting of Indian Bank FGM Office,
Lucknow, 1st Floor, New Building, Hazaratganj, Lucknow-226001**

MODULAR WORKS STATION					
SL:NO	Description	Unit	Number	Amount	Total Amount
	Table				
1	<p>Supplying and installation of Table and Side unit as per specification:-</p> <p>Main Table : Understructure made of straight leg which should be fabricated with cross connector by welding MS CRCA ERW Square Tube of size 50.8mm X50.8mm x 1.6 mm thk with the base of MS tube fitted with Glide Plate Over M8 X50mm metal leveller. The leg shall be supported by the cross connector, which shall be MS ERW RHS 50 mm X30mm (RHS) ,1.6 mm thick members at two levels in 3 side along with 500mm ht X1.2 mm thick CRCA sheet as a perforated stiffener (Laser cutting as per design) by suitable welding. The under structure shall be finished within 60 -80 micron thickness of epoxy polyester powder coating.(Colour to be approved by the Bank) The table top shall be ,25 mm thick of Grade II Type II conforming to IS 3087-2005 with twin pre laminated finishes with 2 mm pvc edging , approved shade . On top of table 12 mm thick toughened glass with lacquered finish shall be fitted with all accessories</p> <p>Side Table : The same as above but to be fitted on the MS straight leg by suitable accessories the rate inclusive of providing wire management by Soft closing access flap as per approval. The rate including accessories: Metal CPU trolley (safe load 20 Kgs). & Key board tray should have 1.2 mm thick CRCA sheet with slides Tray size should be 540mm* 197mm fixed on the side table top (botton side).</p>				
a	Table size: 1650*750*750 mm and Side table: 1350mm*450*750 mm for DGM	Nos	1		
b	Table size: 1500*750*750 mm and Side table: 1050mm*450*750 mm for AGM	Nos	2		
c	Table size: 1500*750*750 mm and Side table: 1050mm*450*750 mm for CM without Table Top glass	Nos	6		
2	Linear Workstation				

<p>Supplying and installation of Linear Working Table ,25 mm thick 0.8 mm twin pre laminated post formed table top with under structure ,Race way,Softclosing access flap etc, Privacy Divider (by Glass & Magnetic Fabric Board), Metal Key board & C.P.U trolley as per below specification.Under Structure : Under structure made of straight leg which should be fabricated with cross connector by CO2 welding MS ERW Tube of size 50.8mmX50.8 Dia x 1.5 mm thk with the base of MS tube fitted with Glide Plate Over M8 X50mm PU leveller. The leg shall be supported by the cross connector ,which shall be MS ERW RHS 50.8mm X30mm (RHS) ,1.5 mm thick members at upper level.The rate inclusive of 400mm X 1.2 mm thick CRCA sheet as a perforated stiffner (Lazer cutting as per design) by suitable welding. Wire Management Suitable MS race way shall be provided for vertical & horizontal wire mangment in the middle of the under structure along with provision for 20 modular swith plate in build metal power box . The under stucture including race ways shall be finished within Min 50 micron thickness of epoxy polyster powder coating.</p> <p>Table Top : Table Top shall be ,25 mm thick of Grade II Type II conforming to IS 3087-2005 with twin pre laminated IS 12823:1990 (reaffirmed 2005) finished of approved shade The particle shall be of uniform thickness and uniform density through the length and width of the boards, with 2mm PVC edge banding finishes. All particle boards shall be flat. Both surfaces of the particle boards shall be sanded to a smooth finish and same shall be fixed 25mm metal clip support (or approved clip) with under structure ,Race way,Softclosing access flap etc, Privacy Divider (by White board & Magnetic Fabric Board), C.P.U trolley as per below specification. The rate including accessories: Metal CPU trolley (safe load 20 Kgs). Key board tray should have 1.2 mm thick CRCA sheet with slides Tray size should be 540mm* 197mm fixed on the able top(botton side).</p> <p>Privacy Divider (partition) in Middle of the of the table : 450 mm height Privacy panel shall be provide in centre for the entire length of linear table. The privacy panel partition shall be 30 mm thick powder coated suitable aluminium extrusion vertical trim and horizonatal trim . The privacy panel shallbe White board & Magnetic Fabric Board back to back. The fabrics should be upholstered with adhesives back to back, The suitable fixing arrangement to be made for firmly fixation on the under structure.</p> <p>Privacy panel :Glass Partition between two works station for a height of 200mm at centre and 100 mm at end , The rate inclusive of providing & fixing of 10mm thk toughned intermediate bevelled glass divider (side) between two workstation table with necessary fittings & hardware as per approved design above table top. The rate inclusive of necessary fittings & hardware as per approved design above table top.</p> <p>The Cost to include the supporting system to privacy divider & under structure such as brackets / fasteners /joining posts / race ways / wire management cleats / runners etc.(Basic cost of fabric Rs. 300/- per running meter.) The shop drawing shall be approved</p>				
Sharing ,Size :1350X750X750mm	Nos	24		

3	<p>Mobile Pedestal :</p> <p>Providing and installing drawer boxes (Box Box File)of size 650 mm ht., 390mm width and 450 mm deep made out of 18mm thk pre laminated particle board Grade II & Type-II (IS12823: 1990; Reaffirmed 2005) finished with 0.8mm thk laminate twin side, front and sides made of 18 mm thk pre laminated particle board Grade II & Type-II (IS 12823: 1990;Reaffirmed 2005)finished in 0.8mm thk laminate and back, drawer bottom to shall be Tandem box ,2 nos. minimum 120mm high drawer & 1minimum 275mm high filing drawer.Handles to be provided. Central locking to be given for each pedestal Soft closing and Anti slam mechanism for pedestal. M8 Leveling stud for free standing pedestal. The anti-tipping mechanism should have fitted in the roller arrangement mounted below file drawer to avoid toppling of unit when file drawer is pulled out. The colour and selection of tandem shall be approved by Bank</p>	Nos	35		
4	<p>Manufacture, Supply and Installation in position Footrest as directed will be Made from high impact polystyrene , Large platform: 450mm x 350mm., Load capacity: 20 kilograms, Non Slip surface enhances overall stability. Tilts (0° to 20°) to provide the most comfortable angle., Color FINISH Black, BRAND Ebco.</p>	Nos	35		
	Summary of modular work station		Amount		
1	Table & Side Unit				
2	Linear Work Station ,Sizes :1350X750X750mm				
3	Mobile Pedestal				
4	Foot Rest				
	Total				
	Remark				

Total Amount in words: Rupees.....only

GST (taxes) will be extra

Place:

Signature & Seal of the Tenderer

Date: