

PREMISES DEPARTMENT ZONAL OFFICE LUCKNOW

TENDER DOCUMENT INTERIOR FURNISHING & ELECTRICAL WORK (INCLUDING LAN CABLING) IN EXISTING PREMISES OF INDIANBANK- K S SAKET BRANCH, DISTRICT- AYODHYA

PART I - TECHNICAL BID

Issued to:

Date: 03.04.2025

•••••				
Last date for submission of Bid	16.04.2025 upto 17:00 HRS at Indian Bank, Zonal Office Lucknow, Premises Department, 2 ND Floor, New Building, Hazratganj, Lucknow -226001			
Date of Opening of Tender	17.04.2025 upto 17:00 HRS at Indian Bank, Zonal Office Lucknow, Premises Department, 2 ND Floor, New Building, Hazratganj, Lucknow -226001			



ZONALOFFICE-LUCKNOW

NOTICE INVITING TENDER

Indian Bank, Zonal Office Lucknow invites sealed bids under Two Bid System containing Part-I (Technical Bid) & Part –II (Financial Bid) from Established Contractors complying minimum qualification criteria for Interior Furnishing & Electrical Work (including LAN cabling) as per Tender and having full time local office at Prayagraj / Varanasi / Lucknow /Gorakhpur / Kanpur for "Tender for Interior Furnishing & Electrical Work (including LAN cabling) in Existing branch Premises of Indian Bank – K S Saket Branch, District – Ayodhya". The Tender Documents can be downloaded from the Bank's website (www.indianbank.in) under Tender Column.

1.	Name of work	Interior Furnishing & Electrical Work (including LAN cabling) in Existing Branch Premises of Indian Bank–K S Saket Branch, District– Ayodhya			
2.	Period of completion	20 days to be reckoned from 4 th day from the date of issue of the Work Order or handing over of site whichever is later			
3.	Validity of Tender	90 Days from the date of opening			
4.	Defects Liability Period	12 Months from the date of virtual completion of work			
5.	Estimated cost of work	Rs. 9.58 Lacs			
6.	Earnest Money Deposit	Rs.10,000/- (Rupees Ten thousand only) by way of DD in favour of Indian Bank payable at Hazratganj. *Firms registered with MSME/ NSIC with valid certificates issued by GOI are exempted from submitting EMD along with bid.			
7.	Retention Money(RM)	10% of the Bill Amount (Final Bill) excluding Taxes			
8.	Interim / Adhoc Payment	No Interim/Adhoc Payment is allowed.			
9.	Liquidated Damages	1% per week of the Contract Value subject to maximum total of 10% official Contract value			
10.	Tender Documents	Tender documents can be obtained from the Bank's website (www.indianbank.in) under Tenders column.			
11.	Last date for the submission of Bids	16.04.2025 upto 17:00 HRS at Indian Bank, Zonal Office Lucknow, Premises Department, 2ND Floor, New Building, Hazratganj, Lucknow - 226001			
12.	Date of opening of Tender	17.04.2025 upto 17:00 HRS at Indian Bank, Zonal Office Lucknow, Premises Department, 2 ND Floor, New Building, Hazratganj, Lucknow - 226001			
13.	Minimum Eligibility Criteria	 Should be in same line of activity minimum for the past 5 years in carrying out similar nature of works ending 31.03.2024. PleasefurnishPurchaseOrder/WorkOrder/Client'sCompletionCertificate / Empanelment Letter issued by PSBs/ PSUs/Central Government /State Government to confirm the same. Should have Registered Office in Prayagraj/Varanasi/Lucknow/ Gorakhpur / Kanpur Please furnish requisite document as proof. 			



3. Should have carried out similar work in the last 3 years in Public Sector Banks.

Copy of TDS Certificate & Work Order / Completion Certificate showing value of work satisfying the above eligibility criteria is to be enclosed.

Similar works means: Interior Furnishing Work (Wall Paneling, Partition Work, False Ceiling & Other Interior Works), Electrical Wiring Works, Supply, Installation of Electrical Panels (HT / LT), Distribution Boards, Earthing Works, Data Works (LAN Works), etc for any Public Sector Banks/Public Sector Units/Central or State Government Departments.

- 4. Should be empanelled in at least 2 Public Sector Banks / Public Sector Units / Central or State Governments

 Please furnish copy of valid empanelment letters as documentary proof
- 5. Contractors applying for this tender should possess the valid "A" Class Electrical contractor's license, issued by the Electrical Inspector to Government, Uttar Pradesh, Lucknow in the name of the contractor or permanent employee of the company. Photocopy of such license should be submitted with the application.
 - 6. Should have valid GST No.
 - 7. Should be registered with Income Tax Authority

The bidders must satisfy the above criteria and furnish the relevant documents as proof. If the Vendors fails to provide relevant documents and meet the minimum eligibility criteria as mentioned above, Bank would disqualify the bidder without assigning any reason whatsoever.

Note:

- 1. Tenderers are required to submit the bid in 2 parts namely Technical bid and financial bid. The Technical bidis to be submitted in sealed cover along with, Necessary documents prescribed in the Bids, Forms and EMD. The Financial bid shall be submitted in a separate sealed cover. The Technical and Financial bids are to be put in a master envelope (3rd Cover) and sealed and super-scribed 'Tender for Interior Furnishing & electrical Works (including LAN cabling) in Existing branch Premises & ATM room of Indian Bank K S Saket Branch, District Ayodhya and addressed to the Zonal Manager, Indian Bank, Zonal Office Lucknow, Premises Department, 2ND Floor, New Building, Hazratganj, Lucknow -226001. Conditional tenders, late tenders, tenders without EMD or EMD not enclosed with Technical Bids, will be summarily rejected. Any tender received open, late or not meeting all the tender conditions /Bids not filled up in Pen are liable to be rejected.
- 2. Earnest money will not carry any interest.
- 3. Sincethebranchisexistingrunningbranchhencedismantlingofexistingfurnishingwillberequiredtocarry



our new furnishing hence financials should be inclusive of dismantling cost. **No additional payment will be made for any dismantling work in branch.**

- 4. If any information furnished by the applicant is found incorrect at a later stage, he shall be liable to be debarred from taking up the work in Indian Bank.
- 5. TheBankreservestherighttoverifytheparticularsfurnishedbytheapplicantindependently.
- 6. Short-listing of contractors will be finalized after inspection of works and obtaining confidential reports (if required) from previous employers for only those firms who fulfill the aforesaid Pre- qualification criteria and that specified in Technical bid.
- 7. Bank is not bound to accept the Lowest (L1) bidder and reserves the right to accept or reject any or all the tenders without assigning any reason whatsoever.
- 8. Submission of this tender document by a bidder implies that he/she has read this notice and other contract /documents and has made him self aware of the scope, specifications, conditions, liabilities and duties bearing on the execution of the contract.
- 9. Return of EMDofremainingbidderswhowereunsuccessfulinthebiddingprocesswillbedonewithina reasonable time say not exceeding 14 days from the date of acceptance of tender submitted by the L1 bidder.
- 10. Each and every page of the tender documents and correspondences accompanying the tender shall have to be duly signed and stamped by the Bidder / Authorised Signatory before submission.
- $11. \ The rates quoted by the bidders hall be based only on the specifications and conditions of the tender documents.$
- 12. Bankisnotliabletomakeanypaymenttobiddersforpreparationtosubmitthebid.
- 13. Clarifications, if any, pertaining to this bids may be referred to Indian Bank, Premises Department, Zonal Office Lucknow through E-mail Id **zoLucknow@indianbank.co.in**

ZONAL MANAGER



FORM OF TENDER

The Zonal Manager Indian Bank Zonal Office Lucknow 2ND Floor, New Building, Hazratganj, Lucknow -226001

Dear Sir,

SUB: Invitation of Tender for Interior Furnishing & Electrical Work (including LAN cabling) in Existing branch Premises & ATM room of Indian Bank-K S Saket Branch, District-Avodhya

Having examined the drawings, specifications, conditions and schedule of quantities prepared by you, and satisfying ourselves as to the location of the site and working conditions, I/We hereby offer to execute the above works at the respective rates which I/We have quoted for the items in the Schedule of Quantities.

I/We further agree to complete the work within the stipulated time as specified in the Tender Document.

I / We understand that Indian Bank is not bound to accept the lowest tender or bound to assign any reasons for rejecting our bid.

In the event of this bid being accepted, I/We agree to enter into and execute the necessary contract required by you. I/We do hereby bind myself/ourselves to forfeit the aforesaid Earnest Money Deposit of **Rs.10,000/-(Rupees Ten thousand only)** in the event of our refusal or delay in signing the Contract Agreement.

- I / We understand that Indian Bank may award the work to more than one Contractor and I / We shall make no claims whatsoever if Indian Bank accept only a part of my / our tender.
- I / We unconditionally agree to Indian Bank's conditions as stipulated in the Documents.

I/We agree to keep our bid open for **90(Ninety)** days from the date of opening of Tender.

I / We agree that incase of my / our failure to execute the work in accordance with the specifications and instructions received from the Bank during the course of the work, Bank reserves the right to terminate my work order and recover all the dues to the Bank from the payment receivable by me. Further, I may also be barred from participating in any type of bid invited by Bank or its subsidiaries in future. Thanking you,

Yours faithfully,

[To be signed by the Authoria	zed Representative of
Firm who has t	the Power to do so]

Place:	
Date :	Name:
	Address:
	Seal:



GENERAL INFORMATION OF THE FIRM

1	Name of the Applicant/Firm/ Organization	
2	Registered Address of the Firm (Please attach address proof as supporting document as Annexure - I)	
3	CONTACTDETAILS Landline No-	
	Mobile No-	
	FAX No –	
	Email Id -	
4	EMD Details	
	(i) Amount(Rs.)-	
	(ii) Demand Draft No	
	(iii) Name of the Bank-	
	(iv) Date –	
	(Please submit EMD Details as Annexure – II. If exempted, please submit requisite proof in the form of copy of self-attested valid certification from MSME and NSIC.)	
5	Year of Establishment (Enclose certified copies of documents as evidence - Annexure - III)	
6	Constitution of Firm (Enclose certified copies of documents as evidence – Annexure – IV)	Sole Proprietorship/Partnership/Private Ltd./ Public Ltd / Any other (Please specify)
7	Name of the Proprietor/Partners/Directors of the Organization / Firm with Qualification (Enclose certified copies of documents as evidence – Annexure – V)	
8	Name/s of Authorized Signatory/Directors/ Partners with Designation and Contact No.	
9	Mode of Authorization (Enclose certified copies of documents as evidence - Annexure - VI)	Resolution / Partnership Deed / Registered Power of Attorney/ Proprietor / Any Other (Please specify)

10	Details of Registration with Registrar of	
	Companies/ Registrar of Firms.	
	(Enclose certified copies of documents as evidence	
	– Annexure - VII)	
11	Whether registered as MSME Organization? If so,	
	provide the date of registration, validity &	
	License No	
	(Enclose certified copies of documents as	
	evidence-Annexure-VIII)	
12	Whether empanelled with Public Sector	YES / NO
	Banks/Public Sector Undertakings/Central	,
	Govt. Department / State Govt. Departments	
	or any other Government Organization and if	
	so, in which class and since when?	
	(Enclose Empanelment letters issued by the	
	Organizations - Annexure - IX)	
12	Number of years of experience in this field	
13	Number of years of experience in this field. (Enclose evidence to meet the eligibility criteria as	
	Annexure - X)	
	·	
14	Banker's Details-	
	(Please attach copy of cancelled cheque as proof	
	- Annexure - XI)	
	(i) Banker's Name:	
	(ii) Account No.:	
	(.,)	
	(iii) Type of Account:	
	(iv) IESC.	
1 5	(iv) IFSC:	
15	Registration with the Government Authorities (Enclose certified copies of documents as	
	(Enclose certified copies of documents as evidence – Annexure – XII)	
	,	
	If firm is exempt from ESI& EPF registration	
	as per extant guidelines, fill N.A. and an	
	undertaking is to be submitted stating the	
	same.	
	a) Income Tax(PAN) No.	
	a) moonie raktrintjito.	
	ii) Goods & Service Tax (GST)No.	
	iii) Labour License	
	iv) ESI	
	iv) ESI	
	v) EPF	
	, <u></u>	



16	Name & Value of Major Works Completed during the last 5 years.	
17	Name & Value of Major Works under execution	
18	Details of Key Personnel Permanently employed.	
19	Details of Equipment owned by Company	
20	Furnish the names of -3- responsible persons along with their designation, address, contact no., etc., for whose organization, you have completed the above-mentioned jobs and who will be in a position to certify about the quality as well as Performance of your organization.	
21	Information relating to whether any litigation is pending before any Arbitrator for adjudication of any litigation or else any litigation was disposed of during the last five years by an arbitrator. If so, the detail so f such litigation are required to be submitted.	
22	Has the applicant or any constituent partner in case of partnership firm/ Company, ever abandoned the awarded work before its completion? If so, give the name of the project And give reasons thereof.	
23	Has the applicant or any constituent partner incase of partnership firm / Company, ever been debarred/black listed for tendering in any organization at any time? If so, give details	

DECLARATION-

- $1. \quad All the information furnished by me/ushere above is correct to the best of myknowledge and belief.\\$
- $2. \quad I/We have no objection if enquiries are made about the work listed by me/us in the accompanying sheets/annexures.\\$
- $3. \hspace{0.5cm} I/We agree that the decision of Indian Bankins election of tenderers will be final and binding to me/us. \\$



- 4. I/We hereby confirm that our firm/agency/company has not been disqualified / debarred / blacklisted by any Governments, Semi-governments, PSUs, Banks including any of the Offices / Branch of Indian Bank Pan India during last 5 year from the date of application.
- 5. I/We hereby confirm that all information, particulars, copies of certificates and testimonials in connection with my/our empanelment are correct and genuine. I am / We are, therefore, liable to face appropriate actions as deemed fit by the Indian Bank in the event of any of the information, particulars, copies of certificates and testimonials are not found correct and genuine. I/We have read the instructions appended to the proforma and I/we understand that if any false information is detected at a later date, the empanelment shall be cancelled at the discretion of the Indian Bank.

DI		0	
DΙ	Λ		н_
1 I	лΠ	١.	ப

DATE-

SIGNATURE OF CONTRACTOR

NAME & DESIGNATION -

SEAL OF ORGANISATION-



(TO BE ISSUED ON LETTER HEAD OF ORGANIZATION)

Date -

TOWHOMSOEVERITMAY CONCERN

	•		, having their registered office at he work ofhave
Succ	essfully executed and completed the work	as detai	iled below:
1	Work Order No & Date	:	
2	Name of Work	:	
3	Brief Scope of Work	:	
4	Location of Work	:	
5	Value of Work as per Work Order	:	
6	Date of Commencement of Work	:	
7	Revised Value as per execution	:	
8	Completion Period	:	
9	Date of Actual Completion of Work	:	
10	Whether any Penalty/Liquidated Damages imposed. If Yes, please give the reasons	:	
11	Whether the contractor employed qualified	:	
12	Engineer/Overseer during execution of work Quality of work(indicate grading)	<u> </u>	Outstanding/Very Good/Good/Satisfactory/Poor
			- Cultivarianting, very Good, Good, Guitolation y/1 Gol
13	Did the contractor go for arbitration? If Yes, then:		
	i)Total amount of claim	:	
	ii)Total amount awarded	:	
14	Comments on the capabilities of the Contractor		Please tick one of the multiple options
	a)Technical Proficiency:	:	Outstanding/Very Good/Good/Satisfactory/Poor
	b)Financial Soundness	:	Outstanding/Very Good/Good/Satisfactory/Poor
	d)Mobilization of Man Power	:	Outstanding/Very Good/Good/Satisfactory/Poor
	d)General Behaviour	:	Outstanding/Very Good/Good/Satisfactory/Poor

Signature of Reporting Officer*with Office Seal

^{*}Officer not below the rank of Assistant Engineer or an Officer in an equivalent or higher rank for works carried out in Government Department / PSU's, Officer not below the rank of Sr.Manager of the Concerned Department/Branch Head in PSBs. For works carried out for Private companies, Copy of TDS has to be submitted for proving the credentials/contract amount. (Report must be submitted in Client's Official Letter Head and to be addressed to the enlistment authority: The Zonal Manager, Indian Bank, Zonal Office Lucknow, 2ND Floor, New Building, Hazratganj, Lucknow -226001



LISTOFENCLOSURES

ANNEXURE NO.	PARTICULARS	TICK IF ENCLOSED
I	Documentary Proof showing Registered Address	
II	Valid certificate from MSME and NSIC issued by Govt. of India	
III	Documentary Proof showing Year of Establishment of the Firm	
IV	Evidence showing Constitution of the Firm	
V	Certified Copies mentioning Name of Proprietor/Partner/Director of the Firm	
VI	Document showing appointment of Authorized Signatory of the Firm	
VII	Document showing details of Registration with Registrar of Firms/ Companies	
VIII	Certificate of being registered as MSME Organization, if mentioned.	
IX	Empanelment Letters	
X	Document showing experience in the field	
XI	Copy of Cancelled Cheque	
XIII	Documentary Proof of Registration in Various Govt. Authorities(PAN,GSTIN, Labour License, ESI & EPF)	
XV	FORM-A along with Copies of Work Order/Completion Certificate of the Works Completed in last 5 years to satisfy eligibility criteria mentioned in the Notice	
XVI	FORM-B along with Copies of Work Order under Execution issued by PSBs/ PSUs / Central Govt. Departments / State Govt. Departments	
XVII	FORM-C	
XVIII	FORM-D	
XIX	FORM-E	
XX	FORM-F	
XXI		

NOTE: IN ABSENCE OF ANY OF THE ABOVE ENCLOSURES, YOUR APPLICATION IS LIKELY TO BE REJECTED.

Place:

		NAME&DESIGNATION
Date	:	
		SEALOFORGANISATION

SIGNATURE



GENERALTERMSANDCONDITIONS

1 Definition of terms/interpretation:

- Employer/Owner/Bank /Indian Bank/ Accepting Authority shall mean Indian Bank with their Corporate Office at No. 254-260, Avvai Shanmugam Salai, Royapettah, Chennai 600 014 inter-alia having their Zonal Office at 2ND Floor, New Building, Hazratganj, Lucknow -226001and any of its employees representative authorized on their behalf.
- Throughout these bidding documents, the terms "bid" and "tender" and their derivatives ("bidder"/"tenderer"), "biddered /tendered", "bidding"/"tendering", etc. are Synonymous.
- Day means calendar day. Singular also means plural
- "Contractor" means the person whose Tender has been accepted by the Employer and the legal successors in title to such person, but not (except with the consent of the Employer) any assignee of such person.
- Tenderer: The term 'Tenderer's hall mean the individual or firm or company whether incorporated or not, undertaking the work and shall include legal representative(s) of such individuals or persons composing such firm or company or successors of such firm or company as the case may be and permitted assigns of such individual or firm or company.

2 Submission of Tender

The Tender must be submitted in Original or as per details given here under. The rates shall be filled in the schedule given in Part – II of the Tender Document

Tender should be submitted in two parts in separately sealed envelopes as described below:

- PART-I:TECHNICALBID
- PART II:FINANCIALBID

The Technical bid is to be submitted in sealed cover along with, Necessary documents prescribed in the Bids, Forms and EMD. The Financial bid shall be submitted in a separate sealed cover. The Technical and Financial bids are to be put in a master envelope (3rd Cover) and sealed and super-scribed 'Tender for Interior Furnishing Works in Existing Premises of Indian Bank – **K S Saket Branch, District – Ayodhya**' and addressed to the Zonal Manager, Indian Bank, Zonal Office Lucknow, Premises Department, 2ND Floor, New Building, Hazratganj, Lucknow -226001

- 3 TheIndianBankdoesnotbinditselftoacceptthelowesttenderandreserves to itself the right of accepting the whole or any part of the tender and the firm shall be bound to perform the same at the rate mentioned .
- a. The rate quoted by the firm shall be net (excluding GST), up to the stage of incorporation and handing over site. All taxes including (excluding GST) or any other tax on material or on finished works like Turn-over Tax, including taxes that may be newly introduced subsequent to the tender etc. in respect of this work shall be payable by the Firm and Indian Bank will not entertain any claim whatsoever in this respect.

The rate quoted should be excluding GST.

The firm who wishes to bid for the above job should have GST registration and should mention the registration number.

4 Earnest money amounting to **Rs.10,000/- (Rupees Ten thousand only)** in the form of Demand Draft drawn in favour of "**Indian Bank**", **payable at Hazratganj** must accompany each bid. EMD amount will not carry interest. Tender without earnest money will be summarily rejected.

Please note that firms registered with MSME / NSIC under single point registration with valid certificates issued by GOI are exempted from submitting EMD. Necessary Certificates must accompany bid. No other



type of certificate is acceptable. The exemption and relaxation in EMD is subject to the validity & acceptance of their registration certificate on the date of opening of tender.

- 4 The Firm shall give a list of his relatives working with the Indian Bank along with their designations and addresses.
- No employee of the Indian Bank is allowed to work as a contractor for a period of two years of his retirement from Indian Bank service, without the previous permission of the Indian Bank. The contract is liable to be cancelled if either the contractor or any of his employees is found at any time to be such a person who had not obtained the permission of the Indian Bank as aforesaid before submission of the bid or engagement in the service.
- 6 The tender for mentioned works shall remain open for acceptance for a period of 90 days from the date of opening of Tender.
- 7 It will be obligatory on the part of the bidder to sign all the pages of tender documents.
- 8 The bidder must pay the amount of Earnest Money as mentioned in the NIT by Bank Demand Draft payable to Indian Bank. No interest on Earnest Money deposited by the bidder shall be allowed. The bidder should attach the Bank Draft along with the technical bid failing which the bid will not be considered. No other mode of payment shall be accepted.
- 9 The Earnest Money Deposit of unsuccessful bidder shall be refunded within two weeks of award of contract to the successful bidder or within one week of actual commencement of work whichever is earlier and in any case not later than four months.
- 10 The Earnest Money Deposit of the successful bidder shall be refunded on the acceptance by the Employer of the Contractor's Demand Draft towards Intital Security Deposit.
- 11 The EMD of the bidder, whose bid is accepted, shall be forfeit in full in case he does not start the work by stipulated date mentioned in the award letter.
- 12 The retention amount at 8%on the value of the bill paid will be held by the Indian Bank apart from ISD. ISD Amount (2%) will be refunded to Contractor within 14 days from the issue of Work Completion Certificate by the Architect and the Retention Money (8%) will be released at the end of Defect Liability Period (12 Months), subject to satisfactory rectification of defects noticed, if any. ISD and Retention Amount held in our Bank's Book will not carry any interest.
- 13 The acceptance of tender will rest with the Indian Bank and the Indian Bank reserves to itself the authority to reject any or all of the bids received without the assignment of a reason. Bids in which any of the prescribed conditions are not fulfilled(or) are incomplete in any respect are liable to be rejected. The Indian Bank reserves the right to accept the tender in full or in part and the bidder shall have no claim for revision of rates or other conditions if his quote is accepted in parts.
- 14 Canvassing in connection with tender is strictly prohibited and the bids submitted by the bidders who resort to canvassing will be liable to rejection.
- 15 All rates shall be quoted on the proper form of the Tender alone. All the entries to be made legibly in ink only. Rates written in pencil or any other mode shall not be considered for evaluation and will be rejected.
- 16 Anitemratequotecontainingpercentagebelow/abovewillbesummarilyrejected.However,wherea bidder voluntarily offers a rebate for payment along with sealed tender, the same may be considered.

17 ABNORMALRATES

The Contractor is expected to quote after careful analysis of costs based on the specifications mentioned in the Tender. If it is noticed that the rates quoted by the Tenderer is unusually high or unusually low, it will be sufficient cause for rejection of the Tenderer unless the Employer is convinced about the reasonableness of the rate on scrutiny of the analysis for such rate to be furnished by the Tenderer on demand. Notwithstanding anything there in stand, the rate once accepted by the Employer shall be final and shall not be subject to any claim either on account of un-workability of rates or on any other ground whatsoever.



- 18 On acceptance of the bid the name of the accredited representative(s) of the Bidder who would be responsible for taking instructions from the Indian Bank shall be communicated to the Indian Bank.
- 19 Special care should be taken to write the rates in figures as well as in words and the amounts in figures only, in such a way that interpolation is not possible. The total amount should be written both in words and in figures.
- 20 The Contractor shall within 7 days of receiving the WORK ORDER submit <u>INITIAL</u> <u>SECURITYDEPOSIT</u> of <u>2% of the contract value in the form of a Demand Draft</u>. On acceptance of the Demand Draft, the Earnest Money Deposit shall be refunded to the Contractor.
- 21 The Contractor shall comply with and give all notices required under any law, rules, regulations, or bye-law of Parliament, State Legislature or Local Authority relating to works. If needed, the Contractor has to obtain required permission/ approval from the building secretary/ association. The Contractor shall before commencing the execution of work issue a certificate to the Employer that he has obtained all the permissions Registrations and give all the notices as are required to be obtained or given under law particularly blasting permission, Police permission etc.
- 22 The Contractor shall be required to maintain the site and the building areas in a neat and clean condition at all times to the satisfaction of the Employer. The Contractor shall especially take care to keep areas free from getting water logged, from concrete/mortar dippings, bricks, steel, shuttering materials or any other material / rubbish.
- 23 Debris and items removed from the building have to be neatly stacked at site and then periodically removed (maximum of one week), carried away by the Contractor and disposed off as per the rules and regulations of the Local Authorities concerned. No debris shall be thrown loose from upper floors. No floor, roof or other part of the building shall be over-loaded with debris or materials as to render it unsafe.
- 24 Employer reserves the right to insist on selection of material, workmanship, detailing and finishes, which they consider, is appropriate, and suitable for the intended use. The contractor is not eligible to claim extra on this account.
- 25 Employer will require the contractor to produce, samples of all the materials, accessories/ finishes prior to procurement/ manufacture. The samples of the materials for the work shall be got approved from the Employer. Failure to comply with these instructions can result in rejection of the work/ materials.
- 26 For painting & Lamination, sample area shall be prepared and the shade got approved. It is also advised to give computer presentation of various colour schemes to the employer before going for sample painting/Lamination.
- 27 The bidder should note that he should execute his part of work without causing any damage to any component of the building and also without disturbing the occupants. Any damage so caused shall be made good at the cost & risk of the firm.
- The successful bidders shall include, in the quoted price, all allied civil works such as chasing in wall, drilling holes etc to support the frames, partitions, make the surface good after grouting, scaffolding required if any to load/unload the materials etc.
- The successful contractor shall also be responsible for the safety and security of all their materials and also for ensuring fire prevention steps at all times in the working premises including their part of the work. The successful contractor has to place full time representative at site, the representative should have thorough subject knowledge. Bank will not be responsible for any untoward accident caused by negligence of the Contractor
- 30 The work shall be carried out without disturbing the existing occupants of other offices. Necessary barricading of the area, if required from the rest of the area shall have to be arranged by the successful contractor at no extra cost. The work is to be organized and executed so as to have least disturbance to the occupants of other offices.



- 31 The contractor should ensure payment of minimum wages + VDA to all labourers / workmen staff employed by him in line with central/ state labour wage act whichever higher.
 - The Contractor shall at all times indemnify and keep indemnified the Employer against all losses, claims, damages or compensation including under the provisions of the payment of the Wages Act 1936, Minimum Wages Act 1948, Employer's Liability Act 1938, Workman's Compensation Act 1923, the Maternity Benefit Act 1961, the Bombay Shops and Establishments Act 1947, Industrial Disputes Act 1947, and Contract Labour (Regulation and Abolition) Act 1970 and Employees State Insurance Act 1948, Motor Vehicles Act 1988 or any modifications thereof or under any other law relating thereto and rules made there under from time to time or as a consequence of any accident or injury to any workman or other person in or about the work whether in the employment of the Employer or Contractor or not, and also against all costs, charges and expenses of any suit, action or proceedings whatsoever out of such accident or injury or combination of any such claims.
- From commencement to completion of works, the Contractor shall take full responsibility for the care of the work and for taking precautions to prevent loss or damage to the work to the maximum extent possible and shall be liable for any damage or loss that may arise to the works or any part thereof from any cause whatsoever including causes of fire, lightning, explosion, earthquake, storm, hurricane, floods, inundation, subsidence, landslides, rock slides, riots (excluding civil war, rebellion, revolution and insurrection) or any latent defect or damage and shall at his own cost repair and make good the same so that at all times the work shall be in good order and condition and in conformity in every respect with the requirements of the Contract.

For the purpose of this condition this expression "from commencement to completion of works" shall mean the period starting with the date of issue of Work Order or date of handing over of site whichever is later and ending with issue of Virtual Completion Certificate.

Without limiting the obligations and responsibilities under this condition, the Contractor shall insure and keep insured the works from commencement to completion, as aforesaid, for the full contract value including Price Variation Adjustment if any against the risk of loss or damage from any cause whatsoever including the causes enumerated in the foregoing paragraphs. In the event of there being a variation in the nature and extent of the works, the Contractor shall from time to time increase or decrease the value of the insurance correspondingly. All the premia for the insurance shall be borne and paid by the Contractor.

Before commencing the work, the Contractor shall without limiting his obligations and responsibilities under this condition, insure against any loss of life or injury to any personnel in the employment of Contractor / Sub-Contractor/nominated Sub- Contractor. For this purpose, an insurance shall be taken by the Contractor /Sub- Contractor. Such an insurance shall be taken to include both employees/workmen covered by the Workman's Compensation Act 1923, as well those employees/workmen not covered by the said Act. Separate insurance policies may be taken for employees/ workmen covered by Workman's Compensation Act 1923, and employees / workmen not covered by the said Act. All the premia shall be paid by the Contractor. Policy/Policies taken under this para for the personnel in employment with the Contractor / Sub-Contractor may be in their Employer's names of the Contractor / Sub-Contractor / nominated Sub-Contractors. In the event of any loss or injury to personnel in employment with the Contractor / Sub-Contractor / nominated Sub-Contractors, the Employer and Contractor shall recover directly from the Insurance Company and ensure that payment of the same is made to the affected parties including the Employer. The policy in original shall be deposited with the Employer.

The Contractor shall at all times indemnify and keep indemnified the Employer against all losses and claims for injuries or damage to any person or any property whatsoever which may arise out of or in consequence of the construction and maintenance of the work and against all claims, demands, proceedings, damages, costs, charges and expenses whatsoever in respect of or in relation thereto. The Contractorshalltakeallprecautionarymeasurestoensurethesafetyoftheworkmenemployedbyit. The



- contractor shall be fully responsible for the any injury or damage caused to the workmen deployed by him at site for carrying out the work and Bank has nothing to do with such happenings and in no way shall be held responsible for the same.
- 33 The contractor shall maintain all registers as required by the Regional Labour Commissioner and should furnish the same to the Bank or its representative as and when required.
- 34 If the work is not started within 7 days from the date of issue of work order then Employer may terminate the work order without assigning any reason. If during the execution of the work, the progress of work is not considered to be satisfactory and is not consistence to be in contingent with the period of the completion of the work then the Bank may terminate the work order by giving a 5 day notice to the contractor. In such case the contractor shall be liable to pay the employer any extra cost involved for the completion of the said work and will not obstruct any way in completing the work through other agency. After completion of entire work the contractor shall be paid for the actual work executed by him at the quoted rates after deducting any claims, damages.
- 35 The time allowed for completing the works is **20 days** to be reckoned from **4thday** from the date of Work Order / date of handing over site whichever is later. Bidder shall submit a programme (time schedule) for executing the entire project and shall furnish the details of their scheme indicating the proposed deployment of their machinery and resources.
- 36 If the Contractor fails to complete any or all the works by the date/s named in Clause 35 (Date of Completion) or within any extended time (permitted by Bank) then the Contractor shall pay or allow the Employer the sum to be worked out at 1.0% of contract value per week to be recovered as Liquidated Damages (and not by way of penalty) for the delay, beyond the said date or extended time, as the case may be, during which the works shall remain unfinished and such damages may be deducted from any moneys due or which may become due to the Contractor. The maximum amount of Liquidated damages shall be 10% of contract value. The contractor shall be bound to extend validity of Insurance Cover till such period of completion as may be considered necessary at their cost.
- 37 Extension of time: If in the opinion of the Employer/ Architects the works be delayed (a)by reason of any exceptionally inclement weather or (b) by reason of instructions from the employer in consequence of proceedings taken or threatened by or disputes, with adjoining or neighboring owners or (c) by the works, or delay of other contractors nominated by the employer and not referred to in the specification or (d) by the reason of authorized extra and additions or (e) by reason or any combination or works men or strikes or lock-out affecting any of the building trade or (f) from other causes which the employer may consider are beyond the control of the contractor, the employer at the completion of the time allowed for the contract shall make fair and reasonable extension of time for completion in respect therefore. In the event of the employer failing to give possession of the site upon the day specified above, the time of completion shall be extended suitably.
 - In case of such strikes or lockouts as are referred to above, the contractor shall, immediately give the employer, written notice thereof. Nevertheless he shall use his best endeavours to prevent delay, and shall do all that may be reasonably required, to the satisfaction of the employer for any extension of time for completion hereunder (which shall be final and binding on the contractor) shall be promulgated at the conclusion of such strike or lock-out and the employer shall then, in the event of an extension being, granted, determine, and declare the final completion date. The provision in clause 36 with respect to payments of liquidated damages shall be construed as if the extended date fixed by the employer was substituted for and the damages shall be deducted accordingly.
- 38 The successful bidder shall be required to execute an Agreement in the proforma attached with this tender document within 7 days from the date of receipt of the notice of acceptance of bid. In the event of failure on the part of the successful bidder to sign the agreement within the above stipulated period, the earnest money will be forfeited and the acceptance of the tender shall be considered as cancelled.



39 PAYMENTDETAILS-

- No advance payment shall be made to the contractor on supply of any material supplied at site for execution. Payment to the contractor shall be made as per actual work done of site.
- No Interim/Adhoc Payment is allowed.
- $\bullet \quad All bills shall be prepared by Contractor in the form prescribed by the Employer/Architects.$
- Bank will deduct the retention money as described in the Clause No 9 and the refund will be made as specified in the same clause.
- The final bill will be released on satisfactory completion of the entire work and on completion of all the terms and conditions / obligations spelt out and on proper submission of the bills together with the measurements properly checked by Architect & Bank's Engineer in presence of Contractor. Final Bill settlement is within 30 days from the date of proper submission of bill & measurements.
- 40 The bidders shall separately specify at the end of the bid the% and value of SGST and CGST as applicable. As on date 9 % CGST and 9% SGST IS APPLICABLE FOR WORKS CONTRACT. Regarding tax part, the tax rate at the time of billing shall rule over and above all documentations. Valid documents shall be produced if asked for at the time before payment. TDS for income tax is as applicable and shall be included in the quoted rates. The comparison for the least bidder shall be made with the basic price of items of work excluding "Goods and Service Tax" part.
- 41 At any stage i.e. during the execution of work, any kind of change required, whether it is in design or specification, the contractor must inform the concerned Department of the Bank or Architect and after getting the approval, the same has to be incorporated by the contractor.
- 42 Single Power point & Water for work will be provide by Bank. The Bank will recover from Contractor the charges for electricity and water if arranged by the Bank on actual basis. The Contractors will make their own arrangement for stay of their workers and they will not be permitted to stay in the Bank Premises.
- 43 The contractor shall not directly or indirectly sublet the work to other party without written permission of the bank.
- 44 The Bank reserves the right to distribute the work for which tenders have been called, among more than one parties, if found necessary. No claim in this respect shall be considered and the contractor agrees to cooperate with other agencies appointed by the Bank.
- 45 Bank shall not be responsible for any loss or damage to the contractor/ labour due to any natural calamity during the course of construction. Contractor is liable to make good all the damages if any, till the work is completed and handed over to the Bank authorities
- 46 Contractor agencies are advised (before quoting the rates) to inspect the site of the proposed work. They must go through specifications and documents. Any clarification, if required, may be taken from the Bank before submitting the tender.
- 47 The quantities mentioned in schedule are provisional and likely to increase /decrease to any extent or may be omitted thus altering the aggregate value of the contract. No claim for loss of profit/business shall be entertained on this account.



- 48 The contractor /vendor failed to carry out the works as per schedule/Quality, the same shall be carryout with different agencies and the actual amount will be deducted from the contractor bills.
- 49 The contractor agency shall keep particular vigil on his workers to maintain very good workmanship of all items, failing which no payment shall be made and no claim of material / labour used shall be made to him in any case, and the same work shall be executed by him again without charging any extra cost.
- 50 TheBankreservestherighttoaccept/rejectanytenderwithoutassigninganyreasons.
- 51 Any work got executed in poor workmanship as pointed out by the Bank' Official will have to be dismantled and redone by the Contractor on his own cost
- 52 Any addition, alteration or correction in the quote shall be signed and stamped properly by the contractor.

DECLARATION:

I/We here by declare that I/ We read and understood the above terms and conditions and that we shall a bide by them if the work is awarded to us.

Signature & Seal of the Firm



ARTICLES OF AGREEMENT

THIS AGREEMENT is made on the	sday ofmonth of b	oetween Indian	Bank and hav	ring its Zona	al	
Office at 2ND Floor, New Building	g, Hazratganj, Lucknow -2260	01 (hereinafter	referred to a	s the "Emp	loyer")	which
expression shall include its succes	sor, legal heirs and assignees (of the one part.				
AND M/s	having its office at					
		(hereinafter	referred	to as	the
"Contractor") which expression sh	nall include its successor, legal	heirs and assig	nees of the se	cond part.		
WHEREAS the Employer has car Furnishing Works & Electrical Wo	_	•				
AND where as the Employer has c	alled for Tender vide ref. no		d	ated		
AND where as the contractor has	submitted the Tender ref. no		d	ated		to
The Employer on						
AN D where as the Employer has is	ssued the work order ref		dat	ted		to
The contractor to do the work.						
AND whereas the Contractor has	agreed to execute the work a	ıs per drawings	s, specification	ns, conditio	ns of co	ntract
and Work Order.						
AND whereas the Employer has	accepted the Contractor's bid	l as aforesaid a	and whereas	the bid sub	mitted 1	by the
contractor has been accepted for	such sum as may be ascertain	ed to be payabl	le in terms of	the Bill of 0	Quantiti	es and
which sum is estimated to be Rs	(Rupees)
Hereinafter referred to as the said	"Contract Agreement".					

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:-

- 1) In consideration of the said Contract Sum to be paid at the times and in the manner set forth in the said Conditions the Contractor shall carry out and complete the Works in terms and conditions herein contained and according to the general conditions of the contract, notice inviting tender, special conditions of contract, general scope of work, technical specifications, schedule of rates and instructions to be given by and the supervision of and to the entire satisfaction of the Employer.
- 2) Contract Price, Taxes and Payment Terms:

Total contract price is Rs. + GST which is inclusive of cost of materials, equipment, installation charges, dismantling work (if any) and tools and tackles required for execution of the job. Above price is inclusive of all taxes & duties except GST in respect of this contract. No claim in this respect will be entertained. Income tax on payments will be deducted and deposited by Employer in accordance with the sales tax law of the state and the provisions of tax deductions at source under income tax act 1961.

3) **Completion Period**:

Time is the essence of the Contract. The work is to be completed in all respects within **20 days** reckoned from 4th **day** from the date of issue of the Work Order or handing over of site which ever is later. If the



Contractor fails to complete the job within the agreed time period the Contractor will have to bear liquidated damages as per the relevant clause mentioned in the Tender Documents.

4) Earnest Money:

The Contractor has deposited an amount of **Rs.10,000/-(Rupees Ten thousand only)** as earnest money.

5) **Inspection of Site**:

The Contractor has inspected the site before submitting his bid and has satisfied himself as to the nature of the work to be executed on the site. Any difficulties which the Contractor may come across in the course of the work shall in no way relieve the contractor to claim or receive extra payment unless the Employer is of the opinion that such difficulties could not have been foreseen and the Employer consents in writing.

6) Supply of Material and Labour:

The Contractor shall arrange all labour, materials, equipments, tools, tackles and everything necessary fort he completion of the work. The Contractor will assume all responsibility for the safety, protection and accounting of all material and equipment and the work during construction. All materials used by the Contractor shall be of the best quality conforming to the required specification mentioned in the bid document and will be subject to the approval of the Employer. All such materials not approved by the Employer shall be removed at once by the Contractor at his own expense. The Contractor shall also at his own expense arrange for carrying out any test of materials which the Employer may from time to time require or if so desired by the employer.

7) **Defective Work/Materials**:

If any part of the work done by the Contractor is found defective in workmanship or if bad or inferior materials have been used the Contractor shall at his own risk and cost demolish all such defective work and rebuild the same and / or replace the bad or inferior materials used within a time frame mentioned to the satisfaction of the Employer. The decision of the Employer in this regard shall be final and binding on the Contractor. In case of default of the contractor to remove the defective work and rebuild the same or replace bad or inferior materials as directed by the Employer, the Employer shall been titled to employ anyone else to carry out the same at risk and cost of the Contractor and recover all expenses incurred in this regard from the contractor.

8) Inspection of Work:

During progress of the work the Employer shall be entitled at all times to have access to and inspect the work.

9) **Supervision**:

The Contractor shall provide one or more competent and technical qualified engineers duly and fully authorized to act on his behalf in all matters relating to the works to be carried out under or any other matter concerning this agreement and who shall at all times be present at the works while any work is in progress as per directions, explanations & instructions of Employer.

10) Compliance with Statutory Regulations & Work Rules:

The Contractor shall be responsible for complying with the applicable laws / bye laws / Regulations in force from time to time and shall have to bear all statuary liabilities to the workers/ personnel engaged for the job. Nothing will be paid extra in this regard. If any amount is paid by the Employer with this regard the same



amount shall be deducted from the Contractor's dues. The Contractor shall have to arrange insurance cover for the workers / personnel engaged by him for the job.

11) **Determination of Contract**:

In the event of Contractor failing to keep / adhere to agreed schedule of work, or in the event of the Contractor failing to comply with the provisions of this contract by default and / or negligence and / or suspension of work or in the event of Contractor failing to complete the work within the stipulated period, the Employer may terminate this Agreement forthwith and employ, at the Contractor's risk and cost, another contractor or sufficient number of workmen to complete the work.

12) Force Majeure:

This clause will be operative only if the work is delayed by

- a. Acts of God
- b. Earth quake or floods or similar natural calamities.
- c. Serious loss or damage by fire or lightning.

In case any Force Majeure condition herein mentioned occurs and continues for a period exceeding 15 days the parties hereto undertake to sit together and devise ways for expeditious and proper performance of the obligations of the parties under this order.

13) Arbitration:

"In the event of any dispute or difference relating to interpretation and application of provisions of the contract and all disputes/ claims whatsoever which shall either during the continuance of the contract or afterwards either between the parties to the contract or the respective representatives touching the construction/ application of any provision/ clause mentioned in the contract or any account or liability between the parties to the contract or as to any act or deed or omission of any party to the contract, in any way relating to these presents, shall be first at the discretion of the Bank attempted to be resolved in good faith by mutual discussion within 30 days of the dispute or question being raised failing which the same shall be settled by arbitration in accordance with provisions of Indian arbitration and Conciliation act 1996.

The Parties concerned shall designate an arbitrator on mutual consent/ consensus. The venue of the arbitration shall be exclusively at Lucknow and any award passed by arbitrator shall be final, conclusive and binding upon the parties and shall be deemed to have been made between parties themselves. The parties to the dispute shall share equally the cost of arbitration as intimated by the arbitrator".

INWITNESS where of the said contracting parties have set their hands and seals on the day and year first herein above witness.
Witness Address
Employer

Witness Address Contractor

PROJECT - ESTIMATE FOR FURNISHING WORKS.

BANK - INDIAN BANK

BRANCH - K.S. SAKET NAGAR

*ALL ITEM TO EXCLUSIVE OF TAXES . Taxes to Mentioned By the Contractor.
*ALL WORKS TO BE DONE AS PER TENDER CONDITIONS.

S.NO.	DESCRIPTION OF ITEM	UNIT	QUANTITY	RATE (Rs.)	AMOUNT (Rs.)
1.0	SUSPENDED FALSE CEILING				
1.1	GYPSUM FALSE CEILING WITH COVE				
1.0	Providing, fabricating and erecting in position totally flushed suspended false ceiling with 12.0mm thick Gypsum board, fixed to a metal frame work comprising of ceiling channel of size 80mmx26mmx0.5mm @ every 457cm centre, inter channel 45mmx15mmx0.9mm @ every 1220 cm centres, peri-meter channel 20mmx26 mm all along the wall/partitions, strap hanger suspenders 25mmx0.5mm with nuts and bolts 6.4mmx12.7mm, connecting clips 2.6mm thick, dry walls screws 25m long, soffit cleats 27mmx37mmx25mmx1.6mm thick and dash fastenes / rawl plugs 12.5 mm diax35mm long with 6mm dia bolts etc. complete with recommended fillers, paper tapes and applying two coats of acrylic emulsion paint of approved shade and make over a coat of primer including making necessary cut outs for light fittings/ ACs etc. complete as per manufacture's specifications. (Quantity as per layout plan/site requirement)	Sqft	325.00		
1.2	FALSE CEILING (ARMSTRONG CEILINGS - FINE FISSURED MICROLOOK EDGE WITH SILHOUETTE GRID (BLACK REVEAL))				
	Providing and fixing false ceiling system manufactured by M/s. Armstrong World Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm, having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID(BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99%, having Fire Performance CLASS O / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of protective paint.	Sqft	375.00		
1.3	Designer MDF board false ceiling/Pillars 12mm thick with CNC Cutting and backing of Acryllic /Metalim,Eqivalent as per direction of the architect.The support system to be as above.	Sqft			
2.0	WALL PANELLING & COLUMN ENCASING WITH DIFFERENT LEVEL INSTRUCTION AS PER ARCHITECT				
	Supplying and erecting Wall paneling / Column encasing (up to false ceiling) as per drawing and design and conforming to the following specifications: Basic frame work: Framing shall consist of Heavy duty Aluminum Box Sections 50mm x 50mm x 2 mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Skin membrane: 9 mm thick BWP grade plywood on face. Finishing: 1.0mm thick laminate sheet of same or combination shades with grooves as per instructions. Skirting: 100mm high laminate of approved make & shade all as directed. Top Border: 150mm high laminate of approved make & shade all as directed. Note: Quoted rates shall include all necessary materials, accessories and labour and also for making provisions for electrical/telephone/computer wiring, conduits and switch boxes, etc. where ever required. (quantity/location should be restricted only to the central pillars in Banking hall/to hide electrical pipes/AC drain pipes/any prime location)	Sqft	275.00		
2.0	DADWINANG				
3.0	CASH CABIN PARTITIONS: Supplying & Erecting full height solid cash cabin partitions (upto false ceiling as per following specifications: Basic frame work: Framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm x 2 mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Skin membrane: To be finished with 12 mm thick BWP grade plywood on each face with grooves, as per drawings/ instructions. Finishing: 1.0mm thick laminate of same or combination shades with grooves in both faces as per instructions. Skirting- 100mm high laminate of approved make & shade all as directed. Top Border: 150mm high laminate of approved make & shade all as directed. It shall have decorative aluminum grill (from 1200mm to 2100mm) fixed with teak wood beading (size – 30mm x 20mm, as per profile) with melamine finish. The job shall also include for provision of laying conduits, switch boxes etc. The erection of partition shall include for expansion bolts cleats, clamps bolts, nuts, screws, rivets and other accessories, all complete up to the satisfaction of the Architect. All door opening shall have rebated teak wood framework (size – 75mm x 50mm, as per profile) on vertical (2 Nos.) and horizontal (1 No.) sides, with melamine finish and rebate of 40mm x 12mm, all complete up to the satisfaction of the Architect. Quoted rates shall include all necessary materials, accessories and labour and also to make provisions for electrical / telephone / computer wiring conduits and switch boxes, etc. (Materials for wiring, conduits, switches etc. shall be separately paid for)	Sqft	135.00		

	Supplying and execting full height northy glored / unglored nortitions as nor full-mine	Caft.	205.00	
3.2	Supplying and erecting full height partly glazed / unglazed partitions as per following specifications: Basic frame work: Framing shall consist of Heavy duty Aluminum Box Sections 50mm x 50mm x 2mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Exposed frame members in the glazed portions shall have wider spacing (approx. 1200 mm) and be finished with 1.00 mm thick laminate of same or combination shades, over 6mm BWP grade ply. Skin membrane: (Opaque portion up to 900mm from floor level and from 2100mm to ceiling, finished with 12 mm thick BWP grade plywood on each face with grooves, as per drawings/instructions. Glazing: 12mm thick laminate of same or combination shades with grooves as per instructions. Glazing: 12mm thick clear float glass fixed with polished teak / steam beech wood glazing beads of approved shape (finished 12 x 25mm). Skirting- 100mm high laminate of approved make & shade all as directed. Top Border: 150mm high laminate of approved make & shade all as directed. Quoted rates shall include all necessary materials, accessories and labour and also to make provisions for electrical / telephone / computer wiring conduits and switch boxes, etc. (Materials for wiring, conduits & switches etc. shall be separately paid for)	Sqft	285.00	
	Supply and erecting low height opaque partitions (up to maximum 1200mm height) conforming to the following specifications: Basic frame work: Framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Skin membrane: 12 mm thick BWP grade ply on each face up to 900mm height. Glazing: 12mm glass in remaining portion, Finishing: 1.0-mm thick laminate of same or combination shades with grooves as per instructions. Edge moulds: All free top/ end surfaces shall have polished teak / steam beech wood moulds of approved shape (from 18 x 50mm sections). Skirting- 100mm high laminate of approved make & shade all as directed. Quoted rates shall include all necessary materials, accessories and labour and also allow provisions for electrical / telephone/computer wiring, conduits and switch boxes, etc. (Materials for wiring, conduits and switch boxes, etc. (Materials for wiring, conduits and switch boxes shall be separately paid for.)	Sqft	90.00	
3.4	Supply and Erecting Bison Panel Board Partition & Door for UPS area. The framework shall consist of Aluminium Box Section as per the specifications mentioned above. The framework shall be than covered with 8mm thick Bison Panel on both the sides and also in the external periphery of the framework. A glass panel of 9" x 2'6" shall be provided at eye level on the door with necessary framework, sections, beadings, etc. All external surfaces of the Bison Panel shall be covered in 1 mm thick laminate of approved shade. The door shutter will have required hardwares such as heavy duty Fire Resistant door closer, locks, hinges, etc. All in SS Brush Finish.	Sqft		
4.0	COUNTER & WORK STATIONS			
4.1	Providing and erecting in position Cash Work Station of approx. size 1370x900x750mm (4.5'x3.0'x2.5'), made of 19mm thick block board pasted with 1.00mm laminate inclusive of a 350mm wide customer top at 1155 mm level, Writing top & customer top should be finished with mirror polished; 18mm thick granite slab Uet black or shade as directed by Bank's	Rft	4.50	
	Engineer) with rounded edges and sides with 1.0mm thick laminate of approved shade/make. Both should have sufficient gap in between to accommodate computer monitor up to full depth. The workstations shall be supported from the partition system made of 19mm thick BWP grade block board finished with 1.00 mm thick laminate of approved shade/make. Free edges shall have 18 mm thick, polished white or steam beach wood moldings of half-round profile as per drawings and instructions and 100mm high laminate of approved make & shade all as directed. Each cash workstation shall comprise of the drawer unit, Tea tray at top, Cash drawers with approved telescopic channels for drawer-slides, automatic locks (keys in duplicate), wire managers, space for computer CPU, modesty panel and other necessary hardware and accessories including satin finish S. S. handles of approved quality. Inner face of cash counter to be provided with 16G, M.S. sheet, painted with two coats of synthetic enamel paint of approved shade & make, over a coat of approved steel primer. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Skirting: 100mm high laminate of approved make & shade all as directed.			
4.2	Engineer) with rounded edges and sides with 1.0mm thick laminate of approved shade/make. Both should have sufficient gap in between to accommodate computer monitor up to full depth. The workstations shall be supported from the partition system made of 19mm thick BWP grade block board finished with 1.00 mm thick laminate of approved shade/make. Free edges shall have 18 mm thick, polished white or steam beach wood moldings of half-round profile as per drawings and instructions and 100mm high laminate of approved make & shade all as directed. Each cash workstation shall comprise of the drawer unit, Tea tray at top, Cash drawers with approved telescopic channels for drawer-slides, automatic locks (keys in duplicate), wire managers, space for computer CPU, modesty panel and other necessary hardware and accessories including satin finish S. S. handles of approved quality. Inner face of cash counter to be provided with 16G, M.S. sheet, painted with two coats of synthetic enamel paint of approved shade & make, over a coat of approved steel primer. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Skirting: 100mm	Sqft	45.00	

4.4	OFFICER COUNTERS / LOW LEVEL COUNTER Supplying and erecting counters (running tables) 915 mm wide and 750mm high including drawer-cum- cabinet unit for files, space for computer CPU, wire managers, modesty panel, tea tray etc. made with 19mm thick BWP grade block board on top and supporting sides / front with necessary well seasoned Malaysian Sal/ Kail/ Mirandi wood frame work. Writing top & customer top should be finished with mirror polished; 18mm thick granite slab (Jet black or shade as directed by Bank's Engineer) with rounded bevelled edges and sides with 1.0mm thick	Rft	11.00	
	laminate of approved shade, make finished on sides with 1.0 mm thick laminate of approved shade and quality, including providing and fixing 450mm long key board tray of approved shade, hardware and accessories at each of the counter. All exposed edges of block board are to be provided with half round teak wood mouldings, duly polished and 100mm high laminate of approved make & shade all as directed. Customer Top will be raised by 6 inches to provide a box type formation in the front elevation. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Skirting: 100mm high laminate of approved make & shade all as directed. Rate to include charges for brass hardware fittings as well as fixtures like sliding gear for drawers of Earl Behari' or equivalent approved make. (ELEVATION DESIGN OF COUNTER WILL BE PROVIDED BY ARCHITECT AS PER SITE CONDITION)			
5.0	DOORS:			
5.1	Supplying and fixing in position overall 32 mm thick solid core hot pressed phenol formaldehyde bonded flush door finished with 1.0 mm thick laminate of approved shade and quality on both sides of the door shutter & beading on edges including cost of hardware fittings e.g. Godrej night latch / mortise lock, hinges, door closure, handles etc. of approved make and quality. (CASH CABIN). Please note that the price must include providing and fixing aluminum grill with square size 75mm x 75 mm in the door as per Bank's instructions with grill tightly stretched and nailed to wooden framework along with steam beach wood beads of approved design complete for Cash Cabin Door as per Bank's instructions	Sqft	42	
5.2	Supplying and fixing in position 32 mm thick solid core hot pressed phenol formaldehyde bonded partly glazed flush door shutter of approved make finished up to 900 mm from floor level with 1.00 mm thick laminate of approved quality on both sides of the door shutter & beading on edges. The upper portion of the shutter is to be provided with 12 mm thick clear float glass fixed with white or steam beech wood glazing beads of approved design, complete as per drawing. Rate to include cost of hardware fittings e.g. mortise lock, hinges, handles, door closer etc. of approved make and quality. (BM CABIN DOOR / PASSAGE DOOR / STR ROOM PASSAGE DOOR)	Sqft	42.00	
5.3	FLAP DOOR Providing and fixing Flap Door of min. size: 3' (B) X 2'6" (H) made of block board with approved lamination on both side, of required size with hinges/tower bolts/stopper/handles etc complete.	Sqft	12.00	
5.4	ENTRANCE DOOR - TOUGHENED GLASS DOOR WITH FIXED GLASS PARTITION & ETCHING WORK (2 UNITS) (DOUBLE DOOR IN EACH UNIT) Providing fabricating & fixing in position twin –style door at Main Entrance made of 12mm thick clear toughened glass (MODI / ST. GOBAIN) in single piece with computerized diamond cut and edge polish pencil edges all around including making required cut holes for lock, handles, pivot patch fitting, corner fitting, injness, etc. Glass should be fixed in S.S finished D-Brackets, etc. Wherever required with metal patch fittings at Top / Bottom / Corner / profile section for fixed glass as approved by Bank Authorities for Door Shutter. For Glass Partition wherever required if any, the glass panels can be bolted together with stainless steel stub post which are into concrete through core drill holes or supported by stainless steel clamp fixing to vertical posts on each side as per requirement at the site with necessary bevelling etc. complete fixed on floor spring of Ozone / Dorma / Godrej Make (ISI Mark & Heavy Duty). The Door Shutters shall have C - shaped Stainless Steel Handle (18" or 24" as directed) on both the door and both the sides of approved make with erection, finishing, etc complete. The fixed glass partition are to be fixed by providing profile section @ Top & Bottom . The entire glass partition is to be finished with one way film, bank logo or as per Bank's Requirement.	Sqft	65.00	
6.0	OTHER ITEMS			
6.1	LOW / FULL HEIGHT STORAGE CABINET P/F in position 450mm deep storage full ht./low ht.cabinets having sides partitions, shelves & shutters, fabricated out of 19mm BWR & 6mm th.BWR Plywood back, with all exposed surfaces & inside of shutters/internal base of drawers to be finished with 1mm thick laminate i/c 31x31mm rounded steem beech wood moulding & 6x19mm steem beech wood edging on edges of comm.board as/arch.drg.complete with shelves, shutter, drawers etc.i/c P/F	Sq.Ft.	145.00	
	necessary hardware telescopic channels for drawers of Hettich,S.S.piano hinges as/appvd.sample,Hettich handles(as/appvd.sample)in all drawers & shutters,locking arrangement,75mm brass tower bolts,Hettich locks in all shutters & drawers,magnet catcher,painting the exposed internal surfaces of block board with 2-3 coats of synthetic enamel paint with melamine finish on wood surface with 6mm comm.ply at rear as per arch.drg.& as per site requirements the rate should include 19mm th.pre-polished Granite Stone (Asian Quartz) as per appoved sample with half round bevelled edge complete on low ht.storage cabinets.			
6.2	necessary hardware telescopic channels for drawers of Hettich,S.S.piano hinges as/appvd.sample,Hettich handles(as/appvd.sample)in all drawers & shutters,locking arrangement,75mm brass tower bolts,Hettich locks in all shutters & drawers,magnet catcher,painting the exposed internal surfaces of block board with 2-3 coats of synthetic enamel paint with melamine finish on wood surface with 6mm comm.ply at rear as per arch.drg.& as per site requirements the rate should include 19mm th.pre-polished Granite Stone (Asian Quartz) as per appoved sample with half round bevelled edge		00.00	
6.2	necessary hardware telescopic channels for drawers of Hettich,S.S.piano hinges as/appvd.sample,Hettich handles(as/appvd.sample)in all drawers & shutters,locking arrangement,75mm brass tower bolts,Hettich locks in all shutters & drawers,magnet catcher,painting the exposed internal surfaces of block board with 2-3 coats of synthetic enamel paint with melamine finish on wood surface with 6mm comm.ply at rear as per arch.drg. & as per site requirements the rate should include 19mm th.pre-polished Granite Stone (Asian Quartz) as per appoved sample with half round bevelled edge complete on low ht.storage cabinets.	Sq.Ft	30.00	

	Sq.Ft	115.00	
Providing and fixing in required position 4mm thick exterior grade Aluminium Composite Panel in Ceiling and Vertical Cladding or as per requirement and directed by Bank's Engineer or Architect over a framework made out of 50 x 50 x 2 mm aluminium SHS anchored to existing M.S Structure including installing the composite panel in grid pattern of 2' x 2' or of required size as directed with the help of aluminium cleats / angles of size 1" x 1" and striking out joints with weather silicon. The rate shall include cutting of panels, its bending, cutting for providing down lighters, providing opening for operation of rolling shutters, labour, scaffolding, etc complete			

John Markholder Faller Wilth StDC CREDENS. HELIODE Tables THECK GLASS. Proceedings and pointed such with the proof based with to me thick based in played and provided the process of the proof based with the proof based	7.0	DIVATIDES			
Popularies and pelaceria pio presistos tables with 100, vertical sides (Acidence, shicking, and moderny paper and and the 10 mars fall was not per families of 10 mars fall was not perfectly and the perfectly and the second of 10 mars fall was not perfectly and the perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars fall was not perfectly and the perfectly and the second of 10 mars fall was not perfectly and the second of 10 mars	7.0	FIXTURES DRANCH MANAGER TARLE WITH SIDE CREDENZA INCLUDE 12 THICK CLASS.	NI.	1.00	
paced made out of Toman takes water proof board with 1 man takes havings just Judice approach victors that pain of necessar shore, your what shale be presented with a size will be provided with a first will be provided with 1 man takes and the man of the provided with a first will be provided with a provided wi	7.1		No.	1.00	
below the top out of for footest below. Rovey table shall be provided with a side unit give. We you colourn in 170 colourn. It should be not be a side of the side					
SOOM, 16-750mm, Po-550mm segrouss), consisting of 150 mm deep deserve at top and a calificate with spen shift particle abstance being the follow shall be used out 100 mm thick waster pourd board with Imm thick homistote lost shake approved by the Architect and sides and boatman of these shall be the mode and 170 mm thick waster pourd in the provided with a productal unit (size — 8-50mm, 17-20mm, 17-20mm, 12-20mm,		by the Architect) on all exposed surfaces. It shall also have 75mm x 40mm teak wood runners			
with spen oble/Jamesed subturbs below abail be made out 19mm thick water proof of drower and stuture and chainer and chainer below shall be made out of 12mm thick water proof of drower shall be made out of 12mm thick water proof ply. The side until shall have CAM books, abandles, patient, chainers, an apparent catheries, are disposed made theory table shall water them the patients of the patient					
The finds of finesce and dupture of colored below shall be made out 19 februs thick seater proof loosed with intenticed maintains the architect and sinker and broom of bood with intenticed maintains and received and the architect and sinkers and broom of handles, guides, shalling usuits, hinges, magnetic catcher's etc. of agreecest make. Every table shall be provided with a prefession usuit may be a Volume in 27 form. In 18 februs 1					
tower with the medic and of Janus Hels sware proof by the Architect and side and bottom of three with the medic and of Janus Hels sware proof by the adventured hels and the provided with a pedestal unit histor — W-50mm. H-720mm. H-720mm. approach before. The table shall know Collam deep facin, before the begin with the Proposed drawer was table to the shall have provided with a pedestal unit histor — W-50mm. H-720mm. H-720mm approach before. The hall have been controlled to the provided with a pedestal unit before the spot when the Proposed drawer unit shall be added and the provided with the surface of the facilities of the provided with four the shall be added and before the provided with four the shall be reliable and better and the shall be reliable and better than the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and ph dealth growthed with four the shall be reliable and the shall be reliable and ph dealth growthed with four the shall be reliable and the shall be reliable and ph dealth growthed with four the shall be reliable and					
deserve shall be mode out of 12mm thick woter proof ply. The side until shall have CAM locks, handles, paides, saiding units, hinges, mappered canders see, of depresed make therey stable shall be able have 100mm drop fields, below the top, in which keyboard drower until shall be all have 100mm drop fields, below the top, in which keyboard drower until shall be all shall have 100mm drop fields, below the top, in which keyboard drower until shall be all shall have 100mm drop fields, below the top and the shall have 100mm drop fields, below the shall have 100mm drop fields, and the shall have 100mm drop fields, and the shall have 100mm drop fields and shall be painted with some thick where poped found and ply shall be provided with some thick where 100mm drop fields and shall be reached to the shall be					
be provided with a peciestal unit (size - WSömm, In *Zömm, DSömm approxe) before. The table shall have PiOmm deep picks, book whe to pur, which belovourd drawer used and be provided with a person of the provided with form thick task word/hard wood lipping. All teaks wood trainforces shall be made out of Portion of the provided with form thick task word/hard wood lipping. All teaks wood trainforces shall be made out of the provided with form thick task word/hard wood lipping. All teaks wood trainforces shall be provided with form thick task word/hard wood lipping. All teaks wood trainforces shall be provided with form thick task word/hard wood lipping. All teaks wood trainforces shall be provided with form thick the provided with a pro		drawer shall be made out of 12mm thick water proof ply. The side unit shall have CAM locks,			
skels stall have 100mm deep facis, below the top, in which keyloroad drawed units stall had hemisted (as plade adjusted). It will be made out 10 mm thick water proof below which may be stall the ministed and plade water proof ply. The unit shall have CAM belox, handles, guides, stilling units etc. of approved mande. The job shall treads for form a form on grower in therewore node, and great add of travers and mande. The job shall treads for form a form on grower in the water and the stall have provided with from thick reads word plant water growing. At the act wood strates shall be readinest poslabed and other interest surfaces shall be painted with the coasts of synthetic canned over one coast of primer, all the painted with the coasts of synthetic canned over one coast of primer, all the painted with the coasts of synthetic canned over one coast of primer, all the painted with the coasts of synthetic canned over one coast of primer, all the painted with the coasts of the painted with the coasts of synthetic canned over one coast of primer, all the painted with the coasts of the painted with the painted with the coasts of the painted with the provided with a pockstal until ever. We discover and shared or cleans the skepword by the Architect and sides and bottom of drawer shall be made unto if 21mm thick water proof by Dr. Dr. Dr. Stall the painted with the coasts of the provided with a pockstal until ever. We discover the painted with the painted with the painted with the painted with painted with the painted wi					
adjusted. It shall be made out 19mm thick water proof board with 1 mm thick isminate jea/shade approved by the Architect and sides and bottom of shares whall be made out of 12mm thick management of the Architect and sides and bottom of shares makes and the provider and the prov					
approved by the Architect; and sides and bottom of drawer shall be made out of 12mm thick water prote by The unit shall have CAM locks, hundles, guides, sliding units et. of approved the provided with form the control of the contro					
winter proof ply. The unit shall have CAM locks, handles, spudies, shiding units etc. of approved mixed proof the control of t					
The job shall include for forma x forms growen in between sides and open able drawers and hunged shutters. All the exposed edge of water profit forms and apply shall be provided with from minimum and the provided with the content of propriets and the provided with from the content of propriets and the provided with the content of providing and placing in positions tables with two costs of synthetic cannot ever one cost of printer, all providing and placing in positions tables with two costs of synthetic cannot ever one cost of printer, all contents and the providing and placing in positions tables with two costs of synthetic cannot ever one cost of printer, all costs and placing in positions tables with two providings and placing in position tables with two, vertical aides/directs, skrining and modeley period the costs of the providing and placing in position tables with two provided by the Architect) of all capacid surfaces. It shall also have 75mm, a 40mm took wood routines with the made out 10 min the water proof by Dr. by real table all by periodic with a 100mm deep facia, before the top, in which keep before the content of drawer shall be adjusted. It shall be made out 10 min thick water proof beard with a 110mm thick water proof beard with a 110mm thick water proof beard with a 110mm thick water proof beard with min thick water proof beard with the minimum thick water proof by The Architect and sides and bottom of drawer shall be made out 10 minimum thick water proof beard with a 110mm thick water proof by The Architect and sides and bottom of drawer shall be made out 10 minimum thick water proof board with the provided with 12 mm thick for gas and the color of the Architect. Deep transport water proof board with the provided with 12 mm thick water proof board with 1 mm thick water pr					
hinged absuters. All the exposed edges of water proof board and phy shall be provided with 6 mm hick cleak would just wood lipping. All teak wood surfaces shall be meaked subting on some part of the provided of the provide					
thick teak wood/hard wood layeing. All teak wood surfaces shall be melannine polished and other internal surfaces shall be painted with wo cost of spruntice canadrour corn cost of printry, ell provided in the paint of position to the paint of the paint					
internal surfaces shall be painted with two costs of symbolic samuel over one cost of primer, all PAP 20 POYCHING and placing in position tables with top, vertical sides (Ariders, skirting and modesty pond transer out of 197m thick seets proof board with turn thick learnines bey/shode approved below the top and for footrest below. The facia of drawer and shatter of caimber below shall be here "Fount 4-dunt tock wood numers below the top and for footrest below. The facia of drawer and shatter of caimber below shall be made out 197m thick water proof board with Imm thick learnines in Jahrah and the made out 197m thick water proof board with Imm thick learnines in Jahrah and the proof board with Imm thick begins to the proof board with Imm thick begins to the proof of the proof of board with Imm thick begins to the proof of the proof of board with Imm thick begins to the proof of the proof of board with Imm thick begins to the proof of the proof board with Imm thick begins to the proof of the					
Providing and planeing position tables with top, vertical soled, winders, sciencing and modesty passel made out of 19mm thick water proof board with 1mm thick laminate (as) shaded approved by the Architect and surfaces, the shall all on how 75mm 4 should be made out 19mm thick water proof board with 1mm thick laminate (as) shaded approved by the Architect and sales and bottom of drawer shall be made out of 12mm thick water proof board with 1mm thick laminate (as) shaded approved by the Architect and addes and bottom of drawer shall be made out 19mm thick water proof by. Every table shall be provided with a 10mm of grain labe water proof board with 1mm thick laminate (as) shalled by the Architect and addes and bottom of drawer shall be made out 19mm thick water proof board with 1mm thick laminate (as) shalled by the Architect and addes and bottom of drawer shall be made out 19mm thick water proof board with 1mm thick laminate (as) shalled by the Architect and addes and bottom of drawer shall be made out 19mm thick water proof board with 1mm thick laminate (as) shalled by the Architect and addes and bottom of drawer shall be made out 19mm thick water proof by. The most of the Architect and addes and bottom of drawer shall be made out 19mm thick water proof board with 1mm thick laminate (as) shalled by the Architect and addes and bottom of the Architect. The water of the Architect of the Architect and the Architect and the Architect and the Architect. Approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) MINISTELLATION STATEMS 1. SUPA CAUPONER WINTHO DESK The water of the Architect. T					
Providing and placing is position tables with top, vertical aided, dividers, skirting and modestry panel mades out of 10 mm thick water proof board with 1 mm thick hamines just shade approved by the Architecty on all expased surfaces. It shall also have 7 forms 40 mm texis wood runners by the Architecty and all expased surfaces are shall also have 7 forms 40 mm texis wood runners by the Architecty and sides and bottom of drawer shall be made out 10 mm thick water proof board with 1 mm thick laminate just place 10 mm thick water proof by 1. Devery table shall be provided with a 100 mm deep facia, below the top, in which keyboard drawer wait all be adjusted; it shall be made out 10 mm thick water proof board with 1 mm thick water proof by 10 mm thick water proof board with 1 mm thick water proof by 10 mm thick water proof board with 1 mm thick water proof by 10 mm thick water proof board with 1 mm thick water proof by 10 mm thick water proof board with 20 mm thick water proof by 10 mm thick water proof board with 6 mm thick to 10 mm thick water proof board with 6 mm thick water proof by 10 mm thick water proof board and ply shall be provided with 6 mm thick to 10 mm thick water proof board and ply shall be provided with 6 mm thick water proof board and ply shall be provided with 6 mm thick water proof board with 10 mm thick water proof by 10 mm thick water proof board and ply shall be provided with 6 mm thick water proof board with 10 mm thick board water proof by 10 mm thick water proof board with 10 mm thick board water proof by 10 mm thick water proof by 10 mm	7.0	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No		
panel made out of 19mm thick water proof board with 1mm thick laminate (as) shade approved by the Architect and students of subinet below shall be made out 19mm thick water proof board with 1mm thick laminate (as) shade approved the facilities of a shade and 19mm thick water proof board with 1mm thick laminate (as) shade of 19mm thick water proof board with 1mm thick laminate (as) shade approved by the Architect and saides and bottom of drawer shall be made out of 12mm thick water proof by). Every table shall be provided with a present of the state water proof board with 1mm shick laminate (as) shade approved by the Architect and sides and bottom of drawer shall be made out 19mm thick water proof board with 1mm shick laminate (as) shade approved by the Architect and sides and bottom of drawer shall be made out of 12mm thick water proof by). The unit shall have CAM locks, handles, guides, sliding units etc. of approved make. In this shade that the shade of the shade of the shade of the state of the shade	1.2		NO.		
below the top and for footreat below. The facia of drawer and shutter of calinet below shall be made out 19mm thick water proof board with Jurn thick learning of a shade approved by the Architecti and sheds and bottom of posterior with Jurn thick learning to the property of the proper					
The facia of drawer and shutter of calaine below shall be made out 19mm thick water proof board with munt hick learnings (as/hade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof by. Provy table shall be provided with a beginning of the proof of the proof of the proof by the Architect) and add the provided with a mode out 19mm thick water proof board with 1mm thick learnings (as a proof of the proof of t					
board with 1 mm thick laminate (sat/shade approved by the Architect) and aides and bottom of drawer shall be made out of 12mm thick water proof by. Every table shall have preded with a pedested unit (sate. "A - 465am, H-720mm, D-450mm approx.) below. The table shall have a proof the shall have and the shall have been shall be provided with a pedested unit (sate. "A - 465am, H-720mm, D-450mm approx.) below. The table shall have made out 19mm thick water proof by. The unit shall base AVAI locks, handles, guides, slighting units etc. of approxed make. The job shall include for dram x 6mm grooves in between sides and open abbe disvers and thick reasons and the shall have come to the satisfaction of the Architect. Every table top shall be reasonable and other internal surfaces shall be painted with two coats of synthetic enamed over one coat of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass (so per provile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 2 mm thick float glass (so per provile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 2 mm thick float glass (so per grotile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. State 120mm at 450mm at 50mm and 60mm at 50mm at 50mm at 50mm and 60mm at 50mm at 50mm at 50mm and 60mm at 50mm at 50mm and 60					
drawer shall be made out of 12mm thick water proof ply. Every table shall be provided with a pedestal unit disc. W-4 456mm, 1-720mm, 10-80mm approx.) below. The table shall have 100mm deep faces, below the top, in which keyboard drawer unit shall be adjusted. It shall be adjusted to the adjusted of the adjusted of the adjusted and adjusted to the adjusted and adjusted to the adjusted and adjusted and hinged shutters. All the exposed edges of water proof board and ply shall be provided with 6mm internal summers shall be painted with two coast to stypathetic ensured ever one coast of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick. Boat plass less per profile with polished and bevelot (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick. Boat plass less per profile with polished and bevelot (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick. Boat plass less per profile with polished and bevelot (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick shall be not adjusted to the satisfaction of the Architect. The satisfaction of the Architect, and the satisfaction of the Architect. The Architect is a satisfaction of the Architect. The writing and finish grain profile and polishing and a satisfaction of the Architect. The Architect is a satisfaction of the					
pedestal unit (size — W. 465mm, H-720mm, D-450mm approxi) below. The table shall have 100mm deep facis, below the texp, in which keyboard drawer unit shall be adjusted. It shall be made out 19mm thick water peof board with 1mm thick laminate last ylabed approved by the unit shall have CMb looks, handles, saides, sliding units co. of approved make. The job shall include for 6mm x 6mm growers in between sides and open able drawers and langed sharters. All the exposed edges of water proof board and ply shall be provided with 6mm thick reak wood/ hard wood lipping. All tesk wood surfaces shall be melanine polished and other complete to the satisfaction of the Architect. Every valide tops shall be provided with 12mm thick float glass (so per profile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) 8.0 MISCELANEOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DESK 7 Providing and floating in position (veil) and customer writing deak (so per design) of columns, bolts, nuts, screes, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and floating approved by the scribicct, on all sides and. It shall be laid over the base of 19mm thick water proof board (already considered in various tensa) and fixed with thick laminate las per shade approved by the scribicct, on all sides and. It shall be laid over the base of 19mm thick water proof powed (live surfaces of form thickness, fixed together, where required) on rear and both sides. The froat shall be made out of 12mm thick glass shall be profiled in drawing parts with bejor 12mm thick water proof phycoal (already considered in various tensa), and fixed with the freed in the groovers, made in side members, in an inclined mammer (so per profile in drawing, parts with bego 12mm thick water proof phycoal all explained to 19mm thick Ward parts with body 13mm thick water proof phycoal and profile is a large shall be position. 8.2 CHEN		` ' ** ' ' '			
100mm deep facia, below the top, in which keyboard driver unit shall be adjusted. It shall be made out I Imm thick barniar (as /shade approved by the Architect) and sides and bottom of drivers shall be made out of 12mm thick water proof by. The Architect and sides and bottom of drivers shall be made out of 12mm thick water proof by. The The Job shall include for for man a form growers in the bevern sides mid open able drawers and hinged shutters. All the exposed edges of water proof board and ply shall be provided with form thick teak wood hard wood lipping, All teak wood surfaces shall be provided with form the satisfaction of the Architect. Every table top shall be provided with Grown that the satisfaction of the Architect. Every table top shall be provided with Grown the satisfaction of the Architect. **Approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5 x) **B.O MISCELLANEOUS ITEMS** **B. SLP & CUSTOMER WHITHO DISK** **Providing and fixing in position (with rear wall) slip and customer writing deak (as per design of overall size: 1.20mm x 50mm. The fixing shall include for expansion bolts, clears, clamps, bolts, must, servew, rivets and other anodated accessories, all complete up to the satisfaction of the Architect. **The complete of the Architect of th					
made out 19mm thick water profe board with 1 mm thick laminate (as) shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water profe play. The unit shall have CAM bocks, handles, guides, alding units etc. of approved make. The job shall include for form as Ching growers in the seven sides and the state of the provided with 6 mm thick teals wood/hard wood lipping. All teals wood surfaces shall be melamine polished and other internal surfaces shall be problemed with the case of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass age per profiley with posibled and bedeed (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass age per profiley with posibled and bedeed (25mm wide) edges all complete to the approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) 8.0 MISCELLANEOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DISK Providing and fisning in position twith rear wally alip and customer writing deak (as per design of positions) and the same of positions of the Architect. The writing top and facial sides shall be made out of 19mm thick water proof board with 1 mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof powed (two surfaces of form thickness, fixed tegether, where required on rear and both sides. The front shall be made out of 12mm thick water proof powed (two surfaces of form thickness, fixed tegether, where required on rear and both sides. The front shall be made out of 12mm thick water proof powed (two surfaces of form thickness, fixed tegether, where required on rear and both sides. The front shall be made out of 12mm thick water proof powed (two surfaces of form thickness, fixed tegether) and the position and the powed and the position and					
unit shall have CAM locks, handles, guides, sliding units eet. of approved make. The job shall include for form x form grooves in between sides and open able drawers and hinged shutters. All the exposed edges of water proof board and pb shall be provided with form the provided with form the provided with form the provided with provided and provided with form the provided and provided with 12 mm thick float glass das per profile with poils had and beveloced (25mm wide) edges all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass das per profile with poils had and beveloced (25mm wide) edges all complete to the satisfaction of the Architect. Approx Mae: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) 8.0 MISCELLANBOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DESK Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size - 1200mm x 300mm x 300mm. The fixing slad include for expansion boths, cleans, satisfaction of the Architect. The writing top and facia sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board listered considered in various inems, land fixed with anadice, it shall include for bevoling and polishings at all the exposed edges. The rate shall include for laminate (as per pond flow and polishings at all the exposed edges. The rate shall include and the provided on rear and both sides. The front shall be made out of 12mm thick glass (as per profile), It shall be fixed in the grooves, made of 6 mm thick-mase fixed topochios in drawing enclosed) with a gap of 75mm (max, in between. The space shall be further divided in four equal parts with the pol 12mm thick water proof bywood, All clags of the glass shall be provided at the top of 4mm thick water proof bywood, All clags of 16mm thick leaves required to no rear and both sides. The front shall be made out of		made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the			
The job shall include for form x 6mm grooves in between sides and open able drawers and hinged shurters. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be mealment polished and other internal surfaces shall be painted with wo costs of synthetic enamed over one cost of primer, all floor glass is aper profile youth polished and beveled (25mm wide) edges all complete to the sanisfaction of the Architect. Approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) 8.0 MISCELLANEOUS ITEMS 8.1 SLP & CUSTOMER WRITING DISK 8.2 Providing and fissing in position (with rear wall) slip and customer writing desk (as per design) of overall size - 1200mm x 450mm x 350mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screes, rivers and other anothered accessories, all complete up to the satisfaction of the Architect. The writing top and fiscing job soliton (with rear wall) slip and customer writing desk (as per design) of overall size - 1200mm x 450mm x 350mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screes, rivers and other anothered accessories, all complete up to the satisfaction of the Architect. The writing top and fiscing job shall be made out of 10mm thick water proof board labready considered in various items.) and fisced with aradilite. It shall include for beveiling and polishing at all the exposed edges. The relate shall include cost of all materials, labour, scafiolding, wastages, polishing and The Peter. Is shall be made out of 12mm thick water proof board (from thick) glass (see per profile), it shall end to the provided of the provided and the vote of shall be made out of 12mm thick glass (see per profile), it shall end to the provided of the provided and the content of the provided and the content of the provided and the vote of the provided and the content of the provided and the special part of the provided and the special part of the provided and the speci					
hinged shutters. Alt the exposed edges of water proof board and ply shall be provided with form thick teak wood/hard wood highing. Alt teak wood surfaces shall be melantine polished and other internal surfaces shall be painted with two coats of synthetic enamed over one coat of primer, all complete to the satisfaction of the Architect. Despite the provided with 12 mm thick and statisfaction of the Architect. September of the provided with 12 mm thick and statisfaction of the Architect. Approx Size: 1372 x 750 x 750 mm (4 6 x 2.5 x 2.5) 8.0 MISCELLANEOUS ITEMS 8.1 SLP ACUSTOMER WRITING DESK Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size = 1200mm x 450mm x 200mm. The fining shall include for expansion boths, cleats, cleamps, boths, nuts, screws, rivets and other anoduced accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick lammate (as per shade approved by the architect), on all sides and. It shall be laid over the base of 19mm thick water proof board (altready considered in various tems), and fixed with so of 19mm thick water proof board (altready considered in various tems), and fixed with so of 19mm thick water proof plywood (we surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile), it shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the option of the provided in the provided of 10mm thick water proof plywood. All edges of the glass shall be provided in the top of the box. An openable shutter of 259mms262mm size manner of 19mm thick BWF					
thick teak wood/hard wood lipping. All teak wood surfaces shall be melamire polished and other internal surfaces shall be painted with two conts of synthetic enamed over one coat of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick flast glass at gae per profile with polished and beeveled [25mm wdel) edges all complete to the satisfaction of the Architect. Brown with polished and beeveled [25mm wdel) edges all complete to the Approx Size: 1372 x 750 ct. 750 mm (4.6 x 2.5 x 2.5) 8.0 MISCELLANEOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DESK Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size in 2100mm x 450mm. The fixing shall include for expansion bolts, cleasts, satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with imm thick laminate (as per shade approved by the architect), on all sides and. It shall be laid over the base of 19mm thick water proof board (aready considered in various items), and fixed with araklite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scanfolding, wastages, polishing and T2 Pc ct. It shall be made out of 12mm thick water proof plywood (two surfaces of form thickness, fixed together, where required) be fixed in the grooves, made in side members, in an inclined range parts with behing the polished. All the exposed deges of saster moof hoard and nhawood shall be movided with farm thick treak. 8.2 CHEQUE DEAP BOX / SUGGESTION BOX Supplying and execting cheque drop box / suggestion box (over all size 400mmx) 50mm for the provided. All the exposed deges of saster moof hoard and nhawood shall be movided with farm thick laminate sheet of combination shade. Immer faces shall be made out of 90mms/90mm C.P. teak/steam been wood section. A slit opening of 10mmx 150mm is to be provided. Providing and faxing in position notice board (as p					
internal surfaces shall be painted with two coats of synthetic enamed over one coat of primer, all complete to the satisfaction of the Architect. Expery table top shall be provided with 12 mm thick float glass (as per profile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Approx Size: 1372 x 750 x 750 mm (4.6 x 2.5 x 2.5) **No.** **No.*					
8.0 MISCELIANEOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DESK No. 2.00 Providing and fixing in position retire rea wall slip and customer writing deak (as per design) of overall size - 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, acrews, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and fixed provided the state of the satisfaction of the Architect. The writing top and facing sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and, it shall be laid over the base of 19mm thick water proof board (laready considered in various tirens), and fixed with a state of the satisfaction of the Architect. 12mm thick water proof board (laready considered in various tirens), and fixed with a state of the satisfaction of the architect), and the capter of the satisfaction of the architect, and the capter of the satisfaction of the architect, and the capter of the satisfaction of the architect, and the capter of the satisfaction of the architect, and the capter of the satisfaction of the architect, and the capter of the satisfaction of the architect of the satisfaction of the architect of the satisfaction o					
Satisfaction of the Architect. Approx Size: 1372 x 750 x 750 mm (4,6 x 2.5 x 2.5) MISCELLANDOUS ITEMS 8.1 SLIP & CUSTOMER WAITING DESK Toroiding and fixing in position with rear wall) slip and customer writing deak (as per design) of revertal size: 1200mm x 450mm x 300mm. The fixing shall include for expansion botts, ecteat, champs, bolts, nuts, serews, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and it. shall be lad over the base of 19mm thick water proof board (already considered in various items), and fixed with araditer. Is shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T&P etc. It shall be made out of 12mm thick water proof bywood (two surfaces of 6mm thickees, tixed together, where required on rear and both sides. The front shall be made out of 12mm thick gase (as per profile) it shall centred with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exmander design of surface runof board and obwood shall be movided with famm thick leaved. Supplying and erecting cheque drop box / suggestion box (over all size 400mmx)150mmx50mm on angle of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm and of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm on the provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with Imm thick laminate short of combination shade. Inner faces shall be painted with two coats of synthetic manular short of 19mm thick water		complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick			
8.0 MISCELLANEOUS ITEMS 8.1 SLIP & CUSTOMER WRITING DESK Providing and fixing in position twith rear walli slip and customer writing desk (as per design) of overall size = 1200mm x 400mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, mist, screws, freets and other anodized accessories, all complete up to the clamps, bolts, mist, screws, freets and other anodized accessories, all complete up to the clamps, bolts, mist, screws, freets and other anodized accessories, all complete up to the clamps, bolts, mist, screws, freets and other anodized accessories, all complete up to the clamps, bolts, mist, screws, freets and other anodized accessories, all complete up to the clamps, bolts, mist, screws, freets and other anodized accessories, and for the clamps and freed with a fine of the clamps and freed with a fine fine of the clamps and fixed with a fine distinct of the clamps and fixed with a fine fine fine fine fine fine fine fine					
8.1 SLIP & CUSTOMER WRITING DESK Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion botts, cleats, clamps, boths, muts, acress, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and fixing is particle and the provided of the satisfaction of the Architect. The writing top and fixing the provide board (laterally considered in various tirens), and fixed with architect. If the satisfaction of the Architect. The writing top and fixing provided by the architect, on all sides and . It shall be ladd over the base of 19mm thick water proof board flaredly considered in various tirens), and fixed with architect in the satisfaction of the satisfaction of the architect, on all sides and . It shall be did over the base of 19mm thick water proof beginning at all the exposed relevent, where required on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the groover, made in side members, in an inclined manner (as per profile) in drawing enclosed) with a gap of 75mm (max) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed cities of water more board and network of with firm thick track. 8.2 CHRQUE BROPO BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx500mm) and ed 19 mm thick Bry grade by board and curved portion at top made out of 90mmx900mm C.P. tesk/steam beach wood section. A site opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick Bry grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate (saper thinks the beautified of the provided with the provided and pro					
Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of statistication of the Architect. The writing top and facial/ides shall be made out of 1 spmm thick water proof board with Imm thick laminate (as per shade approved by the architect), on all sides and, it shall be laid over the base of 19mm thick water proof board with a radial; it is shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 78 P etc. It shall be made out of 12mm thick water proof phywood (two surfaces of 6mm thickness, fixed together, where required on rear and both sides. The front shall be made out of 12mm thick gas per profile, It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between, The space shall be further divided in four equal parts with help of 12mm thick water proof plywood, All edges of the glass shall be polished. All the exposed edgesar of water moro hoard and notwood shall the normal from thick teak. 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (wer all size 400mmx150mm stop) and the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick by the provided with from thick teak water proof board with lam thick laminate (as per shade approved by the architect, lamina		πρριολ οιω: 1312 λ 130 λ 130 mm (4.0 x 2.3 x 2.3)			
Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of statistication of the Architect. The writing top and facial/ides shall be made out of 1 spmm thick water proof board with Imm thick laminate (as per shade approved by the architect), on all sides and, it shall be laid over the base of 19mm thick water proof board with a radial; it is shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 78 P etc. It shall be made out of 12mm thick water proof phywood (two surfaces of 6mm thickness, fixed together, where required on rear and both sides. The front shall be made out of 12mm thick gas per profile, It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between, The space shall be further divided in four equal parts with help of 12mm thick water proof plywood, All edges of the glass shall be polished. All the exposed edgesar of water moro hoard and notwood shall the normal from thick teak. 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (wer all size 400mmx150mm stop) and the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick by the provided with from thick teak water proof board with lam thick laminate (as per shade approved by the architect, lamina					
Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of statistication of the Architect. The writing top and facial/ides shall be made out of 1 spmm thick water proof board with Imm thick laminate (as per shade approved by the architect), on all sides and, it shall be laid over the base of 19mm thick water proof board with a radial; it is shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 78 P etc. It shall be made out of 12mm thick water proof phywood (two surfaces of 6mm thickness, fixed together, where required on rear and both sides. The front shall be made out of 12mm thick gas per profile, It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between, The space shall be further divided in four equal parts with help of 12mm thick water proof plywood, All edges of the glass shall be polished. All the exposed edgesar of water moro hoard and notwood shall the normal from thick teak. 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (wer all size 400mmx150mm stop) and the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick by the provided with from thick teak water proof board with lam thick laminate (as per shade approved by the architect, lamina		ARRODA A ANDONO ANDARO			
Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the statisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and it. Is shall be indied over the base of 19mm thick water proof board (already considered in various items) and fixed with aradite; it shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 78 P etc. It shall be made out of 12mm thick water proof plywood. (Iwo surfaces of form thickness, fixed together, where required on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile) in drawing enclosed) with a gap of 75mm [max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. (Iwo subsessed shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All inclined the proof of 10mm thick water proof plywood. All edges of the glass shall be polished. All inclined the proof of 10mm thick water proof plywood. All edges of the glass shall be polished. All inclined the proof of 10mm thick water proof plywood. All water proof plywood and the proof plymody of 10mm thick water proof plymody and provided with form thick water proof plymody and and curved provided with two coats of synthetic panied paint of approved shade & quality over a coat of primer. Rate to include cost of necessary. 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm.			N-	2.00	
overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facin/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various tiems), and fixed with aradict. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and TaP tel. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick gas (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max, i) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof phywood. All edges of the glass shall be polished. All the exposed sizes of xwater proof board and network shall be normided with firm thick teak. 2. CHEQUED DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) and lae peops designed to the provided with 1mm thick lack. Th	8.1	SLIP & CUSTOMER WRITING DESK	INO.	2.00	
clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and. It shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with aradite; it shall include for breveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood. (It was unfaces of form thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile). It shall be fixed with a good of 55mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof phywood. All edges of the glass shall be polished. All the exposed edges of water more flowers. 8.2 CHRQUE BROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx) 55mmx600mm made of 19 mm thick BWP grade by board and curved portion at top made out of 90mmx000mm (C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick Bwr grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with mitck Bwr grade block board is to be provided. Providing and fising in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be reade		Danciding and fining in a critical (with many cont) also and acceptance uniting deals (acceptance) of			
Satisfaction of the Architect. The writing top and facing/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and. It shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with araditie. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and TaP etc. It shall be made out of 12mm thick business, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile, It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max), in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and olwwood shall be norwided with farm thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mms600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with firm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalently wapped with stretched blazer cloth (Make- R					
thick laminate (as per shade approved by the architect), on all sides and. It shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with a radictie. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 78 P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile, It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max), in between. The space shall be further divided in four equal parts with help of 12mm thick water proof polywood. All edges of the glass shall be polished. All the exposed edges of water morol hoard and nlwwood shall be norwided with fimm thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm for thick law for the control of the provided with firm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalently wrapped with stretched blazer cloth (Make- R		overall size - 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats,			
base of 19mm thick water proof board (already considered in various items.) and fixed with analdite. It shall include for breveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of form thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water more board and nbwood shall he nowided with 6mm thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It is hall have 12mm thick tack 'the front shall have form thick float glass sliding shutter in two parts, it shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the			
araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scalfolding, wastages, posishing and T8 Petc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof polywood. All edges of the glass shall be polished. All the exposed edges of univer rored hourst not ploused and the hormoided with form thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) and of 19 mm thick BWP grade plow and and curved portion at 109 made of 19 mms00mm. C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick alminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) and lexposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with str		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm			
cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of form thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exnosed edges of water proof board and nlywood shall be nrowided with 6mm thick teak 8.2 CHEQUE DROP BOX, SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm (C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. If shall have 12mm thick tack 'the front shall have form thick float glass sliding shutter in two parts, It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalently warpped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Arc		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the			
12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the remosed ceders of water mood hoard and nhewood shall be nrevided with farm thick track No. 2.00		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with			
be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max) in between The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be mornided with 6mm thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx 150mmx 600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx 90mm c.P. teak/steam beach wood section. A slit opening of 10mmx 150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall shall have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make-Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/ partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick water proof plywood, on the back. All the expos		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include			
enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and blywood shall he nrovided with 6mm thick teak. 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmis to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces.It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be fixed with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, 7k P, wastage, transportation etc. required for proper completion of work		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of			
parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and nbwwood shall be nowided with 6mm thick teak 8.2 CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make - Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick water proof plywood, on the back. All the exposed of water proof board and ply shall be provided with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thic		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall			
the exmosed edges of water proof hoard and plywood shall be provided with 6mm thick teak CHQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Caltotex or equivalent) wapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be to covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile)		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing			
Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with Imm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shurter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Celotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kall/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with form thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper com		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal			
made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick watew wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile—Bank's logo (300mm d		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All			
made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick watew wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile—Bank's logo (300mm d	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with firm thick teak	No.	2.00	
C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make-Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX	No.	2.00	
top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make-Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm)	No.	2.00	
The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make ~ Cellotex or equivalent) wrapped with stretched blazer cloth (Make-Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof phywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile-Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm	No.	2.00	
laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track altuminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof ploand and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the	No.	2.00	
laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary 8.3 NOTICE BOARD No. 1.00 Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track altuminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile) in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm c.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade	No.	2.00	
8.3 NOTICE BOARD Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick leak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided.	No.	2.00	
Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also we 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile. Bank's logo (300mm dia. / 300mm x	8.2	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick	No.	2.00	
Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also we 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile. Bank's logo (300mm dia. / 300mm x	8.2	overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic	No.	2.00	
The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall also have 19mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding surtagement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary			
The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall also have 19mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding surtagement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary			
shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD			
shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminates sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to			
track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with fimm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD			
Board (Make - Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD			
with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (a			
thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (a			
be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (as			
melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with fimm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (as			
enamel over one coat of primer, all complete to the satisfaction of the Architect. 8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (a			
8.4 ETCHING WORK & BANK LOGO FOR BRANCH Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile) in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts. It shall have 12mm thick tack The front shall have 6mm thick float glass sli			
Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with fimm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.			
Etching for Toughened glass, Etching for Front counters / Manager Cabin. Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x		overall size — 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall he provided with fimm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.			
Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.—Bank's logo (300mm dia. / 300mm x	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It is shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with aradidte. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile) in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and pluwood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board	No.	1.00	
shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with aradidte. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C-P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (a	No.	1.00	
completion of work. It shall be made out of following profileBank's logo (300mm dia. / 300mm x	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items), and fixed with aradidte. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof hoard and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C-P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (a	No.	1.00	
	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T&P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exnosed edges of water proof board and plywood shall be provided with 6mm thick teak. CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect; on all exposed surfaces. It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along wit	No.	1.00	
commission to the satisfaction of the incineer.	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T&P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (as p	No.	1.00	
_ ,	8.3	overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect. The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and 7k? Petc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof haard and plywood shall he provided with 6mm thick teak CHEQUE DROP BOX / SUGGESTION BOX Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx00mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the pof of the box. An openable shuter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided. The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary NOTICE BOARD Providing and fixing in position notice board (as per	No.	1.00	

8.5	VERTICAL BLINDS	Sq.Ft	65.00	
0.5	Providing & fixing in position vertical blinds of Vista as per approved colour by Bank's Engineer	Sq.rt	65.00	-
	& Architect.			
8.6	Wooden Planter with Plants			
	Providing and placing in position planter made of phenol bonded 19 mm thick Premium Board (Century & Green) with top front and sides finished in 1.0 MM Thick laminate including GI trough with sand and marble chips filling and artificial plants as per the approval of the architect of not less than Rs.750. The design of the grooves shall be as per detailed drawing and complete as per Architects direction	No.	4.00	
8.7	POSTER FRAMES -WALL MOUNTED	No.		
	2 sheets of 36 " x 24 " clear acrylic (poster to be sandwiched in between). Outer sheet is 5mm thick and bevelled crystal edge polished for $3/4$ " at $8-10$ degrees on all sides in the front.Rear sheet is 5 mm thick flat.			
8.6	PAINTING & FINISHING WORK			
8.6.1	Painting on Walls and Ceilings with two or more coats of first quality of Acrylic Emulsion (Make & Shade Approved by Bank / Architect). It shall include for preparing the surfaces clean, even and smooth with thoroughly brushing with broom, scratching with patti and sand papering respectively, so that the surfaces are free from oil, grease, dirt, mortar droppings & other foreign and loose matter. It shall also include for preparing the surface and filling of holes with 2 coat of first quality acrylic wall putty (Birla Wall Care / JK / Asian) before priming coat of whiting / approved primer. The rate shall include cost of all materials such as plaster of paris, whiting / primer, glue (Fevicol), indigo / stainer, brushes, sand paper, patti, dhoti, broom stick, clean water with storage and other containers, labour, scaffolding / ladder charges, cleaning of floors and other sundries etc., all complete to the satisfaction of the Architect. Please note that in the Branch Hall, walls are to be painted below false ceiling and ceiling is not be painted.	Sq.Ft	3063.00	
8.6.2	Providing & applying 2 coats of first quality synthetic enamel paint over a coat of Zinc Chromate metal primer to steel surfaces (window grill, collapsible gate) all of approve make and shade including surface preparation by complete scrapping the existing paint / rust on grills / shutter by using chemical paint striper or suitable approved method, cleaning, filling holes, smoothening the surface all complete as directed by Bank's Engineer. (Measurement Coefficient for each side = 0.5)	Sq.Ft	80.00	
8.6.3	Rolling Shutter as same as above in 8.6.2 but measurement shall be taken for each side with	Sq.Ft	80.00	
	coefficient 1.10 each side.			
	REPAIR WORK			
	RESIDUAL EXPENSES			
	FURNISHING WORK			
	1		1	
	GROSS AMOUNT			

PROJECT - ESTIMATE FOR ELECTRICAL WORKS.

BANK - INDIAN BANK

BRANCH - K.S. SAKET NAGAR

S.N	PARTICULARS				
		Unit	Qty	Rate	Amount
1	POINTS & WIRING				
1.1	Supply & Installation of concealed Point Wiring for light, fan & exhaust fan points controlled thru modular switches complete with boxes & cover plate - The point wiring shall be carried with 3 x 1.5sq.mm FRLSH (Fire Resistant low smoke Halogen) stranded Cu. Wires in 20mm PVC conduit pipe concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The job shall be complete & to the entire satisfaction of the Bank. Each Switch board should be provided with suitable capacity fuses/ fuse indicatort. All switch & sokets shall be modular type complete with cover plate & GI/MS box. The work shall also include for cutting chase for conduits and moulded boxes, if required, in the wall/ floor (Without damaging the building/wall) along with clamping the conduit at every 600mm interval & finally finishing the surface & matching the same with the existing surface. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.				
a	Light points + AFF points including the cost of 6A switch	Point	40		
b	Ceiling fan point + exhaust fanwith step type electronic regulator controlled by one 6 amp. Modular switch. The switch should be at switchboard level.	Point	2		
С	Similar as above for wall mounting fan including box with 6A Control Switch along with clamp and ceiling rose	Point	10		
d	6A switch & Socket on SDb	Point	8		
е	One call bell point with ceiling rose/ 6amp. 3 pin socket controlled by one 6 amp. Push Modular switch. With call bell	Nos.	1		
f	Inverter Light points + AFF points including the cost of 6A switch	Point	10		
1.2	RAW POWER POINT				
	Single Power Points - Supply & Installation of Circuit Wiring (Single 6/16Amps power Points): Supply & laying of circuit wiring for 6/16 Amp. Switch points with 2 x2.5 + 1x 1.5sq.mm FRLSH (Fire Resistant low smoke Halogen) Cu stranded wires laid in 20mm conduit pipe concealed in wall/ floor/ panelling/ partitions as per requirement. The job shall be complete & to the entire satisfaction of the Bank.t. The earth wire of green color only. All switch & sokets shall be modular type complete with cover plate & GI/ MS box. The work shall also include for cutting chase for conduits and moulded boxes, if required, in the wall/ floor (Without damaging the building/wall) along with clamping the conduit at every 600mm interval & finally finishing the surface & matching the same with the existing surface. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.	Point	8		
1.3	AC POINTS AIR CONDITION POINTS -Circuit wiring with 2x4.0sq.mm + 1x 1.5sq.mm FRLS Cu stranded wires				
1.5	(Finolex/ Anchor/ Skytone) to be laid in 19mm PVC pipe heavy duty laid & concealed in wall/floor/ panelling/ partitions as per requirement. The job includes Supply & Fixing of Havells MCB protected power unit DBOXx type c/w 32A DP MCB including proper connections or any equivalent approved by Architect. The job shall be complete & to the entire satisfaction of the Bank (FOR CASSATE / SPLIT AC 2.0 TR UNITS)	Point	5		
1.4	STRONG ROOM MCB				
	Strong room controlling DP MCB at entry gate outside of strong room - Circuit wiring with 2x2.5sq.mm + 1x 1.0sq.mm stranded Cu. conductor (Finolex/Anchor/Havells) to be laid in 19mm M S conduit pipe heavy duty 16swg laid & concealed in wall/ floor/ paneling/ partitions or above false ceiling as per requirement. The electric wiring should be arranged separately for the Strong Room and it is to be connected to a plug outside. The job also includes supply & fixing of 32A DP MCB in 2way box including connections with lugs. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.	Job	1		

	IIDC (DD ANOII + ATM)			ı	I
2.1	UPS (BRANCH + ATM) Sub Main Wiring/ Cabling -: SITC of sub main wiring 4nos. 10 sq.mm Stranded copper wires for UPS Input from main incoming panel to incoming Db of UPS power input system etc. in 25mm dia PVC Heavy duty conduit complete to the satisfaction of the bank. (BRANCH + ATM)	JOB	1		
2.2	UPS Power Input System: SITC of 4way TPN Double door Db IP 42 horizontal Complete with 1no. Incoming 32A. TP MCB and 3 x 32A 2P MCB's to regulate supply for UPS complete in all respect as required and to the satisfaction of the bank.	Set	2		
2.3	Wiring for UPS Input & UPS Output (For both Critical 2Kva & Non- Critical 3Kva UPS) with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex /Anchor /Skytone) to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the Bank. (BRANCH + E-LOBBY)	JOB	2		
2.4	S/F of 32A 2P MCB in 2way metallic box including proper connectionbs thru lugs. Both the Db's shall be inter looped- Qty included in item 3. (2nos. For ATM and 2nos. For Branch)	Each	4		
2.5	UPS Output Power Distribution System: SITC of 12 way SPN Db Double door IP -43 Siemens make with 32A DP 10kA MCB and 09 nos. SP 10kA MCB complete in all respect and as required & to the satisfaction of the bank. Siemens/ L&T/ MDS/ Schnider	Set	2		
2.6	Input Wiring for UPS Db's with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the Bank. (BRANCH + ATM)	JOB	1		
2.7	Supply & fixing of 3nos. 6A switches 1 module & 3nos. sockets 2modules Modular type complete with GI Box, Cover plate etc. The work shall also include for cutting chase for conduits and moulded boxes, if required, in the wall/ floor/ panelling/ partitions (Without damaging the building/wall) & finally finishing the surface & matching the same with the existing surface. The job shall be complete & to the entire satisfaction of the Bank. & include Wiring for computer terminal points with 3 x 1.5sq.mm Fire Resistant Low Smoke Halogen stranded Cu.wires to be laid in 20mm OD PVC conduit or 1" vertical drops heavy duty laid & concealed in wall/ floor/panelling/ partitions or above false ceiling as per requirementFrom UPS - SPN Db - circuits for computer stations. (Please Note that 2 Nos. 6 amps. 5 pin modular type sockets and 1 no 16A 5 pin modular type socket, one 6A modular switch & one 16A modular switch with all accessories, inner/ outer plates, metal box etc. is to be provided near the Server rack & CCTV Rack)	Per Node	8		
3.1	MAIN INCOMING PANEL & DISTRIBUTION SITC of 200A Kit kats fuse unit 3nos in wooden patra complete with 200Amp. Neutral link	Set	1		
	complete in all respect as required.	500			
3.2	Main Incoming Panel Supply, Installation, Testing & Commissioning of main distribution board panel fabricated of 18swg (powder coated) comprising of	Nos.	1		
	Indicator lamps 3 nos. Voltmeter & ammeter(one each)				
	Rotary selector switches 2 nos for voltmeter & ammeter Busbar (each of RYB +N) copper 100 amp each				
	125 Amp MCCB(Siemens/ L&T/ ABB/ Schnider) incoming 3P adjustable 25kA				
	Changeover TPN 100 amp for DG set (Havells/ ABB/ Sochomac)				
	Outgoing 63A 3P MCB's - 6 nos. Outgoing 32Amp 2P MCB's - 6 nos.				
	Earth bus bar 25x5mm GI strip - 2nos. At the bottom.				
4	Supply Installation testing & commissioning of XLPE insulated Armoured Aluminium Conductor Cable between main panel & DB's & generator of required thickness of approved make based on the load assessment & confirmation of the same with architect. This rates include cost of lugs at both the ends (Branch +ATM)				

4.1	3.5C~x50~sq.mm cable from Meter to Kit kat to the main panel (Branch +ATM) (Aprrox - $30~mtr$)	JOB	1		
4.2	4C x 25 sq.mm cable from Main Panel TO LHS DB (Aprrox - 20 mtr)	JOB	1		
4.3	4C x 25 sq.mm cable from Main Panel to RHS DB (Aprrox - 20 mtr)	JOB	1		
4.4	4C x 25 sq.mm cable from Main Panel to Generator (Aprrox - 20 mtr)	JOB	1	-	
5	Supply, installtion, testing & commissioning of VTPN Db double door with MCB as incomer IP 42 complete in all respects for AC, PP and L & F as under - Siemens/ L & T / HAVELLS / ABB	Each	1		
5.1	RHS 6way VTPN db - Loaction RHS wall opposite Cash cabins (From entrance to Rear record room & Toilet area) - Siemens 8GB0406VRC or equivalent				
	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to neutral bus				
	3no. 32A 1P-MCBs 10 KA - AC's - 2nos. RHS & 1rear				
	3no. 16A 1P-MCBs 10 KA - for single power points - 2 cash & 1 May I help You & 2nos. D/W				
	4nos. 10A 1P-MCBs 10 KA for L&F				
	40s. 6A 1P-MCBs 10 KA for L&F				
	Blanking Plates - 2no.				
	All connections to be terminated thru lugs				
5.2	LHS 6way VTPN db - Loaction LHS wall behidn advance (From LHS LV Cash to Mgr Rm)- Siemens 8GB0406VRC or equivalent	Each	2		
	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to neutral bus				
	4o. 32A 1P-MCBs 10 KA - AC's - 3nos. LHS & 1 Mgr Rm				1
	4no. 16A 1P-MCBs 10 KA - for single power points - (LV cash, 2 CRE, 1Advance, 2 MR & 2 Router)				
	2nos. 10A 1P-MCBs 10 KA for L&F				
	2os. 6A 1P-MCBs 10 KA for L&F				
	Blanking Plates - 2no.				
	All connections to be terminated thru lugs				
	The connections to be terminated thru rugs				
6	Glow sign Board - Circuit wiring with 2x2.5sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex/Anchor/Skytone) to be laid in 20 mm PVC pipe heavy duty laid & concealed in wall/floor/ panelling/ partitions or above false ceiling as per requirement. The rates should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the Bank.	JOB	1		
7	EARTHING JOB				
7.1	Supply, Installation, Testing and Commissioning of Maintenance Free Earthing system made up of Copper bonded rod / Galvanized JK Chemrode 10 feet length, 25 mm dia. (Minimum copper bonding shall be 0.25mm) filled with highly conducting metallic compounds with permanent sealing at both the ends with lead terminal including bore well, chamber with cover and all required civil allied works, earth pit to be filled with 2 bags of 25 kg pack of Back Fill Compound (Earth Enhancement Material). The rate should be inclusive of Rod-to Conductor connectors, Earth enhancement material, Pit Cover and other accessories as required and as per specification and other applicable codes (include chamber for earthing, Earthing certificate to be submitted along with the bill). The job also includes wiring with 1 x 10 sq.mm PVC insulated copper conductor wire of 650 / 1100 Volt grade (Finolex, Polycab Make) upto 10 m as earth wire with concealed / exposed GI pipe including making all the connections with guaranteed E/N voltage of less than 3 volts and resistance less than 1 ohms.	Nos	2		

8	F - FIXTURES & FITTINGS	1		1	
8.1	Supplying and fixing PHILIPS / CROMPTON / HAVELLS make 36W LED FLAT PANEL after disconnection of existing fitting 2'x2' size in grid type false ceiling, 600x600 suitable for recess mounting, CRCA sheet, asthetic looking, complete.	Each	12		
8.2	Supplying and fixing Philips make or eqv 15 W LED round type downlighter (Philips / Crompton / Havells / Wipro / Jaguar)	Each	27		
8.3	Supply installation testing and commissioning of 1*20watt Batten type tubular LED light fitting with LEDs, driver, diffuser, and housing complete in all respects in UPS room and record /wc/bath room /suitable place with complete in all respect with required color on need basis.	Each	15		
8.4	S/F of angle holder for bulbs including cost of 12W CFL lamp for Toilets	Each	2		
8.5	Supply & installation of wall bracket fan 450 mm Metal body (Heavy duty/ high speed) Make Cropmton Greaves / Havells/Orient (to be supplied after consultation with architect/Electrical Engineer as per approved drawing)	Each	10		
8.6	Supply & fixing of the 1200 mm 48") Sweep Ceiling fan (Orient / Crompton Greaves/ Havells) with downward rod(below false ceiling), canopy etc. including of PVC flexible copper wire.(white colour)(High speed) (Warranty Cerificate is necessary)with downward rod, circular boxes, ball sockets, ceiling plates, suitable arm bracket etc. including connection with wire)White colour (WITH REGULATOR)	Each	2		
8.7	Supply & Fixing of fresh air fan 12" - Crompton Greaves / Usha/ POLAR / Bajaj	Each	2		
8.8	S/F Heavy Duty Exhaust Fan 450mm with all the accessories complete as per Bank's Instructions in UPS room	Each			
8.9	Supplying and fixing High Luminius LED strip 3000 K 24 watt 5 mtr length with driver (Philips or Havells or Cormpton)	SET	10		
10	T. DAMA CADUNO				
10 10.1	I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer I/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of GI draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects.	Each	8		
10.2	Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make	Each	8		
10.3	Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make	Each	8		
10.4	S/F of 24 Port Jack Panel fully loaded systimex make	Each	1		
10.5	S/F of 9U wall mounted rack c/w fan etc as required	Each	1		
10.6	S/F of Cable Manager as required	Each	1		
	ELECTRICAL WIRING WORKS ELECTRICAL FIXTURES				
	GRAND TOTAL AMOUNT (BRANCH + ATM)				
			*ATT D	ATES ADE EVA	CLUSIVE OF GST