# INDIAN BANK ZONAL OFFICE, BHAGALPUR

# INTERIOR FURNISHING WORKS OF INDIAN BANK TARAPUR BRANCH IN MUNGER

# TENDER SCHEDULE

Er. Amit Kumar Artcon Design Consultants, Patna G-04, Laxmi Palace, Mitra Compund, Boring Road Patna -800001 Mobile No. 9931723771, 9386717726

# INTERIOR FURNISHING WORKS OF INDIAN BANK TARAPUR BRANCH

# INDEX

S.No	Items	
01	NOTICE OF INVITATION TO TENDERER	
02	GENERAL RULES AND INSTRUCTIONS FOR THE	
	GUIDANCE OF TENDERERS	
03	GENERAL CONDITIONS OF CONTRACT	
04	SPECIAL CONDITIONS	
05	SAFETY CODE	
06	SPECIFICATIONS OF CIVIL WORKS (Interior Works)	
07	METHOD OF MEASUREMENT	
08	FORM OF TENDER FOR WORKS	
09	ARTICLES OF AGREEMENT	
10	BILL OF QUANTITIES - Interior furnishing works	
	LIST OF APPROVED BRANDS OF MATERIALS / MANUFACTURERS	
11	SUMMARY OF TOTAL COST OF ALL WORKS	
12	LAYOUT DRAWING	
13	INTERIOR DRAWINGS	



Zonal Office, Bhagalpur

Date: 03.04.2025

#### **NOTICE INVITING TENDER**

# SUB: COMPETATIVE QUOTATION/TENDER FOR INTERIOR & FURNITURE WORK OF INDIAN BANK, TARAPUR BRANCH (NEW BRANCH IN DISTRICT MUNGER) UNDER BHAGALPUR ZONE

Competitive sealed quotations/Tenders are invited in the prescribed format from the contractors. Formats of Quotation/tender documents are enclosed for submission of Interior & Furniture work of INDIAN BANK, TARAPUR BRANCH (NEW BRANCH) in District- Munger, Bihar-813221. Full details and tender documents are available in Bank's website www.indianbank.in or can be obtained from Indian Bank Zonal Office Bhagalpur. Duly filled tenders (separate sealed Technical Bid & Financial Bid in single packet along with IOI/DD of Rs. 5000/-) should be submitted as per following schedule:

1	Issue of Tender Document	From 04.04.2025 to 18.04.2025
2	Submission of Tender	On Or before 19.04.2025 at 05.00 PM
3	Opening of Tender	On 21.04.2025 after 12.30 PM
4	Date of Commencement	7 days from the date of issue of letter awarding the job
5	EMD Amount (Refundable)	Rs. 5000/- through IOI/DD in favor of Indian Bank, Payable at Bhagaipur
6	Time of Completion	30 days
7	Defect Liability Period	12 months
8	Liquidated Damages for delay	Rs.2000/- per day subject to Maximum of 10% of accepted contract amount. (If the work is not completed to the satisfaction of the employer within the stipulated period, the contractor shall be bound to pay to the employer a sum equivalent to Rs. 2000/- per day subject to celling of 10% of the accepted contract amount by way of liquidated damages un-commenced or unfinished after expiry of the completion date.
9	Payment Terms	Neither any advance nor any interim payment will be made. Payment will be made on satisfactory completion of the job on the basis of actual measurement. TDS will be deducted as per Income Tax rules. Retention Money 10% will be deducted from the bill and to be released after 12 months from the date of virtual completion provided no defects is observed during this period.
10	Technical and Financial Bids	Technical bids (Containing Letter of empanelment, Experience certificate and GST Certificate, Audited Balance Sheet, Electrical-License) should be kept in a separate envelope super scribing <technical &="" at="" bank,="" bid="" branch="" for="" furniture="" indian="" interior="" tarapur="" work=""> and financial bids in a separate envelope super scribing <financial &="" at="" bank,="" bid="" branch="" for="" furniture="" indian="" interior="" tarapur="" work="">, falling which, may lead to disqualification of tender.</financial></technical>
11	Document to be attached with the bill	Manager's Satisfaction certificate of completion, manufacture certification Bills (certified by Architect) & 4-5 photographs showing completion status of work.
12	Retention Money	10% (Including Earnest money) Up to 1 year after completion of assigned Job.

The Bank will not be bound to accept the lowest tender and reserves the right to accept or reject any or all the tender without assigning any reason whatsoever. Late/delayed tender shall not be accepted after due date and time of submission of tender.

(Ankur Jayaswa Zonal Manager

Indian Bank,

Zonal Office Bhagalpur

Zonal Office, Bhagalpur

#### **NOTICE INVITING TENDER**

Work: COMPETITIVE QUOTATION/TENDER FOR INTERIOR & FURNITURE WORK OF INDIAN BANK, TARAPUR BRANCH (NEW BRANCH IN DISTRICT MUNGER) UNDER BHAGALPUR ZONE

### General terms & Conditions:-

 Sealed Tender/quotation should be addressed to The Zonai Manager, Indian Bank, Zonai Office Bhagalpur and super scribed name of work <u>INTERIOR & FURNITURE WORK OF INDIAN BANK, TARAPUR BRANCH</u> (NEW BRANCH IN DISTRICT MUNGER) at Jagdish Complex House, Tarapur Bazar, Tarapur, District-Munger, Pin - 813221 and should reach before 05:00 PM on 19.04.2025 at Indian Bank, Zonai Office Bhagalpur.

Mailing Address: The Zonal Manager, INDIAN BANK Zonal Office Bhagalpur

Devdoot Complex, 1st Floor, Radha Rani Sinha Road, Bhagalpur-812001

- 2) No quotation/Tender will be accepted after 05:00 PM on 19.04.2025 and Tenders/quotations will be opened on 21.04.2025 after 12:30 PM unless otherwise informed.
- 3) The quotations/Tender will remain valid for a period of 3 Months from the date of opening.
- 4) Bank reserves the right to accept or reject any or all the quotations/Tender, accept part of any tender, entrust the entire work to any contractor or divide the work to more than one contractor (item wise) without assigning any reason to do so or giving explanation. The rates quoted by the contractor will help for bifurcation and no compensation will paid on this account.
- Contractor should quote rates in figures as well as in words.
- 6) All erasures and alterations made must be attested with the initials of tenderers. No overwriting is permitted.
- Joint tenders shall not be considered. Conditional tenders quoted by the contractor are liable to be rejected.
- 8) No escalation in the rates will be allowed under any circumstances.
- 9) On receipt of the intimation from the acceptance of his quotation/tender, the contractor should submit his acceptance within 3 days if the successful contractor / tenderers fail to undertake the work within 7 days after work allotment, the EMD if any, will be forfeited and acceptance of his tender may be withdrawn.
- 10) The rate quoted in the tenders shall be inclusive of all materials as required and shall be inclusive of all charges of scaffolding, lifting, tools and plants, freights / transportation, labor conditions and fluctuations in rates of excise duty, octroi, GST, VAT, Excise Duty, Service Tax and any other taxes or expenditure of carrying out the works.
- 11) The Agency is advised to inspect and examine the sites and satisfy himself as to the condition prevailing at sites and its surrounding extent of work, scope and conditions under which the work is to be executed. The contractor shall also satisfy himself about the accessibility to the premises.
- 12) The agency shall submit the offer which satisfies each and every condition laid down in this notice, failing which the tender will be liable to be rejected. Conditional bids shall not be considered and will be out rightly rejected in the very first instance.
- 13) Work will be completed in 30 days from the date of issue of tender or work order whichever is earlier. If the work be not completed to the satisfactions of employer within the stipulated period, the contractor will bound to pay to the Employer a sum equivalent to Rs.2000/- per day subject ceiling of Max 10% of the accepted contract amount by way of liquidated damages and not as penalty during which the work remains uncommented or unfinished after expiry of the completion date. The contract may be rescind by giving one week notice in case work is not executed as per specification and as per time schedule given in tender document.



- 14) The liquidated damages as mentioned in the Notice Inviting Tender may not be enforced if the contractor applies for extension of time mentioning the genuine reasons for extension. If an extension of time of completion of the work is sought on the grounds of having unavoidable hindrances in his execution or any other ground, the contractor shall apply in writing to the Zonal Manager, Indian Bank, Zonal Office Bhagalpur with full details of the circumstances which is causing such an extension. Extension of time in days will be granted by the bank if it is proved that the contractor is not a fault for extending the work beyond stipulated date of completion. At the decision in this regard taken by the bank shall be binding to the contractor.
- 15) The successful contractor is bound to carry item work necessary for completion of job even though the same are not included in the schedule of quantity. Rates of extra item will be derived from quotation. In case the rates do not exist in quotation extra item is not similar to the quoted item, then the rate will worked out on actual cost of material and labor, and other expenditure for completing that work plus 15% toward contractor profit and overhead.
- 16) The work shall be carried out in such a way that, there is least disturbance to the staff of Bank. Contractors are required to organize the work in such a way that working of staff and officers/executive of office are not affected. Contractor is required to take adequate care during progress of work to protect belongings. In case any damage, contractor at their own cost shall make the same good.
- 17) The contractor must co-operate with other contractors appointed by the bank so that entire work shall proceed smoothly and to the complete satisfaction of the bank.
- 18) Contractor will arrange necessary tools and plants for completing own work at their cast. In case of any accident the total responsibility will be on the contractor. Contractors are required to submit time schedule of work. After completion of work, cleaning of floors, walls etc are to be done on daily basis to the satisfaction of branch head / engineer-in-charge. After completion of job, the site shall be cleared of all rubbish malba/debris etc in all respect and handover the site in proper manner on completion of work.
- 19) No advance will be paid. Payment will be released on satisfactory completion of job and submission of bills. Retention Money @10% will be deducted from the bill and to be released after twelve (12) months from the date of virtual completion provided no defects is observed during the period.
- 20) In case of non-completion or delay in completion of work or removal of defects in time, the bank shall be free to appoint another agency to get the job done at contractors risk and cost.
- 21) The contractor will attend to all the defects noticed during defect liability period. If the contractor fails to attend the defects, these defects will be got rectified by the bank and the expenditure incurred on this account will be recovered from security deposit/retention money.
- 22) The work shall be got approved by the Architect/engineer and the contractor shall rectify any bad workmanship pointed out at any stage and remove from the site all the rejected materials immediately at his own cost.
- 23) The contractor shall acquaint himself with the site conditions making his own arrangements for storing of materials at site, lift, cartage etc. at his own risk and safety.
- 24) The contractor shall make adequate arrangement for watch and ward of material and shall ensure the safety, breakage and any theft of material fixed or unfixed by him or the other sub-contractor. The Bank shall not be liable for any sort of loss incurred.
- 25) The contractor shall be responsible for application of labour laws, compensation Act for injury and accident to person, whether employed by him or his sub-contractor.
- 26) The contractor shall ensure that the workmen employed by him for the execution of work are suitably covered against Workmen compensation Act and that all liabilities arising out of Workmen's compensation Act ,ESIS and other legislative enactment applicable to such works and workmen shall be to the contractor's account and responsibility.
- 27) Civil, Interior furnishing and Electrical Works will be carried out as per Bank's standard drawing / specifications and to the entire satisfaction of the bank.
- 28) The contractor shall inform the bank, well in time, to check measurements of any work which is likely to be hidden before covering.
- 29) Income Tax at prevailing rates will be deducted at source from contractor's bill and will be deposited with I.T.O. as per rules.
- 30) Any extra work or item can only be started by contractor after obtaining written approval from the Zonal Office, Item executed without-prior approval from the Zonal Office will not be considered for payment.





- 31) The quantities mentioned in the schedule of quantities are approximate. Payment will be made on the actual work done by the contractors. However the contractor should not deviate the quantity without Banks permission.
- 32) The bank has the right to alter the nature of work and to add or omit any items of work or to have the option of the same carried out departmentally or otherwise and such alterations or variations shall be carried out without prejudices to the contract.

33) The bank has the right to terminate the contract if the contractor abandons the work or fails to commence the work in time, or fails to abide by the terms and conditions of the contract.

Date: 03.04.2025 Place: Bhagalpur न वैक s Indian Bank | Ankur Jayaswal) हिन्दार के प्रकार

Indian Bank
X Zonal Office Bhagalpur

I have read and understood all the instruction/conditions given above and I have taken into account the above instructions/conditions while quoting the rates.

### TERMS AND CONDITIONS ACCEPTED

Date: Place:

Signature of the contractor

with seal

# GENERAL RULES AND INSTRUCTIONS FOR THE GUIDANCE OF TENDERERS

- 1. Tenders are hereby invited by Indian Bank, Zonal Office, BHAGALPUR for Interior furnishing works of Indian Bank <u>TARAPUR Branch & ATM</u> Estimated cost of work is <u>As per Tenderer</u>
- 2. Contract documents consisting of the plans, complete specifications, the schedule of quantities of the various classes of work to be done, and the set of conditions of contract to be completed with by the person whose tenders may be accepted, which will also be found in the form of tenders can be seen / purchased at the Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar :812001 Bihar., Mob. No. 9852943484 between the hours of 10.00a.m. 4.00p.m. and every day except on Sundays and Bankholidays.

The site for the work is available/or the site for the work shall be made available in parts as specified below.

- 3. Tenders, must be placed in sealed cover, with the name of the project written on the envelopes to be submitted addressing to <u>Asst. General Manager, Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar:812001 Bihar.</u>, on or before 19.04.2025 at 5:00 PM and will be opened by at Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar:812001 Bihar., Mob. No. 9852943484, on 21.04.2025 at 12:30 PM in presence of the tenderer who may wish to be present.
- 4. Tender documents may be downloaded and submitted duly filled in from Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar:812001 Bihar., Mob. No. 9852943484

The time allowed for the carrying out of the work will be 30 Days for TARAPUR Branch from the Second day after the date of work orders issued by the bank to commence work.

- 5. The bidder should quote in figures as well as in words the rate, and amount tendered by them. The amount for each item should be worked out and the requisite totalsgiven.
- 6. When a bidder signs a tender in an Indian language the percentage above or below and the tendered amount and the total amount tendered should also be written in the same language. In the case of illiterate contractors the rates or the amounts tendered should be attested by awitness.
- 7. Issue of tender form will be stopped 1 day before the date fixed for the opening of tenders.

इंडियन वैक**ः** Indian Book इलाहाबाद ८ ALLANABAS

- 8. Earnest Money, amounting to 5000/- in the form of Bank Draft drawn in favour of "Indian Bank Zonal Office BHAGALPUR" must accompany each tender and each tender is to be in a sealed cover super scribed "Tender for Interior Furnishing works of IndianBank TARAPUR Branch" and addressed to the Asst. Gen. Manager. Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar :812001 Bihar.
- 9. The bidder, whose tender is accepted will be required to furnish by way of security deposit for the due fulfillment of his contract & the Security Depositivill be collected as shown below:
  - (I) 10 % of first Rs.1,00,000/-
  - (II) 7.5% of second Rs.1,00,000/-
  - (III) \_5% of remaining bill amount.

The Security Deposit shall be collected as detailed in clause No 12 (page C: 6) of the General conditions of the contract.

10. The acceptance of a tender will rest with the Bank, which does not bind itself to accept the lowest tender and reserves to itself the authority to reject any or all of the tenders received without the assignment of a reason. All tenders in which any of the prescribed conditions are not fulfilled or are incomplete in any respect are liable to berejected.

The Bank reserves the right to accept the tender in full or in part and the tenderer shall have no claim for revision of rates or other conditions if his tender is accepted in parts.

- 11. Canvassing in connection with tenders is strictly prohibited and the tenders submitted by the Contractors who resort to canvassing will be liable torejection.
- 12. All rates shall be quoted on the proper form of the tender alone.
- 13. An item rate tender containing percentage below/above will be summarily rejected. However, where a bidder voluntarily offers a rebate for payment within a stipulated period, this may beconsidered.
- 14. On acceptance of the tender, the name of the accredited representative (s) of the bidder, who would be responsible for taking instructions from the Employer / CONSULTANTS shall be communicated to the Employer.



- 15. Special care should be taken to write the rates in figures as well as in words and the amounts in figures only, in such a way that interpolation is not possible. The total amount should be written both in figures and in words. In case of figures, the words 'Rs.' Should be written before the figure of rupees and words T' after the decimal figures, e.g. Rs.2.15 P. and in case of words, the word 'Rupees' should precede and the word 'Paise' should be written at the end, unless the rate is in whole rupees and followed by the words 'only', it should invariably be upto two decimal places. While quoting the rate in schedule of quantities, the word 'only' should be written closely following the amount and it should not be written in the next line. If there is discrepancy in the rate of item in figures and words, then the amount mentioned in words will be considered for tender amount purpose.
- 16. The Bank does not bind itself to accept the lowest or any tender and reserves to itself the right of accepting the whole or any part of the tender and the tenders shall be bound to perform the same at the rate quoted.
- 17. Sales Tax or any other tax on material or on finished works like work's contract tax. Turnover Tax, etc., in respect of this contract shall be payable by the bidder and the Bank will not entertain any claim whatsoever in this respect.
- 18. The tender for works shall remain open for acceptance for a period of <u>90 (Ninety) days</u> from the date of opening of tenders. If any bidder withdraws his tender before the said period, then the bank shall be at liberty to forfeit Earnest Money paid along with the tender.
- 19. It will be obligatory on the part of the bidder to tender and sign and tender documents for all the component parts and that, after the work is awarded, he will have to enter into an agreement for each component with the competent authority in the bank.
- 20. The bidder has to submit original and duplicate tender in separate sealed covers at time of submission of tender by mentioning original and duplicate on the sealed cover.



### GENERAL CONDITIONS OF CONTRACT

Except where provided for in the description of the individual items in the schedule of quantities and in the specifications and conditions laid down hereinafter and in the Drawings, the work shall be carried out as per standard specifications and under the direction of Employer/Architect.

#### 1. INTERPRETATION

In constructing these conditions, the specifications, the schedule of quantities, tender and Agreement, the following words shall have the meaning herein assigned to them except where the subject or context otherwise requires.

- i) Employer: The term Employer shall denote <u>Asst.Gen.Manager</u>, at <u>Zonal Office BHAGALPUR</u>, <u>Indian Bank</u> with their Corporate Office at Premises, Expenditure & Estate Department, Indian Bank, Corporate Office, 254-260, Avvai Shanmugam Salai, Royapettah, Chennai 600014 and any of its employees representative authorized on their behalf.
- i) CONSULTANTS: The term CONSULTANTS shall means M/s. ARTCON DESIGN CONSULTANTS, Architectural Engineers& Consulting Engineers, G-04, Laxmi Palace, Mitra Compound, Boring Road, Patna-800001 or in the event of his/ their ceasing to be the CONSULTANTS for the purpose of this contract such other persons/s as the Employer shall nominate for the purpose.
- ii) Bidder: The firm who has submitted the bid in response to the tender notice issued by the Bank.
- iv) Contractor: The term Contractor shall mean Bidder selected by Employer for performance of the work and his/ their heirs, legal representatives, assigns and successors.
- iv) Site: The site shall mean the site where the works are to be executed as shown within boundary in red border on the site plan including any building and erections thereon allotted by the Employer for the contractor's use.
- v) Site Engineer: The Site Engineer may be appointed by the bank. The bank may also determine the number of Site Engineers and the supporting staff at site office to assist them and also whether the Site Engineer shall be temporary or permanent. As far as possible, the Site Engineer should assume charge of his post before the contractor reports on site of work. Where more than one Site Engineer is appointed, one of them shall be designated as Senior Site Engineer by the Premises Department and the other Site engineer shall be resorting to the Senior Site Engineer.



vi) Drawings: The work is to be carried out in accordance with drawings, specifications, the schedule of quantities and any further drawings which may be given by the Employer during the execution of the work.

All drawings relating to work given to the Contractor together with a copy of schedule of quantities are to be kept at site and the Employer/CONSULTANTS shall be given access to such drawings or schedule of quantities whenever necessary.

In case any detailed Drawings are necessary, the Contractor shall prepare such detailed drawings and/or dimensional sketches therefore and have it confirmed by the Employer/CONSULTANTS prior to taking up such work.

The Contractor shall ask in writing for all clarifications on matters occurring anywhere in drawings, specifications and schedule of quantities or to additional instructions at least <u>Ten</u> days ahead from the time when it is required for implementation so that the Employer may be able to give decision thereon.

- vii) "The Works" shall mean the work or works to be executed or done under this contract.
- viii) "Act of Insolvency" shall mean any act as such as defined by the Presidency Towns Insolvency Act or in Provincial Insolvency Act or any amending statutes.
- ix) "The Schedule of Quantities" shall mean the schedule of quantities as specified and funning part of this contract.
- x) "Priced Schedule of Quantities" shall mean the schedule of quantities duly priced with the accepted quoted rates of the Contractor.

#### 2. Scope

The work consists of <u>Tender for Interior Furnishing works of Indian Bank TARAPUR Branch / ATM</u> in accordance with the "drawings" and "Schedule of Quantities". The Civil works are within scope of this tender. It includes furnishing all materials, labour, tools and equipment and management necessary for and incidental to the construction and completion of the work. All work, during its progress and upon completion, shall conform to the lines, elevations and grades as shown on the drawings furnished by the Employer/CONSULTANTS. Should any detail essential for efficient completion of the work be omitted from the drawings and specifications it shall be the responsibility of the Contractor to inform the Employer/CONSULTANTS and to furnish and install such detail with Employer's/Architect's concurrence, so that upon completion of the proposed work the same will be acceptable and ready for use.

Employer/CONSULTANTS may in their absolute discretion issue further drawings and/or written instructions, details, directions and explanations, which are, hereafter collectively referred to as "The Employer's/Architect's instructions" in regard to.

- The variation or modification of the design quality or quantity of works or the addition or omission or substitution of anywork.
- b) Any discrepancy in the drawings or between the schedule of quantities and/or drawings and/or specification.
- c) The removal from the site of any defective material brought thereon by the Contractor and the substitution of any other material lthereof.
- d) The demolition removal and/or re-execution of any work executed by the Contractor/s.
- e) The dismissal from the work of any persons employed there upon.
- f) The opening up for inspection of any work covered up.
- g) The rectification and making good of any defects under clauses hereinafter mentioned and those arising during the maintenance period (retention period).

The Contractor shall forthwith comply with and duly execute any work comprised in such Employer's/Architect's instructions, provided always that verbal instructions, directions and explanations given to the Contractor's or his representative upon the works by the Employer/CONSULTANTS shall if involving a variation be confirmed in writing to the Contractor's within seven days. No works, for which rates are not specifically mentioned in the priced schedule of quantities, shall be taken up without written permission of the Employer/CONSULTANTS. Rates of items not mentioned in the priced schedule of quantities shall be fixed by the employer in consultation with the CONSULTANTS as provided in clause "Variation".

The contractor shall get test certificate of various materials if required by Employer/ Architect at his

Regarding all factory made products for which ISI marked products are available, only products bearing ISI marking shall be used in the work as shown in list of approved brand of materials.



# 3. TENDERER SHALL VISIT THE SITE

Intending bidder shall visit the site and make himself thoroughly acquainted with the local site condition, nature and requirements of the works, facilities of transport condition, effective labour and materials, access and storage for materials and removal of rubbish. The bidder shall provide in their tender for cost of carriage, freight and other charges as also for any special difficulties and including police restriction for transport etc., for proper execution of work as indicated in the drawings. The successful bidder will not be entitled to any claim of compensation for difficulties faced or losses incurred on account of any site condition which existed before the commencement of the work or which in the opinion of the Employer/CONSULTANTS might be deemed to have reasonably been inferred to be so existing before commencement ofwork.

#### 4. TENDERS

The entire set of tender paper issued to the bidder should be submitted fully priced and also signed on the last page together with initials on every page. Initial/signature will indicate the acceptance of the tender papers by the bidder.

(Also see Para 15 of General Rules and Instructions for guidance of bidders). (Page B: 1) The schedule of quantities shall be filled in as follows:

- i) The 'Rate' column to be legibly filled in ink in both English figures and Englishwords.
- ii) Amount column to be filled in for each item and the amount for each sub head as detailed in the "Schedule ofQuantities".
- iii) All corrections are to beinitialed.
- iv) The 'Rate Column' for alternative items shall be filledup.
- v) The 'Amount' column for alternative items of which the quantities are not mentioned shall not be filledup.
- vi) In case of any errors/omissions in the quoted rates, the rates given in the tender marked 'Original' shall be taken as correctrates.

No modifications, writing or corrections can be made in the tender papers by the bidder, but may at his option offer his comments or modifications in a separate sheet of paper attached to the original tender papers.

The Employer reserves the right to reject the lowest or any tender and also to discharge any or all of the tenders for each section or to split up and distribute any item of work to any specialist firm or Finns, without assigning any reason.

The bidders should note that the tender is strictly on the item rate basis and their attention is drawn to the fact that the rates for each and every item should be correct, workable and self-supporting. If called upon by the Employer/CONSULTANTS detailed analysis of any or all the rates shall be



submitted. The Employer/CONSULTANTS shall not be bound to recognize the contractor's analysis.

The work will be paid for as "measured work" on the basis of actual work done and not as "lump sum" contract. All items of work inscribed in the schedule of quantities are to be deemed and paid as complete works in all respects and details including preparatory and finishing works involved, directly, related to and reasonably detectable from the drawings, specifications and schedule of quantities and no further extra charges will be allowed in this connection. In the case of lump-sum charges in the tender in respect of any item of works, the payment of such items of work will be made for the actual work done on the basis of lump-sum charges as will be assessed to be payable by the Employer/CONSULTANTS.

The Employer has power to add to, omit from any work as shown in drawings or described in specifications or included in schedule of quantities and intimate the same in writing but no addition, omission or variation shall be made by the contractor without authorization from the Employer. No variation shall vitiate the contract.

The bidder shall note that his tender shall remain open for consideration for a period of <u>three months</u> from the date of opening of the tender.

#### 5. AGREEMENT

The successful bidder may be required to sign agreement as may be drawn up to suit local conditions and shall pay for all stamps and legal expenses, incidental thereto.

#### 6. PERMITS ANDLICENCES

The Contractor will arrange permits and licenses for release of material, which are under Government control. The employer will render necessary assistance, sign any forms or applications that may be necessary. The basic price of controlled material for the purpose of valuing the tender is to be considered as stipulated below. This will also be the basis of adjustments in settling the contractor'sbills.

#### 7. GOVERNMENT AND LOCAL RULES

The Contractor shall conform to the provisions of all local Bye-laws and Acts relating to the work and to the Regulations etc., of the Government and Local Authorities and of any company with whose system the structure is proposed to be connected. The Contractor shall give all notices required by said Act, Rules, Regulations and Bye-laws etc. and pay all fees payable to such authority/authorities for execution of the work involved. The cost, if any, shall be deemed to have been included in his quoted rates, taking into account all liabilities for licenses, fees for footpath, encroachment and restorations etc., and shall indemnify the Employer against such liabilities and shall defend all actions arising from such claims orliabilities.

## 8. TAXES AND DUTIES

डियन बैंक **रा**ndian Bank डलाहाबाद ८ ALLAHABAD)

The bidders must include in their tender prices quoted for all duties royalties, cess Service Tax, GST and sales tax or any other taxes or local charges if applicable.

No extra claim on this account will in any case be entertained.

# 9. PROVISIONAL SUMS (PS)

All provisional sums described in the schedule of quantities as P S shall be exclusively allotted to the purchase of materials and not for any handling and fixing to be done by the contractor. Such costs of handling and fixing with profit (including transport charges if required) shall be separately included in the contract price as described in the schedule of quantities.

The disposal of the amounts covered under this head will be absolutely at the discretion of the Employer. Contractor is to make payments for these materials to the suppliers on certificate or order issued by the Employer/Architecture and realizes them through his bills from the Employer.

### 10. QUANTITY OF WORK TO BE EXECUTED

The quantities shown in the schedule of quantities are intended to cover the entire new structure indicated in the drawings but the Employer reserves the right to execute only a part or the whole or any excess thereof without assigning any reasons therefore.

#### 11. OTHER PERSONS ENGAGED BY THE EMPLOYER

The employer reserves the right to execute any part of the work included in this contract or any work, which is not included in this contract by other Agency or persons and Contractor, shall allow all reasonable facilities and use of his scaffolding for the execution of such work. The Contractor shall extend all cooperation in this regard.

#### 12. EARNEST MONEY AND SECURITY DEPOSIT

The bidder will have to deposit an amount of 5000/- in the form of Bank Draft drawn in favour of "Indian Bank Zonal Office BHAGALPUR" at the time of submission of tender as an Earnest Money. The employer is not liable to pay any interest on the Earnest Money. Tender will be considered as incomplete, if not accompanied with the EMD and will be rejected.

The Earnest Money of the unsuccessful bidder will be refunded without any interest soon after the decision to award the work is taken or after the expiry of the validity period of the tender.

The successful bidder to whom the contract is awarded will have to deposit as initial security deposit a further sum to make up 2% of the value of the accepted tender including the Earnest Money. The initial Security Deposit will have to be made within Four days from the date of acceptance of tender, failing which the Employer at his discretion may revoke the letter of acceptance and forfeit the Earnest Money deposit furnished along with the tender. The Security Deposit will be collected as shown below:

(I) 10 % of first Rs.1,00,000/- (II) 7.5% of second Rs.1.00.000/- (III) 5% of remaining bill amount.

The retention amount will be refunded to the contractor 14 days (Fourteen) days after the end of defects liability period provided he has satisfactorily carried out all the work and attended to all defects in accordance with the conditions of the contract. No interest is allowed on retention money.



# 13. CONTRACTOR TO PROVIDE EVERY THING NECESSARY

The Contractor shall provide everything necessary for the proper execution of the work according to the intent and meeting of the drawings, schedule of quantities and specifications taken together whether the same may or may not be particularly shown or described therein provided that the same can reasonably be inferred there from and if the contractor finds any discrepancies therein he shall immediately and in writing, refer the same to the Employer/CONSULTANTS whose decision shall be final and binding. The contractor shall provide himself for ground and fresh water for carrying out of the works at his own cost. The Employer shall on no account be responsible for the expenses incurred by the contractor for hired ground or fresh water obtained from elsewhere.

The rates quoted against individual items will be inclusive of everything necessary to complete the said items of work within the contemplation of the contract, and beyond the unit price no extra payment will be allowed for incidental or contingent work, labor and/or materials inclusive of all taxes and duties whatsoever except for specific items, if any, stipulated in the tender documents.

The contractor shall supply, fix and maintain at his own cost, for the execution of any work, all tools, tackles, machineries and equipment's and all the necessary centering, scaffolding, staging, planking, timbering, strutting, shoring, pumping, fencing, boarding, watching and lighting by night as well as by day required not only for the proper execution and protection of the said work but also for the protection of the public and safety of any adjacent roads, streets, walls, houses, buildings, all other erections, matters and things and the contractor shall take down and remove any or all such catering, scaffolding, planking, timbering, strutting, shoring etc., as occasion shall be required or when ordered so to do, and shall fully reinstate and make good all matters and things disturbed during the execution of works to the satisfaction of the Employer/CONSULTANTS.

The contractor shall at all times give access to workers employed by the Employer or any men employed on the buildings and to provide such parties with proper sufficient and if required, special scaffolding, hoists and ladders and provide them with water and lighting and leave or make any holes, grooves etc., if any work, where directed by the employer as may be required to enable such workmen to lay or fix pipes, electrical wiring, special fittings etc. The quoted rates of the bidders shall accordingly include all these above mentioned contingentworks.

### 14. TIME OF COMPLETION, EXTENSION OF TIME & PROGRESSCHART

1. Time of Completion: The entire work is to be completed in all respects within the stipulated period. The work shall deemed to be commence within One day from the date of acceptance letter or date of handing over of site, whichever is earlier. Time is the essence of the contract and shall be strictly observed by the Contractor.

The work shall not be considered as complete until the Employer/CONSULTANTS have certified in writing that this has been completed and the Defects Liability Period shall commence from the date of such certificate.

2 Extension of Time: If in the opinion of the Employer/CONSULTANTS the works be delayed

(a) byreasonofanyexceptionallyinclementweather,or

- (b)byreasonofinstructions from the Employer in consequence of proceedings taken or threatened by or disputes, with adjoining or neighboring owners or
- (c) by the works, or delay, of other Contractors or tradesmen engaged or nominated by the Employer and not referred to in the specification or
- (d) by reason of authorized extra and additions or
- (e) by reason of any combination of workmen or strikes or lock-out affecting any of the building trades or
- (f) from other causes which the Employer may consider are beyond the control of the contractor, the Employer at the completion of the time allowed for the contract shall make fair and reasonable extension of time for completion in respect there for. In the event of the Employer failing to give possession of the site upon the day specified above the time of completion shall be extended suitably.

In case of such strikes or lockouts, as are referred to above, the contractor shall, immediately give the Employer, written notice thereof. Nevertheless, the contractor shall use his best endeavors all that to prevent delay, and shall do all that may be reasonably required, to the satisfaction of the Employer to proceed with the works and on his doing so that it will be ground of consideration by the Employer for an extension of time as above provided. The decision of the Employer as to the period to be allowed for an extension of time for completion hereunder (which decision shall be final and binding on the contractor) shall be promulgated at the conclusion of such strike or lock-out and the Employer shall then, in the event of an extension being granted, determine and declare the final completion date. The provision in clause 15 with respect to payment of liquidated damages shall, in such case, be read and construed as if the extended date fixed by the Employer were substituted for and the damage shall be deducted accordingly.

3. Progress of Work: During the period of construction the Contractor shall maintain proportionate progress on the basis of a Programme Chart submitted by the Contractor immediately before commencement of work and agreed to by the Employer/CONSULTANTS. Contractor should also include planning for procurement of scarce material well in advance and reflect the same in the Programme Chart so that there is no delay in completion of the project.

### 15. LIQUIDATED DAMAGES

Should the work be not completed to the satisfaction of the Employer/CONSULTANTS within the stipulated period, the Contractor shall be bound to pay to the Employer a sum calculated as given below by way of liquidated damages are not as penalty during which the work remains uncommenced or un-finished after the expiry of the completion date.

For contracts having time for completion 6 months and less	2000/- per day or 1% of the estimated amount shown in the tender per week subjected to
	10% of the accepted contracted sum.
For contracts having time for completion exceeding 6 months but not exceeding 24 months	2000/- per day or 0.5% of the estimated amount shown in the tender per week subjected to 7.5% of the accepted contracted sum
For contracts having time for completion exceeding 24 months	2000/- per day or 0.25% of the estimated amount shown I the tender per week subjected to 5% of the accepted contracted sum.



# 16. TOOLS, STORAGE OF MATERIALS, PROTECTIVE WORKS AND SITEOFFICE REQUIREMENTS

The Contractor shall provide, fix up and maintain in an approved position proper office accommodation for the contractor's representative and staff which offices shall be open at all reasonable hours to received instruction notices or communications and clear away on completion of the works and make good all workdisturbed.

All drawings maintained on the site are to be carefully mounted on boards of appropriate size and covered with a coat of approved varnish. They are to be protected from ravages of termites, ants and other insects.

The contractor shall provide at his own cost all-artificial light required for the work and to enable other contractors and sub-contractors to complete the work within the specified time.

The contractor shall provide a suitable temporary hut for the watchmen and clear away the same when no longer required and to provide all necessary attendance, light etc. required.

The contractor shall arrange for temporary latrines for the use of workers and filed staff and keep the same in a clean and sanitary condition to the satisfaction of the Public Health Authorities and shall cause such latrines and soil to be cleared away whenever necessary and shall make good all the works disturbed by theseconveniences.

Every precaution shall be taken by the contractor to prevent the breeding of mosquitoes on the works during the construction, and all receptacles, cisterns, water tanks etc., used for the storage of water must be suitably protected against breeding of mosquitoes. The contractor shall identify the Employer against any breach of rules in respect of antimalarial measures.

The Contractor shall not fix or place any placards or advertisement of any description or permit the same to be fixed or placed in or upon any boarding, gantry, building structure other than those approved by the Employer.

Protective Measures: The Contractor from the time of being placed in possession of the site must make suitable arrangements for watching, lighting and protecting the work, the site and surroundings properly by day by night on Sundays and other holidays.

Contractor shall indemnify the Employer against any possible damage to the building, roads, or members of the public in course of execution of the work.

The Contractor shall provide necessary temporary enclosures, gates, entrances etc., for the protection of the work and materials and for altering and adopting the same as may be required and removing on completion of the works and making good all works disturbed.



Storage of Materials: The Contractor shall provide and maintain proper sheds for the proper storage and adequate protection of the materials etc. and other work that may be executed on the site including the tools and materials of sub-contractors and remove same on completion.

Tools: Levels, prismatic compass, steel and metallic tapes and all other instruments found necessary on the works shall be provided by the Contractor for the due performance of this contract as instructed by the Site Engineer.

All measuring tapes shall be of steel and suitable scaffolding and ladders that may be required for safely taking measurement and shall be supplied by the Contractor.

The masons and the supervisors on the work shall carry with them always a one meter or two-meter steel tape, a measuring tape of 30metres, a spirit level, a plumb bob and a square and shall check the work to see that the work is being done according to the drawing and specifications. The Site Engineer will use any or all measuring instruments or tools belonging to the Contractors as he chooses for checking the works executed or being executed on the contract.

The Contractor should cover in his rates for making provisions for all reasonable facilities for the use of his scaffolding, tools and plant etc., by subcontractors for their work.

#### 17. NOTICE AND PATENTS OF APPROPRIATE AUTHORITY ANDOWNERS

The Contractor shall conform to the provisions of any Acts of the Legislature relating to the work and to the Regulations and Bye-laws of any authorities, and/or any water lighting and other companies, and/or authorities with whose systems the structures were proposed to have connection and shall before making any variations from the drawings or specification that may be associated to so conform, give the Employer/CONSULTANTS written notices specifying the variations proposed to be made and the reasons for making them and apply for instruction thereon. The Employer/CONSULTANTS on receipt of such intimation shall give a decision within a reasonable time.

The Contractor/s shall arrange to give all notices required for by the said Acts, Regulations or Byelaws to be given to any authority and to pay to such authority or to any public officer all fees that may be properly chargeable in respect of the work and lodge the receipts with the Employer. The Contractor shall indemnify the Employer against all claims in respect of patent rights, royalties, damages to buildings, roads or members of public in course of execution of work and shall defend all actions arising from such claims and shall keep the Employer saved harmless and indemnified in all respects from such actions, costs and expenses.

#### 18. CLEARANCE SITE AND SETTING OUTWORKS

इलाहाचाद 🗸 🔠 🔡

The site shown on the plan shall be cleared of all obstructions and materials, rubbish of all kinds. The contractor shall set out the works and shall be responsible for the true and perfect setting out of the work and for the correctness of the positions, levels, dimensions and alignment of all parts thereof. If at any time, any error shall appear during the progress of any part of the work the contractor shall at his own expenses rectify such error, if called upon to the satisfaction of the Employer. The contractor shall further set out the works to the alternative positions at the site until

one is finally approved and the rates quoted in his tender should include for this and no extra on this account will be entertained.

#### 19. DATUM

The average Floor level will be considered "Datum" which is however, subject to final confirmation by the Employer/CONSULTANTS. All levels shown in the drawings are to be strictly adhered to.

#### 20. BENCHES

Any contractor is to construct and maintain proper benches of all the main walls, in order that the lines and levels may be accurately checked at all items.

The wire nails will be driven on the top of Sal wood post on the centre lines of partitions, semi-partitions, counters, walls, in order that lines may be stretched between the Sal wood posts and accurate intersection of interior works. Centre line of interior items etc., may be clearly indicated and checked at any time if it is so required.

# 21. CONTRACTOR IMMEDIATELY TO REMOVE ALL OFFENSIVEMATTERS

All dust, filth or other matters of any offensive nature taken out of Interior items or other place shall not be deposited on the surface but shall be at once carted away by the contractor to place outside site of work.

#### 22. ACCESS

Any authorized representative of the Employer shall at all reasonable times have free access to the works and/or to the workshops, factories or other places where materials are being prepared or constructed for the work and also to any place where the materials are lying or from where they are being obtained and the contractor shall give every facility to the bank or their representatives necessary for inspection and examination and test of the materials and workmanship. Except the representatives of the Employer no person shall be allowed at any time without the written permission of the Employer.

#### 23. MATERIALS, WORKMANSHIP, SAMPLES, TESTING OFMATERIALS

All the works specified and provided for in the specifications or which may be required to be done in order to perform and complete any part thereof shall be executed in the best and most workman like manner with materials of the best and approved quality of the respective kinds in accordance with the particulars contained in and implied by the specifications and as represented by the drawings or according to such other additional particulars, and instructions as may from time to time be given by the Employer/CONSULTANTS during the execution of the work and to his entire satisfaction.

If required by the Employer/CONSULTANTS the Contractor shall have to carry out tests on materials and workmanship in approved materials testing laboratories or as prescribed by the Employer/CONSULTANTS at his own cost to prove that the materials etc., under test conform to the relevant I.S. Standards or as specified in the specifications. The necessary charges for preparation of sample, transporting, testing etc., shall have to be borne by the Contractor. No extra payment on this account should in any case be entertained.

All the materials except where otherwise described stores and equipment required for the full performance of the work under the contract must be provided through normal channels and must include charge for import duties, sales tax, Octroi and other charges and must be the best of their kind available and the Contractor/s must be entirely responsible for the proper and efficient carrying out of the work. The work must be done in the best workmanlike manner. Samples of all materials to be used must be submitted to the Employer/CONSULTANTS when so directed by the Engineer/CONSULTANTS and written approval from Employer/CONSULTANTS must be obtained prior to placement of order.

Should the work be suspended by reason of rain, strike, lock-outs or any other cause, the contractor shall take all precautions necessary for the protection of work and at his own expenses shall make good any damage arising from any of these causes. The Contractor shall cover up and protect from damages, from any cause, all new work and supply all temporary/doors, protection to windows, and any other requisite protection for the execution of the work whether by himself or special tradesmen or sub-contractor and any damage caused must be made good by the contractor at his own expenses.

#### 24. REMOVAL OF IMPROPERWORK

The Employer shall during the progress of the work have power to order in writing from time to time the removal from the work within such reasonable time or times as may be specified in the order of any materials which in the opinion of the Employer/Architect are not in accordance with specifications or instructions, the substitution or proper re-execution of any work executed with materials or workmanships not in accordance with the drawings and specifications or instructions. In case the contractor refuses to comply with order the Employer shall have the power to employ and pay other agencies or carryout the work and all expenses consequent thereon or incidental thereto as certified by the Employer/Architect shall be borne by the contractor or may be deducted from any money due to or that may become due to the contractor. No certificate, which may be given by the CONSULTANTS, shall relieve the contractor from his liability in respect of unsound work or bad materials.

#### 25. SITEENGINEER

The term 'Site Engineer' shall mean the person appointed and paid by the Employer to superintend the work. The contractor shall afford the Site Engineer every facility and assistance for examining the works and materials and for checking and measuring work and materials. The Site Engineer shall have no power to revoke, alter, enlarge or relax any requirements of the contractor or to sanction any day work, additions, alternations, deviations or omissions or any extra work whatever, except in so far as such authority may be specially conferred by a written order of the Employer.

The Site Engineer shall have power to give notice to the contractor or to his foreman, of non-approval of any work or materials and such work shall be suspended or the use of such materials shall be discontinued until the decision of the Employer is obtained. The work will from time to time to be examined by the CONSULTANTS, Engineer from the premises Department of the Employer and the Site Engineer. But such examination shall not in any way exonerate the contractor from the obligation to remedy any defects, which may be found to exist at any stage of the work or after the same is complete. Subject to the limitation of this clause the contractor shall take instructions only from the CONSULTANTS/Employer.

इतिहानाद के ALLAHASAS

#### 26. CONTRACTOR'S EMPLOYEES

The Contractor shall employ technically qualified and competent supervisors for the work who shall be available (by turn) throughout the working hours to receive and comply with instructions of the Employer/CONSULTANTS. The Contractor shall engage at least one experienced Engineer as site-in-charge for execution of the work. The contractor shall employ in connection with the work persons having the appropriate skill or ability to perform their job efficiently.

The contractor shall employ local labourers on the work as far as possible.

No labourer below the age of sixteen years and who is not an Indian National shall be employed on the work.

Any labourer supplied by the Contractor to be engaged on the work on day-work basis either wholly or partly under the direct order or control of the Employer or his representative shall be deemed to be a person employed by the Contractor. The Contractor shall comply with the provisions of all labour legislation including the requirements of

- a) The Payment of Wages Act.
- b) Employer's Liability Act.
- c) Workmen's Compensation Act.
- d) Contract Labour (Regulation & Abolition) Act, 1970 and Central Rules 1971.
- e) Apprentices Act 1961
- f) Any other Act or enactment relating there to and rules framed thereunder from time to time

The Contractor shall keep the Employer saved harmless and indemnified against claims if any of the workmen and all costs and expenses as may be incurred by the Employer in connection with any claim that may be made by any workmen.

The Contractor shall comply at his own cost with the order of requirement of any Health Officer of the State or any local authority or of the Employer regarding the maintenance of proper environmental sanitation of the area where the contractor's labourers are housed or accommodated, for the prevention of small pox, cholera, plague, typhoid, malaria and other contagious diseases. The Contractor shall provide, maintain and keep in good sanitary condition adequate sanitary accommodation and provide facilities for pure drinking water at all times for the use of men engaged on the works and shall remove and clear away the same on completion of the works. Adequate precautions shall be taken by the contractor to prevent nuisance of any kind on the works or the lands adjoining the same.

The Contractor shall arrange to provide first-aid treatment to the labourers engaged on the works. He shall within 24 hours of the occurrence of any accident at or about the site or in connection with execution of the works, report such accident to the Employer and also to the competent authority where such report is required bylaw.



# 27. DISMISSAL OFWORKMEN

The Contractor shall on the request of the Employer immediately dismiss from works any person employed thereon by him, who may in the opinion of the Employer be unsuitable or incompetent or who may misconduct himself. Such discharges shall not be the basis of any claim for compensation or damages against the Employer or any of their officer or employee.

#### 28. ASSIGNMENT

इंडियन वेंक क Indian Bank | इलाहाबाद क ALLAHABAD

The whole of the works included in the contract shall be executed by the contractor and the contractor shall not directly or indirectly transfer, assign or underlet the contract or any part, share or interest therein nor, shall take a new partner, without written consent of the Employer and no subletting shall relieve the contractor from the full and entire responsibility of the contract or from active superintendence of the work during their progress.

# 29. DAMAGE TO PERSONS AND PROPERTY INSURANCEETC.

The Contractor shall be responsible for all injury to the work or workmen to persons, animals or things and for all damages to the structural and/or decorative part of property which may arise from the operations or neglect of himself or of any subcontractor or of any of his or a sub-contractor's employees, whether such injury or damage arise from carelessness, accident or any other cause whatsoever in any way connected with the carrying out of this contract. The clause shall be held to include inter-alia, any damage to buildings whether immediately adjacent or otherwise, and the works forming the subject of this contract by rain, wind or other inclemency of the weather. The Contractor shall indemnify the Employer and hold harmless in respect of all and any expenses arising from any such injury or damages to persons of property as aforesaid and also in respect of any claim made in respect of injury or damage under any acts of compensation or damage consequent upon such claim.

The Contractor shall reinstate all damage of every sort mentioned in this clause, so as to deliver the whole of the contract works complete and perfect in every respect and so as to make good or otherwise satisfy all claims for damages to the property or third parties.

The Contractor shall effect the insurance necessary and indemnify the Employer entirely from all responsibility in this respect. The insurance must be placed with a company approved by the Employer and must be effected jointly in the name of the contractor and the Employer and the policy lodged with the latter. The scope of insurance is to include damage or loss to the contract itself till this is made over in a complete state. Insurance is compulsory and must be effected from the very initial stage. The contractor shall also be responsible for anything, which may be excluded from damage to any property arising out of incidents, negligence or defective carrying out of this contract.

The Employer shall be at liberty and is hereby empowered to deduct the amount of any damages, compensations, costs, charges and expenses arising or accruing from or in respect of any such claim or damages from any sums due or to become due to the contractor.

#### 30. INSURANCE

Unless otherwise instructed the contractor shall insure the works and keep them insured until <u>one</u> month after the virtual completion of the contract against loss or damage by fire and/or earth quake, flood. The contractor shall take insurance policies

- (1) Contractors all risk insurance policy
- (2) Workman compensation policy.

The insurance must be placed with a company approved by the Employer, in the joint name of the Employer and the contractor for such amount and for any further sum if called to do so by the employer, the premium of such further sum being allowed to the contractor as an authorized extra.

The contractor shall deposit the policy and receipt for premiums paid with the Employer within Four days from the date of issue of work order unless otherwise instructed. In default of the contractor insuring as provided above, the Employer on his behalf may so insure and may deduct the premiums paid from any money due, or which may become due to the contractor. The contractor shall as soon as the claim under the policy is settled or the work reinstated by the Insurance Company should they elect to do so, proceed with due diligence with the completion of the works in the same manner as though the fire has not occurred and in all respects under the conditions of the contract. The contractor in case of rebinding or reinstatement after fire shall be entitled to extension of time for completion as the Employer may deem fit.

#### 31. ACCOUNTS RECEIPTS & VOUCHERS

The contractor shall, upon the request of the Employer furnish them with all the invoices accounts, receipts and other vouchers that they may require in connection with the works under this contract. If the Contractor shall use materials less than what he is required under the contract the value of the difference in the quantity of the materials he was required to use and that he actually used shall be deducted from his dues. The decision of the Employer shall be final and binding on the contractor as to the amount of materials the contractor is required to use for any work under this contract.

32. Before taking any measurement of any work the Site Engineer or a subordinate deputed by him shall give reasonable notice to the contractor. If the contractor fails to attend at the measurements after such notice or fails to countersign or to record the difference within a week from the date of measurement in the manner required by the Site Engineer then in any such event the measurements taken by the Site Engineer or by the subordinate deputed by him as the case may be is final and binding on the contractor and the contractor shall have no right to dispute thesame.

#### 33. PAYMENTS

All bills shall be prepared by the contractor in the form prescribed by the Employer/CONSULTANTS.

The final bill shall be submitted by the contractor within Fifteen days of the date fixed for completion of the work or of the date of certificate of completion furnished by the Site Engineer and payment shall be made within three months.

#### FINAL PAYMENT

al Dirico

The final bill shall be accompanied by a certificate of completion from the Employer/CONSULTANTS. Payments of final bill shall be made after deduction of Retention Money as specified in Clause 12 of these conditions, which sum shall be refunded after the completion of the defects liability Period after receiving the Employer's/CONSULTANTS' certificate that the contractor has rectified all defects to the satisfaction of the Employer/

CONSULTANTS. The acceptance of payment of the final bill by the contractor would indicate that he will have no further claim in respect of the work executed.

#### 34. VARIATION /DEVIATION

The price of all such additional items/non-tendered items will be worked out on the basis of rates quoted for similar items in the contract wherever existing or on engineering rate analysis based on prevalent fair price of labour, material and other components as required. The tender rates shall hold good for any increase or decrease in the tendered quantities upto variations of 25%. For variation beyond +/- 25%, then rate for the respective item may be reviewed on mutually agreed terms.

#### 35. SUBSTITUTION

Should the contractor desire to substitute any materials and workmanship, he/they must obtain the approval of the Employer/CONSULTANTS in writing for any such substitution well in advance. Materials designated in this specification indefinitely by such term as "Equal" or "Other approved" etc., specific approval of the Employer/CONSULTANTS has been obtained in writing.

# 36. PREPARATION OF WORKS FOR OCCUPATION AND USE ON COMPLETION

The whole of the work will be thoroughly inspected by the contractor and deficiencies and defects put right. On completion of such inspection the contractor shall inform the Employer that he has completed the work and it is ready for inspection.

On completion the contractor shall clean all windows and doors including the cleaning and oiling if necessary, of all hardware, inside and outside, all floors, staircases and every part of the building. He will leave the entire building neat and clean and ready for immediate occupation and to the satisfaction of the bank.

#### 37. CLEARING SITE ONCOMPLETION

On completion of the works the contractor shall clear away and remove from the site all constructional plant, surplus materials, rubbish and temporary works of every kind and leave the whole of the site and the works clean and in a workmanlike condition to the satisfaction of the Employer/ CONSULTANTS.

#### 38. DEFECTS AFTER COMPLETION

इंडियन चैक Aladian Bank

The Contractor shall make good at his own cost and to the satisfaction of the Employer all defects, shrinkage, settlements or other faults, which may appear within Six months after completion of the work. In default the Employer may employ and pay other persons to amend and make good such damages, losses and expenses consequent thereon or incidental thereto shall be made good and borne by the contractor and such damages, loss and expenses shall be recoverable from him by the Employer or may be deducted by the employer, in lieu of such amending and making good by the contractor, deduct from any money due to the contractor a sum equivalent to the cost of amending such work and in the event of the amount retained being insufficient, recover that balance from the contractor from the amount retained under Clause No 12 together with any expenses the Employer may have incurred in connection therewith.

#### 39. CONCEALED WORK

The Contractor shall give due notice to the Employer/CONSULTANTS whenever any work is to be buried in the earth, concrete or in the bodies of walls or otherwise becoming inaccessible later on, in order that the work may be inspected and correct dimensions taken before such burial, in default whereof the same shall at the opinion of the Employer/Architect be either opened up for measurement at the contractor's expense or no payment may be made for such materials. Should any dispute or differences arise after the execution of any work as to measurements etc., or other matters which cannot be conveniently tested or checked, the notes of the Employer/CONSULTANTS shall be accepted as correct and binding on the contractor.

#### 40. ESCALATION

The rate quoted shall be firm throughout the tenure of the contract (including extension of time, if any, granted) and will not be subject to any fluctuation due to increase in cost of materials, labour, sales tax, octroi etc., unless specifically provided in these documents.

#### 41. IDLE LABOUR

Whatever the reasons may be, no claim for idle labour, additional establishment cost of hire and labour charges of tools and plants would be entertained under any circumstances.

#### 42. SUSPENSION

इंडियन चैक Ølndian Sank । इलाहाबाद क्र ALL HindEAC

Bhagal?

If the contactor except on account of any legal restraint upon the Employer preventing the continuance of the work in the opinion of the Employer shall neglect or fail to proceed with due diligence in the performance of his part of the contract or if he shall more than once make default, the Employer shall have the power to give notice in writing to the contractor requiring the work be proceeded within a reasonable manner and with reasonable dispatch, such notice purport to be a notice under this clause.

After such notice shall have been given the contractor shall not be at liberty to remove from the site of the works or from any ground contiguous thereto any plant or materials to subsist from the date of such notice being given until the notice shall have been complied with. If the contractor shall fail for 7 (Seven) days after such notice has been given to proceed with the works as therein prescribed, the Employer may proceed as provided in clause 43 (Termination of Contract by Employee).

#### 43. TERMINATION OF CONTRACT BY EMPLOYER

If the contractor being a company go into liquidation whether voluntarily or compulsory or being an firm shall be dissolved or being an individual shall be adjudicated insolvent or shall make an assignment or a composition for the benefit of the greater part, in number of amount of his creditors or shall enter into a Deed or arrangement with his creditors, or if the Official Assignee in insolvency, or the Receiver of the contractor in insolvency, shall repudiate the contract, or if a Receiver of the contractor's firm appointed by the court shall be unable, within 14 days after notice to him requiring him to do so, to show to the reasonable satisfaction of the Employer that he is able to carry out and fulfill the contract, and if so required by the employer to give reasonable security therefore, or if thecontractor shall suffer execution to be issued, or shall suffer any payment under this contract to be attached by or on behalf of and of the creditors of the contractor, or shall assign, charge or encumber this contract or any payments due or which may become due to the contractor, there under, or shall neglect or fail to observe and perform all or any of the acts matters of things by this contract, to be observed and performed by the contractor within seven days after the notice shall have been given to the contactor in manner hereinafter mentioned requiring the contractor to observe perform the same or shall use improper materials or workmanship in carrying on the works, or shall in the opinion of the employer not exercise such due diligence and make such due progress as would enable thework.

To be completed within due time agreed upon, and shall fail to proceed to the satisfaction of the employer after seven days notice requiring the contractor so to do shall have been given to the contractor as hereinafter mentioned or shall abandon the contract, then and in any of the said cases, the bank may not withstanding previous waiver determine the contract by a notice in writing to the effect as hereinafter mentioned but without thereby effecting the powers of the employer of the obligations and liabilities of the contractor the whole of which shall continue in force as fully as if the contract, had not been so determined and as if the works subsequently executed had been executed by or on behalf of the contractor (without thereby creating any trust in favor of the contractor) further the employer or his agent, or servants, may enter upon and take possession of the work and all plants, tools, scaffolding, sheds, machinery, steam and other power, utensils and materials lying upon premises or the adjoining lands or roads and sell the same as his own property or may employ the same by means of his own servants and workmen in carrying on and completing the works or by employing any other contractors or other persons or person to complete the works, and the contractor shall not in any way interrupt or do any act, matter of thing or prevent or hinder such other contractors or other persons or person to complete the works, and the contractor shall not in any way interrupt or do any act, matter of thing to prevent or hinder such other contractors or other persons or person employed from completing and finishing or using the materials and plants for the works when shall be completed, or as soon thereafter as conveniently may be, the employer shall give notice in writing to the contractor to remove his surplus materials and plants and should the contractor fail to do so within a period of 14 days after receipt by him the employer may sell the same by Public Auction and shall give credit to the contractor for the amount so realized. Any expenses or losses incurred by the employer in getting the works earned out by other contractors shall be adjusted against the amount payable to the contractor by way of selling his tools and plants or due on account of work carried out by the contractor prior to engaging other contractors or against the SecurityDeposit.

#### 44. ARBITRATION

All disputes or differences of any kind whatsoever which shall at any time arise between the parties hereto touching or concerning the works or the execution or maintenance thereof of this contract or the rights touching or concerning the works or the execution of maintenance thereof of this contract or the construction remaining operation or effect thereof or to the rights or liabilities of the parties or arising out of or in relation thereto whether during or after determination foreclosure or branch of the contract (other than those in respect of which the decision of any person is by the contract expressed to be final and binding) shall after written notice by either party to the contract to the other of them and to the Employer hereinafter mentioned be referred for adjudication to a sole arbitrator to be appointed as hereinafterprovided.

For the purpose of appointing the sole Arbitrator referred to above, the Employer will send within thirty days of receipt of the notice, to the contractor a panel of three names of persons who shall be presently unconnected with the organization for which the work is executed.

The contractor shall on receipt of the names as aforesaid. Select any one of the persons name to be appointed as a sole Arbitrator and communicate his name to the Employer within thirty days of receipt of the names. The Employer shall thereupon without any delay appoint the said person of the Sole Arbitrator. If the contractor fails to communicate such selection as provided above within the period specified, the component authority shall make the selection and appoint the selected person as the SuleArbitrator.

person as the Stried Arbitrator.

If the Employer fails to send to the contractor the panel of three names as aforesaid within the period specified, the contractor shall send to the Employer a panel of three names of persons who shall all be unconnected with either party. The Employer shall on receipt of the named as aforesaid select any one of the persons names and appoint him as the Sole Arbitrator. If the Employer fails to select the person and appoint him as the Sole Arbitrator within 30 days of receipt of the panel and inform the contractor accordingly, the Contractor shall be entitled to appoint one of the persons from the panel as the Sole Arbitrator and communicate his name to the Employer.

If the Arbitrator so appointed is unable or unwilling to act or resigns his appointment or vacates his office due to any reason whatsoever another Sole Arbitrator shall be appointed asaforesaid.

The work under the control shall, however, continue during the arbitration proceedings and no payment due or payable to the contractor shall be withheld on account of such proceedings.

The Arbitrator shall be deemed to have entered on the reference on the date he issued notice to both the parties fixing the date of the first hearing.

The Arbitrator may from time to time, with the consent of the parties, enlarge the time for making and publishing the award.

The Arbitrator shall give a separate award in respect of each dispute or difference referred to him. The Arbitrator shall decide each dispute in accordance with the terms of the contract and give a reasoned award. The venue of arbitration shall be such place as may be fixed by the Arbitrator in his solediscretion.

The fees, if any, of the Arbitrator shall, if required to be paid before the award is made and published, be paid half and half by each of the parties. The cost of the reference and of the award including the fees, if any, of the Arbitrator who may direct to and by whom and in what manner. Such costs or any part thereof shall be paid and may fix or settle and amount of costs to be so paid.

The award of the Arbitrator shall be final and binding on both the parties.

Subject to aforesaid the provisions of the Arbitrator Act 1940 or any statutory modifications or reenactment thereof and the rules made there under, and for the time being in force, shall apply to the arbitration proceedings under this clause.

The Employer and the contractor hereby also agree that Arbitration under clause shall be a condition precedent to any right to action under the contract with regard to the matters hereby expressly agreed to be so referred to arbitration.

I/We hereby declare that I/We read and understood the above terms and conditions and that we shall abide them if the works is awarded to us.



#### SPECIAL CONDITIONS

(In addition to General Conditions of Contract from Employer)

Name of the Employer: Asst. Gen. Manager, at Indian Bank, Zonal Office

BHAGALPUR

Name of work

: Tender for Interior furnishing works of IndianBank TARAPUR

**BRANCH** 

Name of the Architect

: M/s ARTCON DESIGN CONSTULTANTS

Engineers& Consulting Engineers,

G-04, Laxmi Palace, Mitra Compound, Boring Road, Patna-800001

- 1. The Tenders shall study the following "Special conditions" of the Contract, which are in addition to the foregoing General Condition from the employers and these conditions from the employers and these conditions along with Tender Drawings, specifications, BOQ etc., shall from part of the Tender Document. As such the tenderers are advised to study the same carefully.
- 2. The Special Conditions of the Contract shall supersede the conditions in contradiction to the same in the General conditions of the Contract or any other terms and conditions.
- 3. The tenders are not allowed to alter or change either the specifications or unit of schedule at the time of quoting. Incomplete tenders, conditional tenders etc., will berejected.
- 4. Since the execution of work has to be carried out during office hours, the tenderers are expected to carry out the work with minimum disturbance to officestaff.
- 5. The contractor is allowed to work during night hours and Sunday and holidays after taking specific written permission of the authorities without extra cost toowner.
- 6. Any cutting or damages to the floors, walls and ceiling shall be made good by the Contractor as directed by the Architect/Employer at the contractorcost.
  - 7. The Contractor is expected that the minimum amount of cutting/drilling shall be done to fix the screws to the walls, ceiling and floorsetc.
  - 8. The Contractor shall make his own arrangements for accommodation of workers arranged for the work.
  - 9. The Interior Decoration items should suit site dimensions.
- 10. Bidders while submitting the tender should have actually inspected the site and the value of the work have been examined fully before tendering and the tender is based on such examination.

- 11. The quantities mentioned in the schedule are approximate only and subject to the variations on either side during execution. Any of the items of work, which is not found necessary by Architect/Employer during course of execution of work, shall not be perated.
- 12. All drawings and specifications shall be returned without fail along with the tender. In case of failure to the return the same; the bidder may not be called for quotation for future works of the employer.
- 13. The Contractor shall quote for the best materials and workmanship available and whether ambiguity in specifications and drawings, the same shall be got clarified from the Architect/Employer before proceeding with thework.
- 14. If insisted on, the Contractor shall produce test certificate to the Architect/Employer for the quality of materials concerned. No-delay/Claim on this account will beentertained.
- 15. Normally all the materials are to be supplied by the Contractor for the above work, except otherwise mentioned, but if the Owner's desire to supply any material to maintain quality of work, the contractor has to accept it and only labour payment will be made as per standard norms of employer.
- 16. The contractor shall have sufficient allowance in their rates quoted to allow for minor modification in design and finishes as required by Architect/Employer during execution of work.
- 17. The Employer reserves the right to accept or reject in part of whole of any of the Tenders without assigning any reasons therein and conduct negotiations in the manner considered suitable in order to secure clarifications or better terms from the Tenders.
- 18. The Contractor shall be solely responsible in case of any accidents to his workers in course of carrying out thework.
- 19. The contractors are not entitled for any escalation in the prices of materials, labour etc., on any account during the course of the work. The tendered and accepted rates for all items shall be kept valid throughout the period of contract and completing of thesame.
- 20. The Contractors shall abide by all rules, regulations, and statutes imposed by the Government or other concerned authorities. He shall be responsible for workmen's compensation and the other requirements for housing or any other amenities and site facilities, such as water, power required by the contractors crew and shall provide them at his own cost and risk. Any causality or damage caused by any untoward incident during the execution of work shall be at the entire risk and cost of contractor.
- 21. If clerk of works is appointed at the site by the Architect, the Contractors shall afford him-all facilities for examining the work and materials and recordingmeasurements.
- 22. Other agencies will be working in the project during the work. The contractors must allow these contractors to use the scaffolding and water and render them general assistance. No extension to the completion time will be allowed on this account unless special delays caused by otheragencies.



- 23. The Contractors shall set out the works for CONSULTANTS approval and during the progress of the work shall amend at his means the contractors' cost, any errors arising from inaccurate setting out, unless the architect shall decide to the contrary.
- 24. The Contractor shall not, without the written consent of the Architect/Employer, assign this Agreement or sub-let any portion of theworks.
- 25. The Contractors shall be responsible for all structural and decorative damages to the property and for injury caused by the works or workmen to persons, animals, or things and shall hold the Employer harmless in respect thereof. They shall also be responsible for all damages caused to the buildings, subject to this contract, by inclemency of weather, and shall reinstate all damages caused by the same and thoroughly rectify thedamages.
- 26. Employer shall have the right to inspect/supervise the subject work during interior decoration/modification and suggest changes/ alterations/replacements, wherever the work is not as per approved drawing/plan/samples. Employer accepts no responsibility for the costs involved for suchwork.
- 27. The Contractor shall carryout the work as per the detailed drawings furnished by the Architect/Employer from time to time. The drawings enclosed with the tender documents are for tender purpose only and not for execution and detailed drawings will be furnished during the execution of work. Contractor quoted rate is deemed to include for thesame.
- 28. The work will have to be carried out strictly in accordance with specifications and drawings and also as per Architect's instructions. Any deviations from the same will be at the contractor's risk.
- 29. Applicable income tax, work contract tax, Sales Tax. etc., and GST as per statuary rules and regulations prevailing shall be deducted from running account and final bill of the contractor. All statutory taxes/levis as per prevailing government regulations will be deducted at source from the bill Viz. Sales tax on works contractetc.,
- 30. Bidders shall make their own arrangement for all tools and plants, labour etc., required for the execution of the work. No delay/claim in this account will beentertained.
- 31. The Contractor should note that only after the certificate obtained from employer of each item of work, completely in accordance with the specifications and directions given by Employer/Architect the payment of bill would be made in <a href="Three R.A.">Three R.A.</a>, bills including Final R.A. Bill.
- 32. All the materials required and supplied for the works under this contract shall confirm to Indian Standard Specifications where such materials are used and available for all the items the same shall be provided as approved by the CONSULTANTS/Employer.
- 33. All the materials brought to the site shall be stored at Contractor's risk only and the Employer will not be responsible for any theft, pilferage, damage due to any accident etc. owners will not be liable for any claims in this regard until the work are finished and handed over to entire satisfaction of Owner.
- 34. The Contractor should get the approval of Employer/CONSULTANTS of all materials and fixtures and fittings before using on thework.



- 35. The rates for all extra items not covered in the original schedule shall be worked out on cost of materials + Labour +work contract tax + 15% Margin for the contractor's basis only. No subcontracting rates will be taken into account. Rates for extra items, which are connected in the original schedule, shall be derived from the rates quoted in the original tender. As such all-additional items of work that become necessary during the course of execution will have to be got approved by the Architect /Engineer beforeexecution.
- 36. After completion of the work, the contractors shall promptly remove his materials and other equipments and clear the site of the debris andrubbish.
- 37. All the correspondence in regarding to any approval and Technical matters to be made to the Asst. Gen. Manager, Indian Bank, Zonal Office BHAGALPUR, Indian Bank, Zonal Office BHAGALPUR, Devdoot Complex, Radha Rani sinha Road, Ghanta Ghar, BHAGALPUR, Bihar: 812001 Bihar Contractor has to make all arrangements of diverting all existing open and concealed wiring suitably as per the directive of Architect/Employer.
- 39. Before constructing dismantling the walls, the existing doors. If any has to be removed without making any damage and to be stored/fixed as per the directive or Employer / Architect at no extra cost.
- 40. No mobilization advance will be paid to contractors by employers.

  Value of work to be taken for issue of <u>Interim Certificate</u> for payment is not less than <u>Rs.5,00,000 /- for each R.A. Bill.</u>
- 42. Refund of Retention Money: 100% of security deposit after completion of defect liability period.
- 43. Defects Liability Period: <u>Twelve months after date of award of final completion certificate of work.</u>
- 44. Quantities mentioned are approximate and payment shall be made on actual measurements.
- 45. The rate of partitions and wall cladding shall include necessary additional framework supports wherever required to suit the site conditions or stability of the frames. Decision of Architect in this regard shall befinal.
- 46. Rate for doors will include provision of hardware like hinges, locks, handles, tower bolts, doorstoppers, automatic door closers etc. of approved design and make.
- 47. Rates for hardware to include supplying and fixing of necessary matching screws (brass or powder coated).
- 48. The rates for provisions of furniture shall include for placing the required furniture in position and protecting from damage until handed over to employer.
- 49. The rates for all painting and polishing works shall include all preparation of surfaces, sandpapering or rubbing down before each coat, all brushes and cleaning materials.
- 50. After completion of the work the site shall be cleared from all waste, rubble, left over materials etc. and thoroughly cleaned ensuring that all laminates, floorings, walls, furniture surfaces and tops etc. are spotless clean.
- 51. All movable interior items shall be covered with teak wood beading with regard to 8/19m BWR plywood surfaces exposed to floor.
- 52. The veneer, Teak wood/Sal wood surfaces will be finished with melamine polish.



53. The Civil contractor is responsible for preparation of openings of Electrical works and other allied works viz., LAN, Telephone, Fire Detection, Fire Alarm etc., and neatly covering the openings after the Electrical items and other allied items viz., Lan, Telephone, Fire Detection, Fire Alarm etc., are fixed at the earliest in such a way that the progress of Electrical works and other allied works viz., LAN, Telephone, Fire Detection, Fire Alarm etc., is not affected.

54. The Civil contractor should have a qualified supervisor who will be able to study the bill of quantities and drawings and having working knowledge of implementing the same with minimum 3 yrs experience to receive instructions from Architect / employer and implement the same at site and will be available at site of work from 9.00 A.M. to6.00P.M.



#### SAFETY CODE

#### Scaffolds

- Suitable scaffolds shall be provided for workmen for all works that cannot safely be done from the ground, or form solid construction except in the case of short duration work, which can be done safely from ladders. When a ladder is used, it shall be of rigid construction made either of good quality wood or steel. The steps shall have a minimum width of 450 mm and a maximum rise of 300 mm. Suitable hand holes of good quality wood or steel shall be provided and the ladder shall be given an inclination not steeper than  $\frac{1}{2}$  to 1 (1/4horizontal and 1vertical).
- ii) Scaffoldings or staging more than 4 m. above the ground floor, swung or suspended from an overhead support or erected with stationary support shall have a guard rail properly bolted, braced or otherwise secured at least 1 m above the floor or platform of such scaffolding or staging and extending along the entire length of the outside and ends thereof with only such openings as may be necessary for the delivery of materials. Such scaffolding or staging shall be so fastened as to prevent it from swaying from the building or structure.
- iii) Working platforms, gangways and stairways shall be so constructed that they do not sag unduly or unequally and if the height of the platform, gangway or stairway is more than 4 m. above ground level or floor level, they shall be closely boarded and shall have adequate width and be suitably fenced as described in (ii)above.
- iv) Every opening in the floor of a building or in a working platform shall be provided with suitable means to prevent the fall of persons or materials by providing suitable fencing or railing whose minimum height shall be 1m.

Wherever there are open excavations in ground, they shall be fenced off by suitable railing and danger signals installed at night so as to prevent persons slipping into the excavations.

- v) Safe means of access shall be provided to all working places. Every ladder shall be securely fixed. No portable single ladder shall be over 9 m. in length while the width between side rails in rung ladder shall no case be less than 290 mm. for ladder upto and including 3 m. in length. For longer ladders this width shall be increased at least 20 mm. for each additional meter oflength.
- vi) A sketch of the ladders and scaffolds proposed to be used shall be prepared and approval of the Engineer obtained prior toconstruction.

  Other Safety Measures
- vii) All personal of the contractor working within the plant site shall be provided with safety helmets. All welders shall wear welding goggles while doing welding work and all metal workers shall be provided with safety gloves. Persons employed on metal cutting and grinding shall wear safetyglasses.
- viii) Adequate precautions shall be taken to prevent danger from electrical equipment. No materials on any of the sites of work shall be so stacked or placed as to cause danger or inconvenience to any person or thepublic.



#### **Excavation & Trenching**

- (ix) All trenches, 1.25 m. or more in depth shall at all times be supplied with at least one ladder for each 30 m. in length or fraction thereof. The ladder shall be extended from bottoms of the trench to at least 1 m above the surface of the ground.
- x) The contractor shall take all measures on the site of the work to protect the public from accidents and shall be bound to bear the expenses of defense of every suit, action or other proceedings at law that may be brought by any persons for injury sustained owing to neglect of the above precautions and to pay any such persons or which may with the consent of the contractor, be paid to compromise any claim by any such person.

#### Demolition

Before any demolition works is commenced and also during the process of thework.

- a) All roads open areas adjacent to the work site shall either be closed or suitably protected.
- b) No electric cable or apparatus, which is liable to be a source of danger over a cable or apparatus used by the operator, shall remain electrically charged.
  - e) All practical steps shall be taken to prevent danger to persons employed from the risk of fire or explosion or flooding. No floor, roof or other part of the building shall be so over-loaded with debris or materials as to render it unsafe.

### **Personal Safety Equipments**

- i) All necessary personal safety equipment as considered adequate by the Engineer should be kept available for the use of the person employed on the site and maintained in a condition suitable for immediate use, and the contractor should take adequate steps to ensure proper use of equipment by those concerned.
- a) Those engaged in white washing and mixing or stacking of cement bags or any materials, which are injurious to the eyes, shall be provided with protectivegoggles.
- b) Those engaged in welding works shall be provided with welder's protective eyesightlids.
- c) Stone breakers shall be provided with protective goggles and protective clothing and seated at sufficiently safeintervals.
- d) The contractor shall not employ men below the age of 18 years and women on the work of painting with products containing lead in any form. Wherever men above the age of 18 years are employed on the work of lead painting the following precautions should betaken.
  - i) No paint containing lead or lead products shall be used except in the form of paste or ready-madepaint.
  - ii) Suitable face masks should be supplied for use by the workers when paint is applied in the form of spray or a surface having lead paint dry rubbed andscrapped.

Overalls shall be supplied by the contractor to the workmen and adequate facilities shall be provided to enable the working painters to wash during the cessation of work.

Shall be prospered to the state of the state

- iv) When the work is done near any public place where there is risk of drowning all necessary equipments should be provided and kept ready for use and all necessary steps taken for prompt rescue of any person in danger and adequate provision should be made—for prompt first aid treatment of all injuries likely to be sustained during the course of the work.
- v) Motors, gearing, transmissions, electronic wiring and other dangerous parts of hoisting appliances should be provided with efficient safeguards, hoisting appliances should be provided with such means as well reduce to the minimum of the risk of any part of a suspended load becoming accidentally displaced. When workers are employed on electrical installations which are already energized, insulating mats, wearing apparel, such as gloves, sleeves and boots as may be necessary, should provided. The workers should not wear any rings, watches and carry keys or other materials, which are good conductors of electrically.
- vi) All scaffoldings, ladders and other safety devices mentioned or described here in shall be maintained in safe condition and no scaffold, ladder or equipment shall be altered or removed while it is inuse.

Adequate washing facilities should be provided at or near places of work.

- vi) These safety provisions should be brought to the notice of all concerned by display on a notice board at a prominent place at work spot. The person responsible for compliance of the safety code shall be named therein by the contractor.
- vii) To ensure effective enforcement of the rules and regulations relating to safety precautions the arrangement made by the contractor shall be open to inspection by the Labour Officer, Engineers of the Department of their representatives.
- ix) Notwithstanding the above clause from (i) to (ix) there is nothing in these to exempt the contractor from the operations of any other Act or Rule in force in the Republic ofIndia.

At every work place there shall be maintained in readily accessible place first aid appliance including an adequate supply of sterilized dressings and sterilized cotton wool.



#### **SPECIFICATIONS**

- 1). These specifications are for the work to be done, items to be supplied and materials to be used in the works as shown and defined on the drawings and described here in all under the supervision and to the satisfaction of the Architect/Employer.
- 2). The workmanship is to the best available and of a high standard, use must be made of 'Specialist' tradesman in all aspects of the work and allowance must in the rates for doingso.
- 3). The materials and items to be provided by the contractor shall be the best of their respective kinds and as approved by the Architect/Employer in accordance with the samples which may be submitted for approval and generally in accordance with thespecifications.
- 4). Samples of all materials including those specified by name of the manufacturer or the brands, trades name or by the reference to catalogue Nos. are to be submitted to the Architect/Employer for their approval before the contractor either orders delivers in the bulk tosite.
- 5). Samples together with their packing are to be provided by the contractor free of any charge and should any materials are rejected, the same will be removed from the site at the expense of the contractor.
- 6). The contractor is also required to submit specimen finishes of all colors, fabrics, polish shades etc., for approval of the Architect/Employer before proceeding with suchworks.
- 7). The contractor shall produce all invoices, vouchers or receipts account of all purchases done by him for materials if called upon to do so either by Architect or the Employer.
- 8). The contractor should verify all measurements given in the drawings at the site before commencing the work. Any difference should be clarified with the Architect/ Employer before commencing thework.
- 9). It should be necessary to prepare shop drawings, the contractor at his own expense prepare and submit at least four sets of such drawings to Architect/Employer forapproval.
- 10). Partition line out shall be done at the site before starting the work and got approved from the Architect/Employer.
- 11). Workmanship for Joinery: Timbers are to be cut to required size and length and the joinery should start immediately after the line out is finalized. It should be framed up (but not bonded) and stored until required for fixing in position. At this stage it should be bonded and wedged up. Any portion that wraps or develops shakes or other defects shall be replaced before wedging. Thewhole



work is to be framed and finished in a proper line or level and as detailed in the drawings and fitted with all necessary metal ties, straps bolts, screws.

Twinning bonded joints are to be cross-tongued with teak tongues.

- 12). The contract surfaces of dowels, tendons, wedges etc., shall be glued with proper adhesive. Where ever joinery and carpentry works is likely to come in contract with moisture the adhesive shall bewaterproof.
- 13). The contract shall be responsible for providing and maintaining temporary coverage required for the protection of dressed, finished or semi-finished works if leftunprotected.
- 14). <u>Plywood:</u>Plywood shall be of phenol formaldehyde bonded /commercial ply wood of approved type, make, brand etc. Thickness of plywood shall be as per details given in the drawings/ specifications.
- 15). <u>Block Board:</u>Block board shall be of phenol formal dehyde bonded/BWR of approved type, make, and brand etc., Thickness of Block board shall be as per details given in drawings/specifications.
- 16). <u>Timher:</u>Hardwood or Teakwood shall be the best wood locally available and should be well & properly seasoned of mature growth free from worm holes, large loose or dead knots or other defects through improper handling.

Teakwood to be of good quality, free from soft heart, worm & bee holes and other defects.

All wrought timber is to be sawn, planned or works to correct sizes and shapes as shown in the drawings. An allowance of 2 mm shall be permitted for each wrought face.

All wooden members shall be liberally coated and treated with anti-termite paint before fixing.

17). <u>Laminate:</u>Laminate sheeting shall be of specified thickness, make and either plain, sued, satin or with design finish and samples showing the surface texture and pattern are to be submitted in proper sizes for approval beforeuse.

The laminates shall be fixed with proper adhesive of approved grade and brand.

18. Glass &Glazing: The glass used for glazing shall be plain, complying with IS: 3548 unless otherwisespecified.

The glass shall be free from any defects such as bubbles, undulations, waves and cracks etc.

19. <u>Hardware:</u>shall be of approved make and quality samples of each and every hardware item should be submitted and got approved before using. This hardware shall generally confirm to following or as desired by Architect/Employer.

Butt Hinges: Shall be either brass oxidized or power coated aluminum with pins and washers heavy dutytype.

Mertise Locks: Sixlever. कार्या कार्या है जान वेस कार्याओं Bank इसानवाद कार्याओं HABAU Tower bolts: Brass oxidized or powder coated aluminum.

20. <u>Painting & Polishing:</u>All materials required for this work shall be of specified and approved manufacturer, delivered to the site in manufacturers containers with seals etc. unbroken and clearly marked with manufacturers name of trademark with a description of the contents and color. All materials to be stored at thesite.

All brushes, tools, pots, kettles etc., used in carrying out the work shall be clean and free foreign matter.

Surfaces of the new woodwork, which are to be painted, are to be rubbed down, knotted and topped to the approval of Architect/ Employer. Surface of previously painted wood work which are to be repainted shall be cleaned with soap solution of approve solvent to remove dirt, grease etc., Whilst wet the surface shall be flatted down with suitable abrasive and then rinsed down and allowed to dry. Minor area of defective paint shall be removed by scrapping back to a firm edge and the exposed surface touched in with premier as described and topped with putty. Where the wood mark has been previously painted for polished and it to be newly polished, the same shall be prepared with scrapping, burning off or rubbing down. Surfaces of previously painted metal surface which are to be repainted shall be cleaned, flatted down and any rust and loose scale shall be removed completely by chipping, scrapping and wire brushing back to bare metal and touched in with primer as directed by the Architect/ Employer.

21. <u>Aluminum Sections:</u> Aluminum services shall be factory extruded out of aluminum ingots with smooth finish without any defects like pore, roughness etc., and shall be accurate in size, shape and weightetc.,

The aluminum-extruded sections shall generally confirm to dimensions given in the drawings and specifications, correspondingly ensuring the minimum weight structure as specified in manufacturecatalogue.

An allowance of 5% may be allowed for the dimensions of Aluminum sections at discretion of the Architect/Employer.

- 22. Teakwood bending of 18 X 6 mm size/decorative of various sizes should be melamine polished at places as desired by Architect/Employer.
- 23. Teakwood members should be painted/melamine polished as directed by Architect / Employer.
- 24. Each drawer should have two drawer slides of desired length, one 100 mm handle and one lock of approved make at places as desired and as directed by Architect/Employer.



- 25. Each shutter should have two auto close Hinges, one 100 mm along handle and one lock etc., of approved make at places as desired and as directed by Architect/Employer.
- 26. All exposed edges of 18 mm/12 mm thick particle board/plywood should be covered with 1 8 X 6 mm/12 X 6 mm thick Teak wood beading/ laminate at places as desired and as directed by Architect /Employer.
- 27. Each shutter should have two brass hinges (75 mm long), two brass ball catches, 2 brass tower bolts (75 mm long), and one lock of approved make at places as desired and as directed by Architect/Employer
- 28. Architect/Employer should approve samples of all materials, fixtures, fittings, etc., prior to fabrication of interior furniture items(Fixed/Movable).
- 29. Each flush/panel door shutter should have 3 aluminum hinges (150 mm long), one mortise lock, automatic door closer of approved make at places as desired and as directed Architect/Employer.
- 30. Each table should have TW foot rest of size 75 mm X 38 mm, CPU Stand wire manager Holes with PVCCover.



## METHOD OF MEASUREMENT

(1)	Synthetic Carpet/PVCFlooring	Sq.mts area - Finished length X finished width (No deduction shall be made for columns cutouts etc. only finished area shall be paid)
(2)	Partitions/Semi-partitions/ Wall/Columncladding	Sq.mts area - one side only. Finished length X Finished height. The finished height of full ht. partition / wall cladding / column cladding shall be taken from floor finish level to slab bottom / false ceiling bottom whichever isapplicable.
(3)	FalseCeiling ·	Sq.mts area - Finished length X finished width (No deduction for light fittings, AC Grills, columns, cutouts etc.,
(4)	Venetian Blinds/Double pleated curtains	Sq.mts area - (one side only) Finished length X finished height of respective item.
(5)	Painting ofwalls	Sq.mts area - furnished length X finished height of wall painted
(6)	DraperyRods	Finished length on front facia (In running metres)
(7)	Sun ControlFilm	Sq.mts area - (one side only) finished length X finished height
(8)	Table Chairs	As per BOQ



Note: The Contractor shall quote for the best of the material as specified above. The contractor shall obtain proper approval from the Bank's Architect before placing order for the specified materials/agencies. In case of non-availability of the any of the approved/specified materials/agencies during the execution of the work, the Bank's Architect may approve suitable equivalent Brand/Agency and his decision shall be final and binding on the contractor and price variation, if any, shall be adjusted accordingly.



### FORM OF TENDER FOR WORKS

To
The Zonal Manager,
Indian Bank,
Zonal Office .
BHAGALPUR.

DearSir,

# SUB: Tender for Interior furnishing works of Indian Bank TARAPUR Branch regarding tender.

Having duly examined the tender documents including the drawings, specifications, designs, schedule of quantities relating to the works specified in the underwritten memorandum and having visited the site of the said work and having acquired all the requisite information relating thereto as affecting this tender; 1/ We hereby offer to execute the works specified therein at the rates specified in the schedule of quantities and in accordance, in all respects with the specifications, designs, drawings and instructions in writing referred to in the conditions, the such conditions of the contract and with such materials as are specified, by and in all other respects in accordance with such conditions in the schedule of quantities and conditions of contract so far as applicable.

Should this tender be accepted, in whole or in part, 1/ We hereby agree (i) to abide by ad fulfill all the terms and provisions of the said conditions of the contract annexed hereto and the conditions of tender so far as applicable or in default thereof to forfeit and pay to <u>Asst. Gen.Manager, Indian Bank, Zonal Office, BHAGALPUR.</u> The sums of money mentioned in the said documents.

A sum of Rs 5000/- is herby forwarded as Earnest Money Deposit in the form of Demand Draft in favour of "Indian Bank, Zonal Office BHAGALPUR".



1/ We agree (i) that should 1/ We fail to commence the work specified in the above mentioned the bank shall without prejudice to any other right or remedy be the liberty be the liberty to forfeit the Earnest Money, otherwise shall be retained by memorandum, (ii) to execute all the works referred to in the tender document upon the terms and conditions contained or referred to therein and to carry out authorized variations as directed by the Architect/Bank and as per said conditions of the contract.

$\Omega$	ır	R	ınl	ce:	re	are	٠.
v	41	படி	ш	\ L	L J	an c	

The names of the Proprietor/Partners/Directors of our firm are:

- 1)
- 2)
- 3)
- 4)
- 5)

Signature of bidder ......with seal, Dated the .......day of



#### ARTICLES OF AGREEMENT

Articles of agreement made this thedayofdayof
Between Asst. Gen. Manager, Indian Bank, Zonal Office. BHAGALPUR. (Here in after called the
Employer') of Onepart.
AND
M/s
having its
Registered Office at
(herein after called 'the contractor') of the other part.
Whereas the Employer is desirous of getting works for Interior furnishing works of Indian Bank TARAPUR Branch done as per Schedule-1 to this agreement and has annexed drawings, bill of quantities and specifications describing the work to be done, which is prepared by M/s Artcon Design Consultants, Architectural Engineer& Consulting Engineer, G-04, Laxmi Palace, Mitra Compund, Boring Road, Patna-823001. (Here in after called "CONSULTANTS") and whereas the said drawings as per Schedule -2 inclusive, the bills of quantities marked in Tender Schedule and the specifications etc., have been signed by or on behalf of the parties hereto; and where as the contractor has agreed to execute upon and subject to the conditions set forth in schedule - 3 hereto attached (herein after referred to as 'the Condition'), the work shown upon the said drawings and described in the said specifications and included in the said bill of quantities for the sum of Rs  (Rupees
)
1) It consideration of the sum of Rs
(Rupees) to be paid at the time and in the manner set forth in the said conditions, the contractor will upon and subject to the said conditions execute and complete the works shown upon the said drawings and described in the said specifications and bill ofquantities.
2) The contractors has deposited Rs(Rupees) with the Employer Security Deposit for performance of this agreement.
NOW IT IS HEREBY MUTUAL AGREED AND DECLARED BETWEEN THE PARTIES HERETO AS FOLLOWS:
<ol> <li>The contractor hereby agrees and undertakes to execute and complete the said works shown in the said drawings and such further detailed drawings as may be furnished to it by the Employer and describes in the said specification and the said schedule of quantities upon and subject to the said conditions.</li> </ol>
2. The Employer shall for such interior works, pay to the contractor such sums as shall become payable at time, in the manner specified in the said documents.

4. The contract herein contained, comprise of the said work above mentioned and all subsidiary works

3. The said tender and allied documents, drawings, specification, prices schedule of quantities, agreement and documents above mentioned, shall be final and binding on both the parties.

connected therewith in the same site may be ordered to be done from time to time by the Employer even though such works may not be shown in the said drawings or describes in the said specificationsor the schedule of quantities. The contractor hereby agrees and undertakes to do and perform all such works in a though and work man like manner. With best materials and within the time limit herein mentioned.

- 5. The employer reserved to himself the right after the drawings and nature of the work and of adding or omitting any item of work or of having portions of the same carried out departmentally or otherwise and such alterations and such alterations or variations shall be carried out without prejudice to this contract.
- 6. The said conditions shall be read and constructed as forming part of this agreement and parties hereto will respectively abide by and submit themselves to the conditions and stipulations and perform the agreements on their parts respectively as such conditions contained.
- 7. It will be the entire responsibility of the contractor to procure all materials required for the said works.
- 8. The contractor shall complete the said works within 15 days from the date of commencement of work as per work order for the work and will remove from the site all plants, scaffoldings, materials, in use rubbish and leave the work site clean within the said period.
- 9. All disputes arising out of or in any way connected with this agreement shall be deemed to have arisen in Madras and only in courts in Calcutta shall have jurisdiction to determine the same.
- 10. The several parts of this contract have been read and fully understood by us.
- 11. The work-order issued to the contractor shall be treated as part of this agreement.

In witness where of the parties hereto have set their respective hands on the day month and year above Written.

Signed and Delivered by The Indian Bank Signed and Delivered by The Contractor

In the Presence of witness

In the Presence of Witness

	BILL OF QUANTITY OF INTERIOR DESIGN AND FURNI TARAPUR BRANC	SHING WO	ORKS FOR	R INDIAN BA	NK, AT
SI. No	DESCRIPTION OF ITEM	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
1	FALSE CEILING				
	Providing, fabricating and erecting in position totally				
l	flushed suspended false celling with 12.0mm thick	ļ		1	
	Gypsum board, fixed to a metal frame work comprising			! .	
	of ceiling channel of size 80mmx26mmx0.5mm @ every	ŀ	1	1 1	
i	457cm centre, inter channel 45mmx15mmx0.9mm @	1		1 !	
1	every 1220 cm centres, peri-meter channel 20mmx26 mm	1	•	1 )	
	all along the wall/partitions, strap hanger suspenders		i		
	25mmx0.5mm with nuts and bolts 6.4mmx12.7mm,			i I	
	connecting clips 2.6mm thick, dry walls screws 25m long.	i	1	1 [	
	soffit cleats 27mmx37mmx25mmx1.6mm thick and dash				
	fastenes / rawl plugs 12.5 mm diax35mm long with 6mm	<b>,</b>		[ ]	
	dia bolts etc. complete with recommended fillers, paper	Į į	į	. l	
	tapes and applying two coats of acrylic emulsion paint	i			
	of approved shade and make over a coat of primer		ľ	1	
	Including making necessary cut outs for light fittings/	<b>!</b> ,			
	ACs etc. complete as per manufacture's specifications,		1		
	(Quantity as per layout plan/site requirement)	[_	ــــــــــــــــــــــــــــــــــــــ	1 1	
╮┤	Alam Washington C Agana Jaka (C-14 Palas C-11)	Sqm.	48	<del>!</del>	
	New Technologies & Materials (Grid False Ceiling)	<u> </u>	<b> </b>	<del>{</del> }	
	Providing & fixing false ceiling at all heights with GRG (Glass Fibre				
	Reinforced Gypsum) false ceiling tiles of Size 595x595 mm of approved texture, design and patterns having moisture content less than 2%.		!	1 1	
	humidity resistance of 99%, NRC 0.50 to 0.75 as per IS 8225:1987, Non				
	combustible as per BS 476 (part-4)-1970 and light reflectance of 85%			i i	
	(minimum) to be laid in true horizontal level suspended on inter-locking				
	metal T-Grid of hot dipped galvanised fron section of 0.33mm thick			i i	
	(galvanized @ 120 grams per sqm including both sides) comprising of			1	
	main-T runners of size 15x32 mm of length 3000 mm, cross - T of size			)	
	15x32 mm of length 1200 mm and secondary intermediate cross-T of size				
	15x32 mm of length 600mm to form grid module of size 600 x 600 mm,			1 [	
	suspended from ceiling using galvanised mild steel items (galvanizing @			1 1	
	80 grams per sqm) i.e. 50 mm long, 8 mm outer diameter M-6 dash				
	fasteners, 6 mm dia fully threaded hanger rod upto 1000 mm length and L-		ı	, l	
	shape level adjuster of size 85x25x2 mm. Galvanised iron perimeter wall			l i	
	angle of size 24x24x0.40 mm of length 3000 mm to be fixed on periphery			!	
	wall / partition with the help of plastic rawl plugs at 450 mm center to				
	center and 40 mm long dry wall SS screws. The work shall be carried out			ł . J	
	as per specifications, drawing and as per directions of Engineer-in-Charge			1	
	With semi perforated 12 mm thick micro tegular edged GRG false ceiling				
	tiles. (Make Diamond ,Design code - 8829)	1		i 1	
	· · · · · · · · · · · · · · · · · · ·				
		Sqm.	44.96	[	
3	WALL PANELING / COLUMN ENCASING :-			<u>-</u>	
-	Supplying and erecting Wall paneling / Column encasing				
	(up to false celling) as per drawing and design and			, l	
	conforming to the following specifications :			] [	
	Basic frame work:			į į	
	Framing shall consist of Heavy duty (finished size) seasoned hardwood				•
	members (hollock / malaysian sal)				
Į	at max. Intervals 50mm x 50mm @ 600mm c/c both ways			ļ l	
	Horizontally and Vertically. The vertical alternate frames				
	to be fixed to the ceiling with necessary fixtures. Vertical			} · 1	
	members shall be sultably anchored at ceiling level to			† I	
	ensure rigidity.				-
	Skin membrane :			j	
[	6 mm thick BWP grade plywood on face.			<u>ll</u>	



	Finishing:  1.0mm thick laminate sheet of same or combination shades with grooves as per instructions.			<del></del> -		7
	Skirting: 100mm high laminate of approved make & shade all as directed.  Top Border: 150mm high laminate of approved make & shade all as					
	directed. Note: Quoted rates shall include all necessary materials,					l
1	accessories and labour and also for making provisions for electrical/telephone/computer wiring, conduits and switch boxes,	<b>}</b>				I
1	etc. where ever required. (quantity/location should be restricted	1				l
1	only to the central pillars in Banking half/to hide electrical pipes/AC drain pipes/any prime location)	}	]	ı		Ì
1	Principles of the state of the		ļ			l
<u> </u>	much a transfer of the second	Sam.	13		<u></u>	l
⁴	Double skin partitions:- Supplying and erecting full height opaque/solld partitions (up to false ceiling/8' height) as per following		}	'		
i	specifications: Basic frame work:				li.	١
	Framing shall consist of Heavy duty finished size) seasoned hardwood	l				l
1	members (hollock / malaysian sal) at max. intervals 50mm x 50mm @ 600mm c/c both ways Horizontally and Vertically. The vertical					ļ
	alternate frames to be fixed to the ceiling with necessary fixtures. Vertical					l
1	members shall be suitably anchored at ceiling level to ensure rigidity. <u>Skin membrane:</u> To be finished with 6mm thick BWP grade plywood					
1	on each face with grooves, as per drawings/instructions.					l
1	Finishing: 1.0mm thick laminate of same or combination shades with grooves in both faces as per instructions.					Ì
	Skirting- 100mm high laminate of approved make & shade all as directed.					l
1	Top Border: 150mm high laminate of approved make & shade all as directed.					l
1	Quoted rates shall include all necessary materials, accessories and					l
1	labour and also to make provisions for electrical / telephone / computer wiring conduits and switch boxes, etc. (Materials for					l
1	wiring, conduits,					l
	switches etc. shall be separately paid for)					
	·	Sqm.	26			
5	Double skin partitions:- Supplying and erecting full height partly glazed/aluminium grill partitions for BM cabin side partition/ cash back					1
	side portion respectively as per following specifications::					
1	Basic frame work: Framing shall consist of Heavy duty (finished size) seasoned hardwood members (hollock / malaysian sal) at max, intervals		Ì	,		١
l	50mm x 50mm @ 600mm c/c both ways Horizontally and					l
ł	Vertically. The vertical alternate frames to be fixed to the celling with necessary fixtures. Vertical members shall be suitably anchored					l
ļ	at ceiling level to ensure rigidity.	l				1
	Exposed frame members in the glazed portions shall have wider spacing (approx. 1200 mm) and be finished with 1.00 mm thick laminate of	i	}			
	same or combination shades, over 6mm BWP PLy.		, <u> </u>			1



	1				
1	Skin membrane: (Opaque portion up to 900mm from floor	Γ –			
1	level and from 2100mm to celling, finished with 6mm		1		
1	thick BWP grade plywood on each face with grooves, as	)	ì	1	ì
	per drawings/ instructions,		1	ı	
[	Finishing: 1.0mm thick laminate of same or combination	Į.	l	Ţ	
	shades with grooves as per instructions.	l	1	ı	
i	Glazing: 8mm thick clear float glass fixed with polished	ľ	İ	[	1 1
1	teak / steam beech wood glazing beads of approved shape (finished 12 x	<b>\</b>	}	}	<u>የ</u>
1	25mm). (for BM cabin side partitions, including acid etching / frosting of	]		l	1 i
İ	approved design ,on the glass)	1	ſ	ŀ	[
1	Al. grill: Readymade anodized aluminium grill of approved design and	ì	)	Ì	)
	quality fixed with continuous teak wood / steam beach beads of approved			Ì	
ļ	shape (finished 35 x25mm) dulypolished by NC lacquer finish, (for Cash	l	Į i	į	ļ ļ
l	Cabin SidePartitions)	ŀ	1	ľ	i
ŀ	SkirtIng- 100mm high laminate of approved make & shade all as directed.		ļ ,		
1	Top Border: 150mm high laminate of approved make &	<b>S</b>		1	
1	shade all as directed.				[
i	Quoted rates shall include all necessary materials,	ļ	1		
]	accessories and labour and also to make provisions for	Ì	]	]	ן ו
l	electrical / telephone / computer wiring condults and	1			
Į.	switch boxes, etc. (Materials for wiring, conduits &	1	ļ ,		ļ
1	switches etc. shall be separately paid for)				
I		i	] ,		
<u></u>		Sqm.	34	L	<u> </u>
-6	Do- as item 5 but with 12mm thick clear float glass up to	]	]		
1	door height (instead of 6mm glass in wooden partition)	l	[		Į Į
I	with 6" bottom rail complete all as directed by the Bank.	l			
	(for BM cabin).	Sqm.	0		
7	Supply and erecting low height opaque partitions (up to maximum	}	\		
	1200mm height) conforming to the following specifications:	I			
1	<u>Basic frame work:</u> Framing shall consist of Heavy duty finished size)		[		]
[	seasoned hardwood members (hollock / malaysian sal) at max. Intervals		j i		· . ]
1	50mm x 50mm @ 600mm c/c both ways Horizontally and	•	]		<b>!</b>
1	Vertically. The vertical alternate frames to be fixed to the celling	(	ļ ļ		(
	with necessary fixtures. Vertical members shall be suitably anchored	1	]		[
ļ .	at ceiling level to ensure rigidity.		] .		
	Skin membrane: 6 mm thick BWP grade ply on each face up to 900mm	ì	}		<u> </u>
	height,		] ,		
[	Glazing: 10mm glass in remaining portion,	l	<u> </u>		
1	Finishing: 1.0-mm thick laminate of same or combination shades with	[			
[ ]	grooves as per instructions.				ļ <b>!</b>
<b>\</b>	Edge moulds: All free top/ end surfaces shall have polished teak / steam	}	}		}
	beech wood moulds of approved shape (from 18 x 50mm sections).				
[	Skirting: 100mm high laminate of approved make & shade all as directed.				<b>!</b>
'	Quoted rates shall include all necessary materials, accessories		]		1
[	and labour and also allow provisions for electrical/				<b> </b>
<b>\</b>	telephone/computer wiring, conduits and switch boxes, etc. (Materials	ļ	! !		ŀ
	for wiring, conduits and switch boxes shall be separately paid for.)		[ .		
[					<b>!</b>
<b>\</b>		]	) i		1
		<b> </b>	,,		
		Sqm	8.5 _	·!	
8	COUNTERS/WORK STATIONS:-				



	<del></del>				
Į	Providing and erecting in position Cash Work Station of approx. size		[		
1	1370x900x750mm (4.5'x3.0'x2.5'), made of 19mm thick block board			ĺ	]
	pasted with 1.00mm laminate Inclusive of a 350mm wide customer	1	!		ľ
	top at 1155 mm level,. Writing top & customer top should be with			ŀ	
1	rounded edges and sides with 1.0mm thick laminate of approved		1	]	
!	shade/make. Both should have sufficient gap in between to	i	!		! !
1	accommodate computer monitor up to full depth. The workstations	<b>\</b>	{	}	}
1	shall be supported from the partition system made of 19mm thick	ŀ	1		
	BWP grade block board finished with 1.00 mm thick laminate of		l	1	
	approved shade/make. Free edges shall have 18 mm thick, polished			ļ	
i	white or steam beach wood moldings of half-round profile as per drawings		<b>i</b> .		1
l	and instructions and 100mm high laminate of approved make & shade all	l	[		l l
ľ	as directed.		ľ		
	Each cash workstation shall comprise of the drawer unit, Tea tray at				1 1
1	top, Cash drawers with approved telescopic channels for drawer-				!
	slides, automatic locks (keys in duplicate), wire managers, space				] [
1					i
1	for computer CPU, modesty panel and other necessary	1			\             \
1	hardware and accessories including satin finish S. S. handles of approved	i			
1	quality. Inner face of cash counter to be provided with 16G, M.S.				
	sheet, painted with two coats of synthetic enamel paint of approved				
	shade & make, over a coat of approved steel primer. Inner faces shall be				
[	painted with two coats of synthetic enamel paint of approved shade &	l I			[ [
	quality over a coat of primer.				
1	Skirting: 100mm high laminate of approved make & shade all as directed.				
		R.M	3.04		1
9	Providing & fixing 12mm thick clear float glass on Cash Counters at front	IR-IVI	3.04		<u> </u>
"					
	& sides, with S S clamps/patch fittings, necessary pollshed beadings etc	i			
	complete all as directed by the Bank.				
	Note: Front glass to be fixed in slanting position towards inside cash			· .	
l	area with required angle as directed. Above glass to be fixed either in	[			Į Į
	two pieces. Lower piece having one semi-circular/rectangle 6"	1			
	dia/long opening at customer top level & other piece to be fixed				
	at suitable height making 3" slit for conversation with customer. In				
	this case, only glass area to be measured for payment purpose.) In				
	case of single piece, one semi-circular/rectangle 6* dia/long				
} '	opening at customer top level & one circular hole of required dia at	\			<b>\</b>
	suitable height for conversation at centre of cash counter to be provided				
		<b>]</b>			]
		Sqm.	6.7		i
10	Providing and fixing in position readymade anodized aluminium grill				
	of approved design and quality fixed with continuous teak wood / steam	1			
	beach beads of approved shape (finished 35 x25mm) duly polished by				<b>i</b>
	NC lacquer finish.	:			
	(to be considered in cash cabin ceiling, if required, as per site requirement)	<b> </b>			
1		<u>'</u>			) . j
	l	Sam.	6.7	l .	



44	Transport of the state of the s				
11	and 750mm high including drawer-cum-cabinet unit for files, space for computer CPU, wire managers, modesty panel, tea tray etc. made with 19mm thick BWP grade block board on top and supporting sides / front with necessary well seasoned Malaysian Sal/ Kail/ Mirandi wood frame work, finished and sides with 1.0 mm thick laminate of approved shade and quality, including providing and fixing 450mm long key board tray of approved shade, hardware and accessories at each of the counter. All exposed edges of block board are to be provided with half round teak wood mouldings, duly polished and 100mm high laminate of approved make & shade all as directed. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.  Skirting: 100mm high laminate of approved make & shade all as directed. Rate to include charges for brass hardware fittings as well as fixtures like				
1	sliding gear for drawers of 'Earl Behari' or equivalent approved make.	1	İ	1	\
		ļ l		ļ	l
	<b>\</b>	ļ ļ		<b> </b>	
	1	<u>[</u>	_	[	
<del>  1</del> 7		R.m.	2.74	<b> </b>	
12	Providing and fixing 1'-6" high, 12mm thick clear float glass railing on	į l	j	[ \	ļ
1	clerical counters with S. S. decorative posts of 50mm dia all as directed by the Bank.	  see	_	ļ l	
<b> </b>	DOORS :-	Sam.		- <del></del> -	
13	Supplying and fixing in position overall 32 mm thick solid core hot	<del>  </del>			<del>                                       </del>
<b>)</b>	pressed phonol formaldehyde bonded flush door finished with 1.0 mm	\ \ \			)
	thick laminate of approved shade and quality on both sides of the door	ļ [			ŀ
}	shutter & beading on edges including cost of hardware fittings e.g.	\ <b>\</b>	ļ		ļ .
	hinges, handles etc. of approved make and quality & making provision of peep hole of suitable size with glass& beading all-round	! [			l
	all asdirected by Architects. (Cash/Store/other doors)	<b>(</b>			ļ
	• • • • • • •	Sqm.	10		
14	Supplying and fixing in position 32 mm thick solid core hot pressed			<u> </u>	<del></del>
	phenol formaldehyde bonded partly glazed flush (8mm thick clear float	( )	Ì		ļ l
	glass fixed) door shutter of approved make finished up to 900 mm	(	Ì		ļ l
)	from floor level with 1.00 mm thick laminate of approved quality on	l i			]
	both sides of the door shutter & beading on edges. The upper portion of the shutter is to be or steam beech wood glazing beads of approved		ĺ		
1	design, complete as per drawing.	\ <b>i</b>	ľ		\ \ \ \ \ \
]	Rate to include cost of hardware fittings e.g. , hinges, handles, etc. of	ļ	İ		
<b>\</b>	approved make and quality. (Manager cabin door &UP5)	\ <b>\</b>			\
]			.		
<u>   </u>	HOPER Demiliary and fular Bendert at the Land Her day he are a 18	Sqm.	4	<u></u>	
	(LOCKS) Providing and fixing "Godrej Night Latch" / "Godrej Mortice Lock" in required places, all complete with fixing, fitting, etc.		i		
(		<u> </u>		ļ i	
<b></b> _	<u> </u>	Each		<b></b>	!
16	(Lyonallie page elaces) a	1			
) 1	(HYDRAULIC DOOR CLOSER) Providing and fixing Hydraulic door closers of specified brand, all complete as per instructions of Architect / Employer.	Each			\ <b>\</b>
فيسسا	specified orang, an complete as per instructions of Architect / Employer.	cacti		لـــــــــــــــــــــــــــــــــــــ	



15 Providing fabricating & Riching is position twin—stille door at Malia Entrance made of well seasoned teak wood of site 100 yS for mor and anotized/powder coated Aluminium sections of required site on frame, top & bottom rail and 12mm thick glass(Mod/) Saint Gobain make) including fibring the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fishly including all incidentals etc complete. Glass to be fixed in the groovers of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & Raining heavy dusty double action hydraulic floor spring (ISI mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/Pototom, bolts, locks & sastin finish stainliess steel decorative tubular handles/approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved stade N.C. lacquer in mat saith finish. The rate should also include cost for decorative techning on the glass.  3) Fixed portion  3) Fixed portion  3) Fixed portion  4) Door  CUBBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  57 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick RWB grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter/aces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) eggle pipings and 100mm high teak wood skirling duly polished/y painted as directed. Inner faces of cabinet including shutters shall be polished in approved shade,  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satula fishets 45. S., handles etc. of approved make. (Payment will be on the area of cabinet face).  Sigm. 2.32  b) Maximum 400mm deep x 750mm high laminate of approved shade & quality over a coast of prinner, Price edges of block board including interme	Errar to inner conservation in the conservatio	Entrance made of well seasoned teak wood of size 100 x 50 mm or anodized/powder coated Aluminium sections of required size on frame, top & bottom rail and 12mm thick glass(Modi/ Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. Sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action or it, and including necessary fixing materials on the lintel/bottom, boits, locks & attin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
anodized/powder coated Aluminium sections of required site on fame, top & biotion rail and 21mm thick glastifoldi's Saint Gebahi make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteness to have proper fixity including all incidentals etc complete, Glass to be fixed in the groows of the tesk wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action bydraulic floor spring (ISI mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, boits, locks & satin finish storiess steel decorative tubour handles/approx.300mm long) on both focas complete as per drawing and instructions. The exposed tesk wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:  17 Providing and erecting in position low/ full helpht Storage cabinet Made of 19 mm thick 3WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick tarrinate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) degle lightings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including interest shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and stalin finished 3.5. Inacles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  3) Maximum 400mm deep x 750mm high mainted of approved shade including intermediate shelves as per drawing/ instructions. Exposed surfaces shall be infished with 100mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic ename	ar to in his constant of the same state of she can be same state of she	anodized/powder coated Aluminium sections of required size on frame, top & bottom rail and 12mm thick glass(Modi/ Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. Sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action includes cost of providing & fixing heavy duty double action and action including necessary fixing materials on the lintel/bottom, boits, locks & actin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
anoduced/powder coated Aluminium sections of required site on fame, top & bottom rall and 12mm thick glastifieddi / Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etc complete. Glass to be fixed in the groows of the tesk wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring (ISI mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, boits, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed tesk wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick tarrinate of same or combination shades as per instructions with polished white or steam beech wood (ferm thick) degle lightings and 100mm high tesk wood skirting duly polished/ painted as directed. Inner faces of cabinet including interest shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. Is analess etc. of approved make. [Payment will be on the area of cabinet face).  Skirting: 100mm high haminate of approved make & shade all as directed.  3) Maximum 400mm deep x 750mm high  Maximum 400mm deep x 750mm, high made of 19mm thick away grade block boards including intermediate shelves as per drawing/ Instructions. Exposed surfaces shall be finished with 100mm laminate of approved shade & quality over a c	ar to in ne co se in hy lnc sa loc ex lac de lac lac de lac lac de lac lac de lac lac de lac lac lac lac lac lac lac lac lac lac	anodized/powder coated Aluminium sections of required size on frame, top & bottom rail and 12mm thick glass(Modi/ Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. Sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action includes cost of providing & fixing heavy duty double action and action including necessary fixing materials on the lintel/bottom, boits, locks & actin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
top & bottom rail and 12mm thick glass(Modif / Saint Gobalin make) including fishing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all indidentals etc complete. Glass to be fixed in the grooves of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring (18 mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & satin finish stainless steel decorative tubular handles(paprox.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion  b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:-  17 Providing and erecting in position low/ full helph Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be filiathed with 1 mm thick faminate of same or combination shades as per instructions with polished white or steam beech wood (form thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and stain finished s.5, handles etc. of approved make. (Payment will be on the area of cabinet nece).  Skirting: 10mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750mm high  Froviding and erecting in position side cabinet units with sbutters of approve shade including internediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm  Immater of approved shade and make, luner faces shall be painted with two coats of synthetic enamel pai	to income consistence in the con	top & bottom rail and 12mm thick glass(Modi/ Saint Gobain make) including fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. Sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action includes cost of providing & fixing heavy duty double action includes cost of providing & fixing heavy duty double action including necessary fixing materials on the lintel/bottom, boits, locks & actin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
including fishing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fishly lockuding all incidentals etc complete. Glass to be fixed in the grooves of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring (ISI mark ) in the floor, fixing the door on it, Including necessary fixing materials on the Intel/Bottom, bolts, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. Iscquer in mat satin finish. The rate should also include cost for decorative tching on the glass.  a) fixed portion  b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDEUNITS-  17 Providing and erecting in position low/ full height Storage cablinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (ferm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including interes shall be painted in approved shade.  Shutters will be bung by auto-closing hinges, locks, magnetic door catcher and satin finished S. 5, handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  9) Maximum 400mm deep x 750mm high  Froviding and erecting in position side cabinet units with shutters of approve dishade and make, Inner faces shall be painted with two coats of synthetic enamel paint of approved shade as paired with two coats of synthetic enamel paint of approved shade as paired with positions. Proved shade and make, Inner faces shall be painted with two coats of synthetic enamel	in ne co se in hy lni sa loi ex lac de lac lac de lac lac de lac lac de lac lac de lac lac lac lac lac lac lac lac lac lac	ncluding fixing the frame to brick wall/RCC/wooden surfaces with necessary fasteners to have proper fixity including all incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action organization of providing a fixing heavy duty double action organization of providing a fixing heavy duty double action organization of providing and action organization of providing necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm ong) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
necessary fasteners to have proper fixity including all incidentals etc complete. Gibas to be fixed in the grows of the teak wood/al. sections with necessary materials/beading etc. The job also includes cost of providing & fixing heavy duty double action hydraulic floor spring (15 mark) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, boils; locks & satin finish stainless steed decorative tubular handles/approx.200mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion  b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (firmt thick) edge lippings and 100mm high teak wood skirling duly polished jamined as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by autoclosing hinges, locks, magnetic door catcher and satia finished \$5, shandles etc. of approved make. (Payment will be on the area of cabinet face).  \$kirling: 100mm high laminate of saproved make & shade all as directed.  3) Maximum 400mm deep x 750mm high made of 19mm thick sWP grade block boards including intermediate shelves as per dawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, prime and approved shade.  Polymer painted as directed. Inner faces shall be painted with two coats of synthetic enamel paint of	a) b) CL 17 Prof sh sp Sh co ste ca wi sk a) b) 18 Pro ap BV Ins tw	necessary fasteners to have proper fixity including all Incidentals etcomplete. Glass to be fixed in the grooves of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring ( ISI mark ) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Fixed portion	Sqm.	+		
complete. Glass to be fixed in the grooves of the teak wood/al. sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy dury double action hydraulic floor spring (151 mark) in the floor, fixing the door on it, including necessary fixing materials on the Intel/bottom, bolts, locks & sath flinish stainless steel decorative tubular handles/approx.200mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. bacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion b) Door Sqm. 6  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  TProviding and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet Including shutters shall be painted in approved shade.  Shutters will be ung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet facu).  Skirting; 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Froviding and erecting in position side cabinet units with shutters of approve size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make, inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, Free edges of block boards shall be finished with upolished with two or steam	se in hy lnc sa loc ex lac de lac de lac lac de lac lac de lac lac de lac lac de lac lac lac lac lac lac lac lac lac lac	complete. Glass to be fixed in the grooves of the teak wood/al, sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action organization by draulic floor spring { ISI mark } in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door	Sqm.	+		
sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring [15] mark ] in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, boits, locks & statin finish stainless steed decorative tubular handles/approva.200mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also Include cost for decorative etching on the glass.  a) Fixed portion Sqm. 6 b) Door Sqm. 6 c) Sqm. 6 c) Sqm. 6 c) Door Sqm. 2.32 c) CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:- c) Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (firm thick) edge lippings and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirling: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32 b) Maximum 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 100mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished whith on steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be p	see in hy local see in hy loca	sections with necessary materials/beading etc. The Job also includes cost of providing & fixing heavy duty double action hydraulic floor spring ( ISI mark ) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, boits, locks & atin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  1) Fixed portion 1) Door 10 Door 11 Door 12 TOPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS: 15 Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: 15 hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm.	+		
includes cost of providing & King heavy duty double action hydraulic floor spring (ISI mark) in the floor, fixing the door on it, including necessary fixing materials on the linter/bottom, bolts, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both facts complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion  5qm. 6  b) Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick lam/nate of same or combination shades as per instructions with polished white or steam beech wood (farm thick) edge lepips; and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirling: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Froviding and erecting in position side cabinet units with shutters of approve size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make, inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of optimer. Free edges of block board shall be finished with polished whith corst can been wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel pa	a) b) CU 17 Pro of sh coo stee of Sh can wi sk a) b) 18 Pro ap ap ap ap at two stee of sh can with sk and sh ap ap ap ap ap ap ap ap ap ap ap ap ap	ncludes cost of providing & fixing heavy duty double action hydraulic floor spring { ISI mark } in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    Fixed portion   Door   TUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-   Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:   hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
hydroulic floor spring { ISI mark.} In the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and Instructions. The exposed teak wood surfaces to be polished in approved shade N.C. bacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion Sam. 6 b) Door Sam. 2.32  CUPBORADS / STORAGE CABINETS / TABLE SIDE UNITS:  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick lam/nate of same or combination shades as a per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly piolished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high haminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sem. 2.32 b) Maximum 400mm deep x 2100 mm high  Sem. 2.32 b) Maximum 400mm deep x 750mm, high made of 19mm thick approved shade and make. Inner faces shall be painted with two coats of synthetic ename paint of approved shade & quality over a coat of primer. Free edges of block boards including intermediates shelves as per drawing/instructions. Exposed surfaces shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic ename paint of approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	hy inc sa loc ex lac de de de de de de de de de de de de de	nydraulic floor spring ( ISI mark ) in the floor, fixing the door on it, including necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm ong) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  In Fixed portion  Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+	·	
Including necessary fishing materials on the lintel/hostiom, boits, locks & satin finish stainless steel decorative tubular handles(approx.300mm long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade NLC lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion Sam. 6 b) Door Sam. 2.32  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  17 Providing and crecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick lam/nate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirling duly polished; planted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing iniges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sam.  18 Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, prace edges of block board shall be finished with polished	a) b) CU 17 Pri sh sp Sh cor ster of Sh cai wi sk a) b) 18 Pri ap BV Ins Ian tw	ncluding necessary fixing materials on the lintel/bottom, bolts, locks & atin finish stainless steel decorative tubular handles(approx.300mm ong) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  I Fixed portion  Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
satin finish stainless steel decorative tubular handles(approx.200mm   long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C. lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.    a)   Fixed portion   Sqm. 6	sa los ex lass de de de de de de de de de de de de de	atin finish stainless steel decorative tubular handles(approx.300mm ong) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  I Fixed portion  Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:  Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
long) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications: Shutter faces shall be finished with 1mm thick taminate of same or combination shades as per instructions with polished white or steam beach wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door carcher and salul finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 750mm high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing/ instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with wo coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with sociats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with sociats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall	loc ex lac de de de de de de de de de de de de de	ong) on both faces complete as per drawing and instructions. The exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  1) Fixed portion 1) Door 1: CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS: 1: Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: 1: hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
exposed teak wood surfaces to be polished in approved shade N.C lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion  5qm. 5qm. 6  b) Door  CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished 5. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 750 mm high and of 19mm thick away grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with so coats of synthetic ename	a) b) CL 17 Pri of sh co stee of Sh cai wi sk a) b)  18 Pri ap ap ap ap tw	exposed teak wood surfaces to be polished in approved shade N.C acquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  1) Fixed portion  1) Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
lacquer in mat satin finish. The rate should also include cost for decorative etching on the glass.  a) Fixed portion b) Door CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:- Providing and erecting in position low/ full helphs Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications: Shutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (form thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be houng by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  ½kirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high and of 19mm thick away and be cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick away grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make, inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with sociats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with sociats of synthetic enamel paint of approved shade & quality over a coat of primer. Pree edges of block board shall be finished with sociats of	lac de de de de de de de de de de de de de	Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
a) Fixed portion b) Door Sqm. 6 CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications: Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face). Skirting: 100mm high laminate of approved make & shade all as directed. a) Maximum 400mm deep x 750 mm high  Sqm. 2.32 b) Maximum 400mm deep x 750 mm high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make, inner faces shall be painted with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with more coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade.	a) b) CL 17 Pri of shi coo stee of Shi car with Sk a) b) 18 Pri ap ap ap at two stee of shi car with sk an ap ap at two stee of shi car with sk an ap ap at two stee of shi car with sk an ap at two sk sk sk an ap at two sk sk sk sk sk sk sk sk sk sk sk sk sk s	Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
a) Fixed portion b) Door Sqm. 6 CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications: Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face). Skirting: 100mm high laminate of approved make & shade all as directed. a) Maximum 400mm deep x 750 mm high  Sqm. 2.32 b) Maximum 400mm deep x 750 mm high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make, inner faces shall be painted with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with more coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coast of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade. Shall be painted in approved shade.	a) b) CL 17 Pri of shi coo stee of Shi car with Sk a) b) 18 Pri ap ap ap at two stee of shi car with sk an ap ap at two stee of shi car with sk an ap ap at two stee of shi car with sk an ap at two sk sk sk an ap at two sk sk sk sk sk sk sk sk sk sk sk sk sk s	Providing and erecting in position low/ full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
b) Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm.  18 Providing and erecting in position side cabinet units with shutters of approve size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade. Shutters will	b) CL 17 Proof she special she special she she she she she she she she she she	DOOR CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:- Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
b) Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm.  18 Providing and erecting in position side cabinet units with shutters of approve size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade. Shutters will	b) CL 17 Proof she special she special she she she she she she she she she she	DOOR CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:- Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
b) Door  CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm.  18 Providing and erecting in position side cabinet units with shutters of approve size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Part edges of block board shall be finished with two coats of synthetic enamel paint of approved shade. Shutters will	b) CL 17 Proof she special she special she she she she she she she she she she	DOOR CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:- Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or	Sqm,	+		
CUPBOARDS / STORAGE CABINETS / TABLESIDE UNITS:-  17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick BWP grade block board including intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door	CL 17 Pro of she spoot steed of She can will ske a) 18 Pro ap ap ap at two fins fam two she can will ske ap ap ap ap ap ap ap ap ap ap ap ap ap	CUPBOARDS / STORAGE CABINETS / TABLE SIDE UNITS:- Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications: hutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or				
17 Providing and erecting in position low/ full height Storage cabinet Made of 19 mm thick 8WP grade block board including Intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 750 mm high and of 19mm thick  BWP grade block boards including intermediate shelves as per drawing/ Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	17 Proof shows spoon steed of showing skeed showing skeed shows a showing shows a showing skeed shows a showing shows a showing shows a show a	Providing and erecting in position low/full height Storage cabinet Made if 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or				
of 19 mm thick 8WP grade block board including Intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished 5. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 2.32  b) Maximum 400mm deep x 200mm high amade of 19mm thick approved shade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	of ships shi	of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or			·	
of 19 mm thick 8WP grade block board including Intermediate shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutter faces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished 5. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 2.32  b) Maximum 400mm deep x 200mm high amade of 19mm thick approved shade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	of ships shi	of 19 mm thick 8WP grade block board including intermediate helves as per direction, lockable shutters etc. conforming to following pecifications:  hutterfaces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or				
shelves as per direction, lockable shutters etc. conforming to following specifications:  Shutterfaces shall be finished with 1mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirling duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm.  2.32  b) Maximum 400mm deep x 750mm high square for thick shade all as directed.  a) Maximum 400mm deep x 750mm high made of 19mm thick approved shade saying finistructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block boards hall be finished with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Primer faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	sh sp sh sp sh sp sh sh sh sh sh sh sh sh sh sh sh sh sh	helves as per direction, lockable shutters etc. conforming to following pecifications: hutterfaces shall be finished with 1 mm thick laminate of same or ombination shades as per instructions with polished white or				
Specifications:  Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm.  2.32  b) Maximum 400mm deep x 750 mm high  Sqm.  7 Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick awp grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	sp. Sh. coo sto te: of Sh. car wi sk. a)  18 Pro ap BV ins ian tw	pecifications: hutterfaces shall be finished with 1 mm thick laminate of same or ombination shades as per instructions with polished white or			] ]	
Shutter faces shall be finished with 1 mm thick laminate of same or combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 750 mm high  Sqm. 5qm.  18 Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm  Iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. paint of approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	street st	hutterfaces shall be finished with 1 mm thick laminate of same or ombination shades as per instructions with polished white or				I
combination shades as per instructions with polished white or steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm. 2.32  b) Maximum 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with spolished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	store text of shape shap	ombination shades as per instructions with polished white or			1	1
steam beech wood (6mm thick) edge lippings and 100mm high teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm.  2.32  b) Maximum 400mm deep x 2100 mm high  Sqm.  7 Sqm.  2.32  b) Maximum 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	stotetes of Sh (car with Sk (ca	·		1		
teak wood skirting duly polished/ painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm. 2.32  b) Maximum 400mm deep x 750mm, high made of 19mm thick approved block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	te: of Sh can wi Sk a) b) 18 Pn ap BV Ins Ian tw			1	I	1
of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Froviding and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	of Sh car wi Sk a)  b)  18 Pro ap BV ins ian tw			F	· ·	
Shutters will be hung by auto-closing hinges, locks, magnetic door catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  O  Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	Sh car wi Sk a)  b)  18 Pro ap BV ins ian tw	_ ,, ,	1	1	· .	l
catcher and satin finished S. S. handles etc. of approved make. (Payment will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  O  Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	b)  18 Properties of the second secon	- · · · · · · · · · · · · · · · · · · ·		1		I
will be on the area of cabinet face).  Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  O  Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	b)  18 Properties of the second secon		1			1
Skirting: 100mm high laminate of approved make & shade all as directed.  a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  Sqm. 0  Sqm. 2.32  18 Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  8WP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	b)  18 Properties of the second secon	**	i	l		l
a) Maximum 400mm deep x 750 mm high  Sqm. 2.32  b) Maximum 400mm deep x 2100 mm high  O  Sqm.  18 Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	b)  18 Pro ap BV Ins Ian tw	vill be on the area of cabinet face).		1	I	1
b) Maximum 400mm deep x 2100 mm high  Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	18 Pro ap 8V Ins Ian tw	kirting: 100mm high laminate of approved make & shade all as directed.		1	I	
b) Maximum 400mm deep x 2100 mm high  Froviding and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	18 Pro ap 8V Ins ian tw	) Maximum 400mm deep x 750 mm high		1		i
b) Maximum 400mm deep x 2100 mm high  Froviding and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	18 Pro ap 8V Ins ian tw			I		I
Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	18 Pro ap 8V Ins Ian tw		Sam.			ļ
Providing and erecting in position side cabinet units with shutters of approx size of 400mm deep x 750mm, high made of 19mm thick  BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	ap 8V Ins Ian tw	Maximum 400mm deep x 2100 mm high		0		İ
approx size of 400mm deep x 750mm, high made of 19mm thick BWP grade block boards including intermediate shelves as per drawing / Instructions. Exposed surfaces shall be finished with 1.00mm Iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door	ap 8V Ins Ian tw		Sqm.	<u> </u>	<u> </u>	
BWP grade block boards including Intermediate shelves as per drawing/ Instructions. Exposed surfaces shall be finished with 1.00mm Iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	av ins ian tw			1	<b>'</b>	
Instructions. Exposed surfaces shall be finished with 1.00mm laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door	ins fan tw	pprox size of 400mm deep x 750mm, high made of 19mm thick		1		!
Instructions. Exposed surfaces shall be finished with 1.00mm Iaminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door	ins fan tw	WP grade block boards including Intermediate shelves as per drawing /	' <b>l</b>			
laminate of approved shade and make. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	fan tw		!			
two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	tw	•	1	1	!	
coat of primer. Free edges of block board shall be finished with polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door		**	1			
polished white or steam beech wood half round moulds (out of 20 x 20 mm sections). Inner faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	1 100	• • • • • • • • • • • • • • • • • • • •	Į	l	[	l
20 mm sections). Inner faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door	]	· -	1	1	<b>l</b>	!
synthetic enamel paint of approved shade & quality over a coat of primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade.  Shutters will be hung by auto-closing hinges, locks, magnetic door			1	1		
primer, painted as directed. Inner faces of cabinet including shutters shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door						
shall be painted in approved shade. Shutters will be hung by auto-closing hinges, locks, magnetic door		vilulenc enamel basit of abbloxed snade & obasity over a coat of	1			
Shutters will be hung by auto-closing hinges, locks, magnetic door			1	1		
		rimer, painted as directed. Inner faces of cabinet including shutters	1			
1 leatcher and satin finished S. S. handles etc. of annocoved make 1 1 1 1		rimer, painted as directed. Inner faces of cabinet including shutters hall be painted in approved shade.				l
· · · · · · · · · · · · · · · · · · ·		rimer.painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door	]	1	]	]
Skirting: 100mm high laminate of approved make & shade all as directed.		rimer painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make	i	ŀ		Ī
Quoted rates shall include cost of necessary hardware, viz handles,	Qu	rimer, painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed.				
locks with keys in duplicate, etc. (Actual face area will be measured	loc	rimer painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make		1		
(for payment purpose.)(to be put on table's side)		rimer, painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shalf include cost of necessary hardware, viz handles,		1	l	1
		rimer, painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shalf include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured		1		
		rimer, painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shalf include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured				
	1	rimer, painted as directed. Inner faces of cabinet including shutters half be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shalf include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured				
		rimer, painted as directed. Inner faces of cabinet including shutters hall be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shall include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured or payment purpose.) (to be put on table's side)				
		rimer, painted as directed. Inner faces of cabinet including shutters hall be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. luoted rates shall include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured or payment purpose.) (to be put on table's side)	<del></del>	<del></del>	-	
a Credenza 3'-0" x 2'-6")(elevation area calculation) Each 0	TA	rimer, painted as directed. Inner faces of cabinet including shutters hall be painted in approved shade. hutters will be hung by auto-closing hinges, locks, magnetic door atcher and satin finished S. S. handles etc. of approved make kirting: 100mm high laminate of approved make & shade all as directed. Quoted rates shall include cost of necessary hardware, viz handles, ocks with keys in duplicate, etc. (Actual face area will be measured or payment purpose.) (to be put on table's side)  redenza 3'-6" x 2'-6") (elevation area calculation) redenza 3'-0" x 2'-6") (elevation area calculation)	<del></del>	<del></del>		



19				_	
1	Providing and erecting in position tables as per drawing and	i		Ţ <u></u>	
ļ	conforming to the following specifications:	l l	Į.	Į.	ļ
i	Structure of 19mm thick block board for sides, top and modesty	1	[	ľ	
	panel, finished with 1.00 mm thick laminate of approved shade and	1		i	
	make Including drawer-cum-cabinet unit, CPU Trolley, modesty panel,	I	ĺ	ļ	]
1	tea tray ,wire managers, 450mm long key board trey, hardware and	[	i	1	
1	accessories etc complete. All exposed edges of block board are to be	ì	)	1	}
i	provided with helf seved seet word weldings of plots posts are to be		ł	1	1
l	provided with half round teak wood moldings, duly polished.	Ī			
1	Inner faces shall be painted with two coats of synthetic enamel paint	ł		1	ľ
1	of approved shade & quality over a coat of primer.	ţ.	ļ	<b>,</b>	4
	Rate to include charges for brass hardware fittings as well as fixtures like	l .		1	Į.
1	sliding gear for drawers of 'Earl Behari' or equivalent approved make.		ľ		ſ
	Note:-Size/quantity to be considered as per approved layout/sitting	ļ .	Ì	[	
Į	plan/staff strength & site requirement.) Lamianate pasting	t	Į	Į	Į.
1	pattern /design as per banks design guideline/detail/reference.	ŀ	]		1
	I			ļ	
			ľ		
1	I aminosto parting entropy Mostan as Last - day.	<del> </del> _	<del> </del>	<del></del>	<u> </u>
)	Lamianate pasting pattern /design as per banks design	1	)	)	)
<b></b> _	guideline/detail/reference.		<u> </u>	<del> </del>	
<b></b> -	a) Approx size 1830 x 915 x 750 mm (6.0'x 3.0'x 2.5')	Each	1		
<u></u> _	b) Approx_size	Each	2		
20	Supply and erecting wall mounted customer writing ledge of approx, size	<u> </u>			
	1200x230mm, top made of 12mm thick float glass and sides/bottom	1	I		
ſ	etc., made of 19mm thick BWP grade block board finished with 1mm		ļ		
i	thick laminate of approved shade and quality, inner faces shall be painted	ļ			
	· · · · · · · · · · · · · · · · · · ·		,		
]	with two coats of synthetic enamel paint of approved shade & quality over		!		
ĺ	a coat of primer. Rate to include making of suitable nos. of boxes	l .			
	of suitable sizes to keep different types of slips/leaflets etc.	<b>i</b>			
	finishing edges with				
ነ ነ	6mm thick polished steam beach wood lipping.	<b>`</b>	i '	'	
i	•	Each	1		
21	Supplying and erecting cheque drop box / suggestion box (over all size				
	400mmx150mmx600mm) made of 19 mm thick BWP grade ply board	1			
(	and curved portion at top made out of 90mmx90mm C.P. teak/steam	Į I			1
	beach wood section. A slit opening of 10mmx150mm is to be	<b>!</b>			
	• -				
	provided at the top of the box. An openable shutter of				
	259mmx262mm size made of 19 mm thick BWP grade block board is to be	i i			
1	provided. The entire exposed timber surface including all free edges is	]	ľ	1	
	to be finished with 1mm thick laminate sheet of combination shade, inner				
	to be missico with thick familiate sheet of combination shade, higher				
	faces shall be painted with two coats of synthetic enamel point of				
	faces shall be painted with two coats of synthetic ename! paint of approved shade & quality over a coat of primer. Rate to include			5 5 5	
	faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc.			5 5 5	
	faces shall be painted with two coats of synthetic ename! paint of approved shade & quality over a coat of primer. Rate to include				
	faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc.	Engh	,	5 5 5 5 5 5	
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.	Each	2		
22	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having	Each	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm	Each _	22		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be	<u>Each</u>	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm	Each			
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be	Each	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour	Each _	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical bilinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain	Each _	. <u>2</u>		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical bilinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer	Each	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical bilinds: Providing & fixing levelor 10mm vertical bilinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spacing. The top rail should be fixed on bracket of 14 SWG	Each	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast color with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spracing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per		2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast color with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spracing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per	Each	2		
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spacing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per approved design and direction of the Architect.				
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spacing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per approved design and direction of the Architect.				
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spacing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per approved design and direction of the Architect.				
	faces shall be painted with two coats of synthetic enamel point of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.  vertical blinds: Providing & fixing levelor 10mm vertical blinds having top rail 39mmX34mm high with wall thicknessof 1.2mm having 25mm decorative insert. Control unit shall be of Derlin. Plastic runner shall be moulded from Derlin plastic with artification head rail & the top end of the louver fabric shall be polyster viscose/polyster yarn dyed in fast colour with or without protective coating on louvers with chemical for stain resistance and soil repetancy and shall have GI weight and steel/polymer ball chain for spacing. The top rail should be fixed on bracket of 14 SWG galvanized spring steel fixed firmly on walls by nylon plug and screw as per approved design and direction of the Architect.				

Notes:-

Contractor to Note that:-



- a) Footrests & CPU stand to be provided (laminated) with each table / counter without any extra charges, @ 1 per person.
- b) Extra members, wherever required for stability / otherwise, to be provided with the required finish without ant extra charges

	List of Approved Makes of Materials		
SNO	Description of material	Particulars	Make /Details
1	Plywood/Block board (BWR)	6mm, 9mm, 12mm,	Kitply / Green panel / /Century/
2	Laminate		Greenlam/Merino/
1 1		1	NewmiKa/Archidiam
1 1	: :	1.0 mm	<b>,</b>
3	Glass	6mm, 8mm, 10mm,	Modi /Saint gobain
4	Vertical blinds		Vista, Universal
5	False ceiling		USG Boral/Saint gobain/Western
6	Flush door shutter		Green ply /Century ply/ kilply
7	Veneer	4 mm	Century/ Green/
8	Lock/Door Closures/Hardware		Godrej/Ebco/Hardwyn
9	Screws		GKW / Malle fold /Netfold
10	Paints		ICV Burger/ Nerolac/ Aslan
11	AC grill		Air products/Omicron/Patrawala
12	Channels , Slides, Fitting		Ebco/Hettich/ Godrei/dorset
_13	Aluminum Section (If Required)	Powder coated finish	JindaVindal
_14	Floor springs		Hyper/ Dorma/Hardwyn/dorset
15	Melamine Polish		Asian paint, Nerolac
16	Wood preservatives		Woodguard, PCI, Black Japan
17	Calcium Silicate Board	12mm	Hillox/ USG Boral
18	Adhesives		Fevicol (SH), Mahacol, Araldite.
. 1			l



Α	MAIN WOKS	AMOUNT (RS.)
1	INTERIOR WORK BRANCH	
2	FIXTURES WORK BRANCH	
3	ATM INTERIOR WORK	nil
4	ATM FIXTURES WORK	nil
<del></del> -	TOTAL	





