

**BILLS OF QUANTITIES OF FURNISHING WORK OF INDIAN BANK  
AT C.G. ROAD BRANCH.**

Sr. No.	Description	Quantity	Rate	Unit	Amount																				
[A]	FURNISHING WORK FOR BRANCH																								
1	CASH COUNTER																								
	Supplying, fixing and keeping in position single window counter complete as per design, and drawing made out of 18mm thick commercial plywood of approved make, complete with 3/4" th. C.P. Teak wood lipping on all edges wherever required.																								
	The cost shall be inclusive of S & F of a drawer and shelf unit with 18mm thick commercial plywood and with Godrej/ equivalent lock in drawer and shelf unit. The cost shall also be inclusive of the following.																								
[a]	size :																								
	<table><tr><td>Description:</td><td>L</td><td>B</td><td>Ht.</td></tr><tr><td>Writing Top</td><td>5'-0"</td><td>2'-6"</td><td>2'-6"</td></tr><tr><td>Transaction Top</td><td>5'-0"</td><td>1'-0"</td><td>3'-9"</td></tr><tr><td>3 Drawers with pegion hole</td><td>2'-0"</td><td>1'-3"</td><td>2'-0"</td></tr><tr><td>Computer key Board</td><td></td><td></td><td></td></tr></table>	Description:	L	B	Ht.	Writing Top	5'-0"	2'-6"	2'-6"	Transaction Top	5'-0"	1'-0"	3'-9"	3 Drawers with pegion hole	2'-0"	1'-3"	2'-0"	Computer key Board							
Description:	L	B	Ht.																						
Writing Top	5'-0"	2'-6"	2'-6"																						
Transaction Top	5'-0"	1'-0"	3'-9"																						
3 Drawers with pegion hole	2'-0"	1'-3"	2'-0"																						
Computer key Board																									
	Supplying and fixing metal key Board of Ebco Earl Bihari make in counter as per design and instructions.																								
	Providing 18 mm thick plywood with T.W beading self for CPU stand below counter																								
[b]	Working top shall be finished with laminated sheet 1.0 mm thick of approved make, natural Teak wood Texture/ choice shade laid with grains parallel to the length of the counter.																								
[c]	Transaction top finish as in (b) above.																								
[d]	Front pannel and front projection shall be finished with laminated sheet 1.0 mm thick of choice shade approved by Architects/Bank and fixed on 18mm thick commercial plywood with horizontal and vertical grooves as per design.																								
[e]	Skirting : 6" high Laminated sheet 1.0mm thick for skirting shall be glued on to pannel of [in front and rear] 18 mm thick commercial plywood of approved make ht.																								
[f]	The projecting portion shall have 9" deep with vertical supports as requored made of 18mm thick commercial plywood of approved make.																								
[g]	Foot rest of 3" x 1.5" in C.P. Teak wood.																								

Sr. No.	Description	Quantity	Rate	Unit	Amount
[h]	All wood work shall be wax/spirit polished over a coat of linseed oil to a smooth and uniform finish of choice colour and shade.				
[i]	All fittings like brass knobs/ S.S Godrej multipurpose locks to each drawer and cabinet doors, piano hinges, ball catcher stopper etc.	5		RFT	
<b>1[a]</b>	<b>SINGLE WINDOW COUNTER</b>				
	- Do - as in item No. 1 but with transaction top.				
	<p>Description:            L            B            Ht.</p> <p>Writing Top            5'-0"            2'-6"            2'-6"</p> <p>Transaction Top    5'-0"            0'-9"            3'-0"</p> <p>3 Drawers with pegion hole            2'-0"            1'-3"            2'-0"</p> <p>Computer key Board</p> <p>Supplying and fixing metal key Board of Ebco Earl Bihari make in counter as per design and instructions.</p>	5		RFT	
<b>1[b]</b>	<b>LOW HEIGHT COUNTER</b>				
	- Do - as in item No. 1 but with transaction top.				
	size :				
	<p>Description:            L            B            Ht.</p> <p>Writing Top            5'-0"            2'-6"            2'-6"</p> <p>Transaction Top    5'-0"            0'-9"            3'-0"</p> <p>2 Drawer &amp; 1 shutter storage cabinate (As per design and instructions)</p> <p>Computer key Board</p> <p>Supplying and fixing metal key Board of Ebco Earl Bihari make in counter as per design and instructions.</p>	30		RFT	
<b>1[c]</b>	Providing and fixing counter having width of 2' 3" using 18mm thick commercial plywood for Top and verticale support, Providing drawer storage unit at every 4'6" length one Drawer & one Shutter storage cabinate and Key board of metal of Ebco Earl Bihari make in counter as directed complete. Top and sides of the counter shall have 1.0 mm thick laminate. All the surface not laminated shall be polished/painted complete as directed (System Room).	10		RFT	

Sr. No.	Description	Quantity	Rate	Unit	Amount
1[d]	<p>PROVIDING AND FIXING TABLE TOP ONLY</p> <p>Table top 2'-0" width shall be made for 18mm thick commercial ply wood + 4" wide 18 mm plywood on edge with 36 mm Steam beach edge beading with 1.0mm th laminate with necessary wooden support framing . Table top shall be supported on Low height partition as directed. All the surface without lamination shall be polished.. All exposed edges of plywood shall have polished steem beach beading. etc complete as directed</p>	10		RFT	
2	<p>Providing and fixing both sides laminated partition using 2" x 1 1/2" Teak wood members in a grid of 2'-0" x 2'-0" fixing 6mm th commercial plywood and 1.0mm laminate on both sides of skeleton, providing 5.0/8.0 mm th float glass as directed in the partition. Providing door shutter using 5" x 1 1/2" th steam beach member for Styles and rails and fixing 8mm th glass in between as per design 4" Long 3 Nos stainless steel hinges shall be provided 8.0 mm th glass shall be provided in door shutter as directed. Godrej Mortice lock shall be provided in door shutter steam beach Beading glass. All visible members if not laminated shall have melamine polished as directed.</p> <p><b>Note :Rate shall be same for solid partition</b></p>	200		SFT	
2[a]	<p>Providing and Fixing One side ply wood and laninate partition.above false ceilling</p> <p>Providing and fixing one sides laminated partition using 2" x 1 1/2" Teak wood members in a grid of 2'-0" x 2'-0" fixing 6mm th commercial plywood and 1.0mm laminate on one sides of skeleton.. All visible members if not laminated shall have melamine polished as directed.</p>	40		SFT	

Sr. No.	Description	Quantity	Rate	Unit	Amount
3	Providing and Fixing low height partition using 2" x 1 1/2" member in grid of 2'-0" x 2'-0" fixing 6 mm thick commercial plywood of approved brand on both side of T.W skeleton fixing 1.0 mm thick laminate of approved shed on both sides and. Fixing steam beach member of 2 1/2" x 1" T.W. members in a shape as directed shall be fixed on all exposed edges. Fixing 12 mm th free glass as directed steam beach beading glass. Applying melamine polish on exposed steam beach members as directed complete., Providing 12mm th glass with polish edges shall be provided as directed.	300		SFT	
3[a]	Providing and fixing Isolated flush door shutter as follows.  Using 4" x 2" Steam beach members and 31mm th waterproof flush shutter with 5/8mm th glass as per design and instruction. Providing Steam beach member on periphery for fixing 4" long hinges 3 Nos. Fixing 1.0mm th laminate on both sides. Providing S.S Handles, Godrej Mortice Lock, stoppers, doorstop & polishing to exposed edges directed complete.	25		SFT	
4	Providing and laying pannelling on pillars and walls having 6mm th commercial plywood and 1.0mm th laminate fixed on wall & pillars with T.W. framing of 2" x 1" at 2'-0" c/c bothways or 18mm thick commercial plywood with laminate paneling on wall & pillar etc. complete as directed.	300		SFT	
5	Providing and fixing Glass partition on Cash counter/ SW Counter front side top as follows.  12mm th glass shall be fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Making necessary cut outs in glass, all edges of the glass touching to the adjoining componants shall be diamond polished,the top open edge shall have pencil round moulding as directed complete.	20		SFT	
5[a]	Providing and fixing Glass partition on Low Height counter front side top as follows.				

Sr. No.	Description	Quantity	Rate	Unit	Amount
	12mm th glass shall be fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Making necessary cut outs in glass, all edges of the glass touching to the adjoining componants shall be diamond polished,the top open edge shall have pencil round moulding as directed complete.	40		SFT	
6	Suppling and providing Table as per the following description Size 6'-0" x 3'-0". Table top shall be made for 18mm thick commercial ply wood with 1.0mm th laminate with necessary intermediates support. Table top shall be supported by 18mm thick commercial ply wood with wooden framing 1.0mm thick laminate. Storage cabinate of 1'-3" x 1'-6" x 2'-0" shall be provided using 18mm thick commercial ply wood having 3 Nos drawers as directed with slidding channel of Ebco makle ,Godrej lock / S.S. Handle. Computer Key board of metal of ebco Earl Bihari make shall be provided. Exposed surfaces of the cabinate shall have 1.0mm th lamiante. Foot rest of 1 1/2" x 3" T.W members shall be provided. All the surface without lamination shall be polished. Apron made from lamiantion shall be provided in a pattern as directed. Table shall have stand for keeping CPU and cable Manager shall be provided in table top.	1		NO	
6[a]	- do- as above but Assisiant Manager / Advance Officer Table size 5'-0"x2'-6" with storage unit 2 Nos drawer and 1 no shutter	2		NO	
6[b]	- do- as above but size 4'-6"x2'-6" without drawer storage unit (Officer Table)	4		NO	
6[c]	- do- as above but size 4'-0"x2'-3" without drawer storage unit (Assistant Table)	2		NO	

Sr. No.	Description	Quantity	Rate	Unit	Amount
7	Supplying and providing side cabinet for keeping computer and printer size 3'-3" Length 1'-4" Width and 2'-6" height. Having partly openable and partly drawer shutters as directed. Cabinet shall be made from 18mm thick commercial ply wood with 1.0mm thick laminate back shall be made from 6mm th commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with 1.0mm th laminate and "Godrej" lock. Drawer shall slid on slidding channel, all the surfaces of the cabinet without laminate shall have polish/paint as directed. Rate includes all necessary provisions for installing computers. for Manager	1		NO	
7[a]	- Do - as in above but size shall be 3'-0" x 1'-4"x 2'-6" ht Partly Drawer / <b>Partly Openable Shutter</b>	8		NO	
7[b]	Supplying and providing side storage cabinet as per following description.  Size : Depth 1'-4" ht. 2'-6" /7'-0"having openable shutter as directed. Cabinet shall be made from 18mm thick commercial plywood for verticale, shelves, shutters and 6mm commercial plywood for backing with 1.0 mm thick laminate on all exposed surface and polishing/painting for internal surface with verticale (at 3'-0" c/c) shelves at 1'-3" c/c shutters openable in 18mm thick commercial plywood with all S.S hinges, towers bolts, powder coated handle, ball catches, S.S godrej multi purpose lock compltd. Edges to be finished with teak wood lipping etc. including all incidental etc. complete. [Filling storage Cup Board]	300		SFT	
7[c]	Providing and fixing Electric cup board using 18mm thick commercial ply wood with 1.0 mm thick laminate on outer side polishing/painting on internal surface with Godrej lock handle,ball catches complete as directed depth of cup board 1'-4".	35		SFT	
7[d]	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" T.W members for frame, 18mm Tk Commercial plywood with 1.0mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All the surface shall be polished/ enamel paint as directed complete.	15		SFT	

Sr. No.	Description	Quantity	Rate	Unit	Amount
8	Providing soft board for pin up using 6mm thick commercial plywood on back side and 12mm th soft board on front. Fixing cloth of selected design of Basic rate of Rs. 150 per mt. T.W member shall have polish as directed complete.	9		SFT	
9	CUSTOMER WRITING DESK Size 3'-0" x 1'-0" x 6" ht. Sides and bottom shall be made from 18mm thick commercial ply wood with 1.0mm thick lamiante at inner & outer surface. Top shall be made from 12mm th glass with bevelled and polished edges making diff divisions by 12mm th glass for slips or forms as directed complete.	1		NO	
10	Providing and fixing of letter box cum suggestion box of size 1' 3"x1'-0" x 3'-6" ht. Box shall be made from 18mm thick commercial plywood with 1.0mm th laminate, back shall be 6mm th commercial plywood shutter shall be made from 18mm thick commercial plywood with 1.0mm th laminate and Godrej lock, The top shall have a slit for dropping latter, all the surface of the box without laminate shall have polish as directed.	1		NO	
11	Providing and fixing "EG/Godrej" or equivalent make door closure.	6		NO	
11[a]	Providing and fixing heavy duty Floor Spring of Avertie or euivalent make	3		NO	
12	Supplying and fixing verticale Blind of Approved made like Trans or Equivalent make with selected fabric of approved design and shed.	405		SFT	
13	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surfaces as per drawing & direction with all labour & materials to the satisfaction of the Site Engineer as per manufacturer's specification.	100		SFT	
14	Supply office stool 1'-0" x1'-0" 1'-4" ht to be made of Teak Wood frame 2" x 2" with Square Tapered legs to be Provided with 19 mm thick Commercial Ply wood with laminated top. Including polish/paint complate as directed.	2		NO	
15	ALUMINIUM WORK				

Sr. No.	Description	Quantity	Rate	Unit	Amount
[a]	<b>MAIN ENTRANCE DOOR</b> Providing & fixing powder coated Aluminium main entrance door having frame of 101.6 x 44.5 x 2.82 mm th weight 2.236 kg/Rmt shutter shall be made from style 85.0 x 44.45 x 3 mm th weight 2.05 kg/Rmt ,Top rail 95.25 x 44.45 x 2mm th weight 1.519 kg/Rmt, Bottom rail 150 x 44.45 x 2.90 mm th weight 2.472 kg/Rmt beading clip 19 x 17.20 mm weight of 0.124 kg/Rmt 8mm th float glass as directed. Rate shall include copper door lock of approved make S S Handles of approved design, concealed tower bolts, Neoprin Rubber gasket, fixing with all colour as directed aluminium section shall be Jindal make of equivalent section of Hindalco. Aluminium frame shall have in built projection for door stopper with groove for rubber gasket. Detail as per architects drawings.				
	[I] OPENABLE PORTION	67		SFT	
	[II] FIXED GLASS PORTION	65		SFT	
[b]	<b>GLASS PARTITION FOR THE FRONT SIDE (FIXED)</b> Supplying and fixing Glazing using powder coated aluminium section and 12 mm thick plain glass( Modi Float Glass or Equivalent) Size of section shall be 100 mm x 45 mm x 2.80 mm thick including necessary aluminium glazing clips, rubber gaskets, silicone clear sealant between the glass and other necessary hardware etc. Making necessary cut out in glass complete as per design.				
		40		SFT	
<b>TOTAL COST OF 'A'</b>					

**(SEAL & SIGNATURE OF CONTRACTOR)**