

BILL OF QUANTITY FOR FURNISHING WORKS					
FOR INDIAN BANK BRANCH AT MUNSHIGANJ					
NOTE :					
1. For doors lowprofile mortice lock 240 no. 1936 with imperial handle of anodised brown color					
2. Locks of drawers other than cash should be of Premium multipurpose lock no.5131					
3. Locks for cuboards doors - for left handed doors:door no. 5011 & for right handed 5012					
4. Floor Spring for the doors should be of floor spring no. 4102					
5. Locks for Cash drawers should be multilatch no. 1624					
6. Hydraulic door 2 speed no. 4159					
7. Cash Cabin & Single Window should have ultra twin bolt no. 4950 / 4951 with inside opening.					
8. All types of hardware to be of Godrej make					
9.All Items to include fire Retardant anti bacterial paint from Nav air international FR (Viper) (white colour)as per manufacturers specification.					
S.No.	Description	Quantity	Unit	Rate	Amount
1	LOW HEIGHT PARTITION GLAZED Providing and fixing in position Double skin partition 6'-6" height. The underframe of salwood 2.5" x2.5" at 2'-0" c/c (Max.)The underframe to be finished with 6mm urea bonded ply on both sides and finished with 1.0mm laminate of approved colour and shade as per approval of the Architect. The partition to include 12mm, thick Modi Float glass with etching from 3'-9" to 6'-6" on the sides and back with all hardware etc. All exposed edges to be covered with teak wood Beading in places as per design duly melamine polished inclusive of all materials,hardware, night latches, labour, T&P, taxes, levies, etc. completed to the satisfaction of the bank & drawing. The partition yto include space for conduits for U.P.S, LAN, Electrical wiring etc. as per the satisfaction of the Architect.All exposed edges to be machine cut and Polished . All edge to edge Glass joint to be machine polished and sealed with silicon sealant.Teak wood Beading of size 3.5" x 2" on the top member of the partition including door opening dulg TRAY properly finished with teak wood bead				
	All exposed woodwork to be melamine polished and all underfaces to be duly enamel painted with proper primer base.Cash Cabin Partition should have ultra twin bolt no. 4950 / 4951 with inside opening All hardware to be of Godrej make.Providing & fixing of hydraulic door closure with quality of two speed No-4159 .	125	Sqft		
2	LOW HEIGHT PARTITION SINGLE WINDOW including door Providing and fixing in position partly glazed half height double skin partition (5'-6" high). The underframe of kailwood 2" x2" at 2'-0" c/c (Max.)..The underframe to be finished with 6mm urea bonded ply on both sides and finished with 1.0mm laminate of approved colour and shade as per approval of the Architect. The partition to include 12mm thick Modi Float glass with etching from 2'-6" to 4'-6" on the sides and back with all necessary hardware and night latches etc. as per design. All exposed edges to be covered with teak wood Beading in places as per design duly melamine polished inclusive of all materials,hardware, night latches, labour, T&P, taxes, levies, etc. completed to the satisfaction of the bank & drawing. Item includes teak wood lipping of size 3" x 1.5"All unexposed edges to be finished with Enamel paint with proper base of Primer.Single Window Partition should have ultra twin bolt no. 4950 / 4951 with inside opening All hardware to be of Godrej make.The partition to have necessary cash passing TRAY properly finished with teak wood beading as per approval .				
	Providing & fixing of hydraulic door closure with quality of two speed No-4159	145	Sft		
3	GLAZING ON FRONT SIDE OF THE CASH CABIN Provision & Fixing 12mm float glass (with etching) in front of cash cabin with teak wood beading including cutout for passing currency as/ details from a height of 3'-9" to 6'-6". All the edges of the glass to be machine polished.This would also include cutout for talking.	15	Sqft		
4	MAIN DOOR WITH FIXED WINDOW GLAZING Supplying and fixing of main door and window made out of 8 mm thick clear float glass (door size 5'-0" x 7'-0"). Powder coated Aluminium frame (only on Top and Bottom of the door), of approved make (20 microns) made out of 100mmX 45mmX 2.5mm with all necessary accessories like beadings screws raul plugs including supplying and fixing of heavy duty floor springs of approved make. Supplying and fixing of 12 mm thick plain glass (modi) , 230 mm height SS door handle and also including etching, cost of labour etc. complete as per satisfaction of the Architect.	110.00	SQFT		
5	SINGLE WINDOW COUNTER Providing and fixing into position Single window 2'-6" wide Counters made up of Phenol bonded 19 mm thick commercial board covered with 1.0mm thick laminate on the front and sides.The table top to be covered with polished Red / Black Granite with moulded egdes as per the approval of the Architect.				

	The front façade to have 19 mm thick Phenol bonded commercial board with 1.0 mm thick laminate in two colours as shown in the drawing and approved by the Architect. Each Single Window to have a 12mm float glass (with etching) partition in front of counter with teak wood beading as per approval of the Architect and as per Standards of the Bank. The edges of the glass to be machine polished. 1 Drawers to have divisions for keeping cash as per Banks Specifications.Provision of footrest to be made as earlier specified. .All Drawers to have Godrej locks as per direction of the Architect .Locks for Cash drawers should be multilatch no. 1624. Locks of drawers other than cash should be of Premium multipurpose lock no.5131				
	Every counter shall be provided with a key board tray, a drawer which shall slide on tray system provision (sliding mechanism), and a cabinet with a shutter below W-375, H-750mm. Keyboard tray to be made of 19 mm thick commercial board laminated. Drawers and a cabinet with a shutter below W-375mm, H-750mm, Depth- 500mm. shall consist of 12 mm thick commercial board for bottom, sides and back of 19 mm thick phenol bonded commercial board with laminate in front.				
	All the units shall be provided with all the necessary hardware as approved by the Architect such as knobs, handles, Godrej cabinet locks, sliding mechanism as approved by the Architect, Magnetic Catchers Piano brass hinges etc. All unexposed surfaces to have synthetic enamel paint with primer, all complete as per detailed drawing, specifications and directions of the engineer in charge.Footrest in teak wood as per drawing. All exposed edges to be finished in teak wood moulding or lipping in clear melamine polish.	5	R ft		
6	CUSTOMER CARE COUNTER				
	Providing and fixing into position Customer Care Counters 2'-6" wide made up of Phenol bonded 19 mm thick commercial board covered with 1.0mm thick laminate on the front and the sides in two colours as shown in the drawing.The table top to be covered with polished Red Granite with edges moulded as per the approval of the Architect.The storage unit shall consist of drawers and openable shutters in 19 mm thick phenol bonded commercial board with 1.0 mm thick laminate as shown in the drawing.				
	Every counter shall be provided with a key board tray, a drawer which shall slide on tray system provision (sliding mechanism), and a cabinet with a shutter below W-375, H-750mm, Depth-500mm.Keyboard tray to be made of 19 mm thick commercial board laminated. Drawers and a cabinet with a shutter below W 375mm, H-750mm, Depth- 500mm. shall consist of 12 mm thick commercial board for bottom, sides and back of 19 mm thick phenol bonded commercial board with laminate in front.				
	All the units shall be provided with all the necessary hardware as approved by the Architect such as knobs, handles, Godrej cabinet locks, sliding mechanism as approved by the Architect, Magnetic Catchers Piano brass hinges etc. All unexposed surfaces to have synthetic enamel paint with primer, all complete as per detailed drawing, specifications and directions of the engineer in charge.Footrest in teak wood as per drawing. All exposed edges to be finished in teak wood moulding or lipping in clear melamine polish.Lock of drawers other than cash should be of Premium multipurpose lock no.5131. Locks for cuboards doors - for left handed doors:door no. 5011 & for right handed 5012	17	R ft		
7	REAR STORAGE 2'-6" HEIGHT				
	1'-4" DEEP low height storages. Outer framework i.e. top, sides, shutters, shelving of 19mm thick block board. Back shall be of 8mm thick commercial ply. All surfaces exposed to view to be finished with 1.0mm thick laminate. All edges of the block board shall have Steam beech wood edging of 1/4"x3/4" All shutters shall be provided with lock (1 no. for two shutters), auto closing hinges (2 nos. per shutter), brass catchers, 4" long S.S. brush finish handles, tower boil 4" long, 1 no. Intermediate shelf shall rest on S.S.- studs for adjustable shelving etc. Woodwork protected with melamine polish. Entire surfaces left without lamination to be finished with two or more coats of spirit polish. All complete as per drawing, approval and instructions of the Architect . Measurement will be taken from the front face.Lock of drawers other than cash should be of Premium multipurpose lock no.5131.Lock for cuboards doors - for left handed doors:door no. 5011 & for right handed 5012	37.5	sqft		
8	MANAGER TABLE				
	Size -1.65 m (L)X 0.75 (W)X 0.75 (H) Providing and placing in position table made of phenol bonded 19mm thick commercial board with top front and sides finished in 1.0mm thick laminate in front, top and sides and 6mm thick Modi float glass on top as per design. The table to have teak wood moulding as per design. Every table shall be provided with a key board tray, a drawer which shall slide on tray system provision (sliding mechanism), and a cabinet with a shutter below W-375, H-750mm, Depth-500mm. 450x345 size Keyboard tray to be made of 19 mm thick commercial board laminated. Drawers and a cabinet with a shutter below W-375mm, H-750mm, Depth- 500mm. shall consist of 12 mm thick commercial board for bottom, sides and back of 19 mm thick phenol bonded commercial board with laminate in front.				

	All the units shall be provided with all the necessary hardware as approved by the Architect such as knobs, handles, Godrej cabinet locks, sliding mechanism as approved by the Architect, Magnetic Catchers Piano brass hinges etc. All unexposed surfaces to have synthetic enamel paint with primer, all complete as per detailed drawing, specifications and directions of the engineer in charge. Footrest in teak wood as per drawing. All exposed edges to be finished in teak wood moulding or lipping in clear melamine polish. Locks of drawers other than cash should be of Premium multipurpose lock no.5131. Locks for cuboards doors - for left handed doors: door no. 5011 & for right handed 5012	1	No		
9	SIDE CREDENZA Providing and placing in position side credenza of size 1'-4"x 3'-0" x 2'-6"				
	Outer frame work i.e top, sides, bottom shutters and shelving of 19 mm thick block board. Back of 8 mm ply. 2 Drawers and 2 sliding shutters shall be provided made of 12 mm Ply finished with 1 mm thick laminate. All exposed edges to be finished with teak wood lipping of size 1/4" x 3/4" all complete including locks handles Drawer Slides etc. All wood work with melamine polish. All undersurfaces duly painted in enamel with paper primer base. The Sliding shutters on Rollers with proper sliding mechanism. Locks of drawers other than cash should be of Premium multipurpose lock no.5131. Locks for cuboards doors - for left handed doors: door no. 5011 & for right handed 5012	2	No		
10	WRITING COUNTER Writing Counter of 19mm urea bonded board as/ design with Red granite on 19mm thick Phenol Bonded Commercial Board. The counter to have a notice board at the upper portion and a suggestion counter at the lower portion as per detailed drawing. Vertical Separators for slips to be provided made of 19 mm thick Commercial Board finished with Steam beach Lipping duly melamine polished. The suggestion box to be of 19 mm thick board finished with 1 mm thick laminate. All exposed edges to be duly melamine polished and underfaces duly enamel painter with base primer.	1	pc		
11	NOTICE BOARD INCLUDING CHEQUE DROP BOX ,SUGGESTION BOX Providing and fixing notice board size as required / directed (matching with the panel of the cabin) with operable shutter on the front. Made out of 19mm block board frame and outer frame in 2 1/2" x 1 1/2" teak wood section, concealed hinges, locking arrangement, glass of (5.5mm thick) with rear panel of SITATEX board, covered with fabric of approved shade. (Basic rate Rs. 100/- per mtr, 48" width), fixed to back ply 6mm thick. All complete including melamine polish in stain of required shade. All complete as per approval of the Architect.	1	No		
Grand Total					